Anschreiben Ganslandt

dqrep: Facilitating harmonized data-quality assessments with Stata

Carsten Oliver Schmidt
Stephan Struckmann, Birgit Schauer
Institute for Community Medicine
SHIP/KEF

Take #1
Population-based epidemiologic cohort studies



Photos: © Carsten Oliver Schmidt

Take #1
Population-based epidemiologic cohort studies



Take 1:
Support data collections and statistical analyses more efficiently



Files?
Variables?
Missing data?
Violations?
Distributions?
Associations?

Take 1:
Support data collections and statistical analyses more efficiently



ANALYSIS PERSPECTIVE

Take #2
Make science more transparent

nfdi 4 health



Research: increasing value, reducing waste 2

Increasing value and reducing waste in research design, conduct, and analysis

John P A Ioannidis, Sander Greenland, Mark A Hlatky, Muin J Khoury, Malcolm R Macleod, David Moher, Kenneth F Schulz, Robert Tibshirani

Take #2
Improved information management



ANALYSIS PERSPECTIVE

Analysis perspective
Single survey/examination DQ reporting

```
net from https://packages.qihs.uni-greifswald.de/repository/stata/dqrep
net install dqrep, replace
```

dqrep,

- >60 ados
- pdf, docx reports + result files (spreadsheet + graphs)

Analysis perspective
Single survey/examination DQ reporting - Output

Data quality report

Report created: 13:08:46 14 Jul 202

Report content

- Dataset overview
- Integrity issues and notes
- Descriptive variable overview
- Missing values (Item missingne
- Range violations
- Univariate outliers
- Variance proportion overview
- Overview for single variable
- Change-log for modified variab

Data quality measures overview 1

Primary variables	Missings all %	Nonresponse rate - Item %	Inadmi val
sbp1 Systolic blood pressure 1. measurement (mmHg)	.09%	.09%	

Descriptive variable overview

Primary variables	Levels
sbp1 Systolic blood pressure 1. measurement (mmHg)	125

Missing values (Item missingness)

Primary variables	Permitted jump N (%)	Missing spec. N (%)	M sy
sbp1 Systolic blood pressure 1. measurement (mmHg)	0 (0%)	0 (0%)	

Range violations

Primary variables	Lower inadm. limit (N)	Upper inadm. limit (N)
sbp1 Systolic blood pressure 1. measurement (mmHg)	40 (0)	300 (0)
sbp2 Systolic blood pressure 2. measurement (mmHg)	40 (0)	300 (0)



Formal background: Data quality framework

Universitätsmedizin GREIFSWALD

Dimensions

Integrity | Completeness | Consistency | Accuracy

Domains

- Structural data set error
- Relational data set error
- Value format error
- Crude missingness
- Qualified missingness
- Range and value violations
- Contradictions
- Unexpected distributions
- Unexpected associations
- Disagreement of rep. meas.


Schmidt et al. BMC Medical Research Methodology (2021) 21:63
https://doi.org/10.1186/s12874-021-01252-7

BMC Medical Research Methodology

RESEARCH ARTICLE Open Access

Facilitating harmonized data quality assessments. A data quality framework for observational health research data collections with software implementations in R

Carsten Oliver Schmidt[1*], Stephan Struckmann[1], Cornelia Enzenbach[2], Achim Reineke[3], Jürgen Stausberg[4], Stefan Damerow[5], Marianne Huebner[6], Börge Schmidt[4], Willi Sauerbrei[7] and Adrian Richter[1]

Horizon 2020 Programme

DFG Deutsche Forschungsgemeinschaft

Analysis perspective
Methodological approach

Integrity

Completeness

Consistency

Focus: Data values

Boolean, abs., rel. Frequencies

Boolean, abs., rel. Frequencies

Accuracy

Focus: Variables

Diverse methods, metrics, e.g.:

- Mean, Median, SD, Min , Max
- Intra Class Correlations, Mixed Models
- (Non)-Parametric Regressions
- Outlier Assessments (e.g. Grubbs, Medcouple..)
- Confidence intervals

INFORMATION PERSPECTIVE

Take #2
Improved information management

Universitätsmedizin GREIFSWALD



Take #2
Improved information management



Machine Readibility

e.g. as spreadsheet, ideally some CDM

Improved information management
INPUT



Richter et al. 2019

Improved information management
INPUT – dqrep standard

var_name	varshortlabel	data_type	scalelevel	missinglist	jumplist	refcat	eventcat	limit_hard	limit_hard	limit_soft_	limit_soft_	key_obser	key_devic	key_datet	variablerole	var_order	sourcefilename	segments
id	ID	integer	nominal												idvars	1	SHIP_study	INTRO
exdate	Exam. date	datetime	interval												processvars	2	SHIP_study	INTRO
sex	Sex	integer	nominal			1	2							exdate	controlvars	3	SHIP_study	INTRO
age	Age	integer	ratio					<20						exdate	controlvars	4	SHIP_study	INTRO
obs_bp	Obs. BP	integer	nominal	.d,.t,.v,.z										exdate	processvars	5	SHIP_study	SOMATOMETRY
dev_bp	Device BP	integer	nominal	.d,.t,.v,.z										exdate	processvars	6	SHIP_study	SOMATOMETRY
sbp1	Syst. BP 1	float	ratio	.d,.t,.v,.z				<40	>300	<85	>220	obs_bp	dev_bp	exdate	keyvars	7	SHIP_study	SOMATOMETRY
sbp2	Syst. BP 2	float	ratio	.d,.t,.v,.z				<40	>300	<85	>220	obs_bp	dev_bp	exdate	keyvars	8	SHIP_study	SOMATOMETRY
dbp1	Diast. BP 1	float	ratio	.d,.t,.v,.z				<10	>200	<40	>120	obs_bp	dev_bp	exdate	keyvars	9	SHIP_study	SOMATOMETRY
dbp2	Diast. BP 2	float	ratio	.d,.t,.v,.z				<10	>200	<40	>120	obs_bp	dev_bp	exdate	keyvars	10	SHIP_study	SOMATOMETRY
obs_soma	Obs. Somat.	integer	nominal	.d,.t,.v,.z										exdate	processvars	11	SHIP_study	SOMATOMETRY
height	Heigth	float	ratio	.d,.t,.v,.z				<80	>230			obs_soma	dev_lengtl	exdate	keyvars	12	SHIP_study	SOMATOMETRY
dev_length	Dev. Height	integer	nominal	.d,.t,.v,.z										exdate	processvars	13	SHIP_study	SOMATOMETRY
dev_weight	Dev. weight	integer	nominal	.d,.t,.v,.z										exdate	processvars	15	SHIP_study	SOMATOMETRY
weight	Body weight	float	ratio	.d,.t,.v,.z				<30	>250			obs_soma	dev_weigh	exdate	keyvars	14	SHIP_study	SOMATOMETRY
waist	Waist circum.	float	ratio	.d,.t,.v,.z				<30				obs_soma		exdate	keyvars	16	SHIP_study	SOMATOMETRY
obs_int	Obs. Interview	integer	nominal	.d,.t,.v,.z										exdate	processvars	17	SHIP_study	INTERVIEW
school	Educ. level	integer	nominal	.d,.t,.v,.z		2 3 9	4 5 6 7 8					obs_int		exdate	minorvars	18	SHIP_study	INTERVIEW
family	Marital stat.	integer	nominal	8,9,.z	.j	1	2 3 4 5					obs_int		exdate	minorvars	19	SHIP_study	INTERVIEW
smoking	Smoking	integer	nominal	8,9,.z	.j	0	1 2					obs_int		exdate	minorvars	20	SHIP_study	INTERVIEW
stroke	Stroke ever	integer	nominal	8,9,.z	.j	1	2					obs_int		exdate	minorvars	21	SHIP_study	INTERVIEW
myocard	Myoc. inf. ever	integer	nominal	8,9,.z	.j	1	2					obs_int		exdate	minorvars	22	SHIP_study	INTERVIEW
diab_knowr	Diabetes	integer	nominal	8,9,.z	.j	0	1					obs_int		exdate	minorvars	23	SHIP_study	INTERVIEW
diab_age	Diab. Age onset	integer	ratio	8,9,.z	.j							obs_int		exdate	minorvars	24	SHIP_study	INTERVIEW
contraceptic	Contracep. ever	integer	nominal	8,9,.q,.z	.j	1	2					obs_int		exdate	minorvars	25	SHIP_study	INTERVIEW
income	Housh. income	integer	ratio	98,99,.q,.z	.j							obs_int		exdate	minorvars	26	SHIP_study	INTERVIEW
hdl	HDL	float	ratio	.d,.t,.v,.z				<0						exdate	minorvars	27	SHIP_study	LABORATORY
ldl	LDL	float	ratio	.d,.t,.v,.z				<0						exdate	minorvars	28	SHIP_study	LABORATORY

ANALYSIS PERSPECTIVE
Take II

Analysis perspective
Multiple survey/examination DQ reporting

```
dqrep, rd(Example7) metadatafile("SHIP_metadata.xlsx") ///
       segmentname(segments) problemvarreport(4) benchmark(3)
```



Analysis perspective
Multiple survey/examination DQ reporting – Output





dqrep
Use scenarios
& Options

dqrep
Use scenarios

Universitätsmedizin GREIFSWALD

Active dataset ➡

```
dqrep *bp*
```

Set of datasets
Metadata via command syntax
Variable invariant metadata ➡

```
dqrep, rd(Example3) targetfiles("SHIP_study") ///
       itemmisslist(99900 99901 99902 99914) ///
       itemjumplist(99800 99801 99802) ///
       reportname("SHIP-Samplereport") ///
       reporttitle("SHIP-0 Data quality report") ///
       reportsubtitle("Report with anonymized SHIP-0 data") ///
       reportformat("docx") keyvars("sbp1 sbp2 dbp1 dbp2") ///
       minorvars(cholesterol stroke diab_known waist weight) ///
       observervars(obs_bp) devicevars(dev_bp) ///
       controlvars(age sex) idvars(id) timevars("exdate") store
```

Set of datasets
Metadata via spreadsheet
Variable variant metadata ➡

```
dqrep, rd(Example4) metadatafile("SHIP_metadata.xlsx") store
```

dqrep
Options

#76

```
dqrep [varlist], [options]
```

- Study data files and folders
- Result data files and folders
- Metadata files and folders
- Variable selections and variable roles
- Report formatting
- Analysis settings

+ adaptable
  - report structures, tables
  - languages
  - grading

Conclusion - dqrep

Strenghts
- A single command call suffices for complex DQ reporting
- Highly customizable → yet focus standard reports
- **dqrep relies on transparent information management**

Limitations
- No interactive assessments → formalized workflows
- Numerical variables (tries to convert strings)
- Not all data-quality related information automatically extracted
- Stata stability issues with single reports >100-150 variables
- Creating extensive metadata time-consuming

```
net from https://packages.qihs.uni-greifswald.de/repository/stata/dqrep
net install dqrep, replace
```

carsten.schmidt@uni-greifswald.de

Universitätsmedizin Greifswald . KöR

Carsten Oliver Schmidt
ICM SHIP/KEF
Fleischmannstraße 8 . 17475 Greifswald
www.medizin.uni-greifswald.de