

# GETTING STARTED WITH STATA FOR MAC<sup>®</sup> RELEASE 16



A Stata Press Publication  
StataCorp LLC  
College Station, Texas



® Copyright © 1985–2019 StataCorp LLC  
All rights reserved  
Version 16

Published by Stata Press, 4905 Lakeway Drive, College Station, Texas 77845  
Typeset in  $\text{\TeX}$

ISBN-10: 1-59718-280-X  
ISBN-13: 978-1-59718-280-5

This manual is protected by copyright. All rights are reserved. No part of this manual may be reproduced, stored in a retrieval system, or transcribed, in any form or by any means—electronic, mechanical, photocopy, recording, or otherwise—without the prior written permission of StataCorp LLC unless permitted subject to the terms and conditions of a license granted to you by StataCorp LLC to use the software and documentation. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

StataCorp provides this manual “as is” without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. StataCorp may make improvements and/or changes in the product(s) and the program(s) described in this manual at any time and without notice.

The software described in this manual is furnished under a license agreement or nondisclosure agreement. The software may be copied only in accordance with the terms of the agreement. It is against the law to copy the software onto DVD, CD, disk, diskette, tape, or any other medium for any purpose other than backup or archival purposes.

The automobile dataset appearing on the accompanying media is Copyright © 1979 by Consumers Union of U.S., Inc., Yonkers, NY 10703-1057 and is reproduced by permission from CONSUMER REPORTS, April 1979.

Icons other than the Stata icon are licensed from the Iconfactory, Inc. They remain property of the Iconfactory, Inc., and may not be reproduced or redistributed.

Stata, **STATA** Stata Press, Mata, **MATA** and NetCourse are registered trademarks of StataCorp LLC.

Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations.

NetCourseNow is a trademark of StataCorp LLC.

Other brand and product names are registered trademarks or trademarks of their respective companies.

For copyright information about the software, type `help copyright` within Stata.

The suggested citation for this software is

StataCorp. 2019. *Stata: Release 16*. Statistical Software. College Station, TX: StataCorp LLC.

# Contents

1	Introducing Stata—sample session	1
2	The Stata user interface	24
3	Using the Viewer	33
4	Getting help	37
5	Opening and saving Stata datasets	45
6	Using the Data Editor	47
7	Using the Variables Manager	62
8	Importing data	65
9	Labeling data	70
10	Listing data and basic command syntax	76
11	Creating new variables	85
12	Deleting variables and observations	92
13	Using the Do-file Editor—automating Stata	95
14	Graphing data	102
15	Editing graphs	104
16	Saving and printing results by using logs	107
17	Setting font and window preferences	111
18	Learning more about Stata	113
19	Updating and extending Stata—Internet functionality	117
A	Troubleshooting Stata	124
B	Advanced Stata usage	126
C	More on Stata for Mac	131
	Subject index	134

# Cross-referencing the documentation

When reading this manual, you will find references to other Stata manuals, for example, [U] [27 Overview of Stata estimation commands](#); [R] [regress](#); and [D] [reshape](#). The first example is a reference to chapter 27, *Overview of Stata estimation commands*, in the *User's Guide*; the second is a reference to the `regress` entry in the *Base Reference Manual*; and the third is a reference to the `reshape` entry in the *Data Management Reference Manual*.

All the manuals in the Stata Documentation have a shorthand notation:

[GSM]	<i>Getting Started with Stata for Mac</i>
[GSU]	<i>Getting Started with Stata for Unix</i>
[GSW]	<i>Getting Started with Stata for Windows</i>
[U]	<i>Stata User's Guide</i>
[R]	<i>Stata Base Reference Manual</i>
[BAYES]	<i>Stata Bayesian Analysis Reference Manual</i>
[CM]	<i>Stata Choice Models Reference Manual</i>
[D]	<i>Stata Data Management Reference Manual</i>
[DSGE]	<i>Stata Dynamic Stochastic General Equilibrium Models Reference Manual</i>
[ERM]	<i>Stata Extended Regression Models Reference Manual</i>
[FMM]	<i>Stata Finite Mixture Models Reference Manual</i>
[FN]	<i>Stata Functions Reference Manual</i>
[G]	<i>Stata Graphics Reference Manual</i>
[IRT]	<i>Stata Item Response Theory Reference Manual</i>
[LASSO]	<i>Stata Lasso Reference Manual</i>
[XT]	<i>Stata Longitudinal-Data/Panel-Data Reference Manual</i>
[META]	<i>Stata Meta-Analysis Reference Manual</i>
[ME]	<i>Stata Multilevel Mixed-Effects Reference Manual</i>
[MI]	<i>Stata Multiple-Imputation Reference Manual</i>
[MV]	<i>Stata Multivariate Statistics Reference Manual</i>
[PSS]	<i>Stata Power, Precision, and Sample-Size Reference Manual</i>
[P]	<i>Stata Programming Reference Manual</i>
[RPT]	<i>Stata Reporting Reference Manual</i>
[SP]	<i>Stata Spatial Autoregressive Models Reference Manual</i>
[SEM]	<i>Stata Structural Equation Modeling Reference Manual</i>
[SVY]	<i>Stata Survey Data Reference Manual</i>
[ST]	<i>Stata Survival Analysis Reference Manual</i>
[TS]	<i>Stata Time-Series Reference Manual</i>
[TE]	<i>Stata Treatment-Effects Reference Manual: Potential Outcomes/Counterfactual Outcomes</i>
[I]	<i>Stata Glossary and Index</i>
[M]	<i>Mata Reference Manual</i>

# About this manual

This manual discusses **Stata for Mac**<sup>®</sup>. Stata for Windows<sup>®</sup> users should see *Getting Started with Stata for Windows*; Stata for Unix<sup>®</sup> users should see *Getting Started with Stata for Unix*. This manual is intended both for people who are completely new to Stata and for experienced Stata users new to Stata for Mac. Previous Stata users will also find it helpful as a tutorial on some new features in Stata for Mac.

Following the numbered chapters are three appendixes with information specific to Stata for Mac.

We provide several types of technical support to registered Stata users. [GSM] 4 **Getting help** describes the resources available to help you learn about Stata's commands and features. One of these resources is the Stata website (<https://www.stata.com>), where you will find answers to frequently asked questions (FAQs) as well as other useful information. If you still have questions after looking at the Stata website and the other resources described in [GSM] 19 **Updating and extending Stata—Internet functionality**, you can contact us as described in [U] 3.8 **Technical support**.

## Using this manual

The new user will get the most out of this book by treating it as an exercise book, working through each example at the computer. The material builds, so material from earlier chapters will often be used in later chapters. Bear in mind that Stata is a rich and deep statistical package—just as statistics itself is rich and deep. The time spent working the examples will be repaid with dividends when doing true statistical analyses.

The experienced user may still have something to learn from this manual despite its name. We suggest looking through the chapters to see if there is anything new or forgotten.

## Notational conventions

The preferences for Stata are located under the Application menu, as is common for applications in macOS. The name of this menu, however, depends on what flavor of Stata you have installed: it could be **Stata/MP 16.1**, **Stata/SE 16.1**, **Stata/IC 16.1**. Throughout this documentation, we will call it **Stata**. Thus, we will say that Preferences can be found at **Stata > Preferences**, though the exact name of the top-level menu may be slightly different.

# 1 Introducing Stata—sample session

## Introducing Stata

This chapter will run through a sample work session, introducing you to a few of the basic tasks that can be done in Stata, such as opening a dataset, investigating the contents of the dataset, using some descriptive statistics, making some graphs, and doing a simple regression analysis. As you would expect, we will only brush the surface of many of these topics. This approach should give you a sample of what Stata can do and how Stata works. There will be brief explanations along the way, with references to chapters later in this book as well as to the system help and other Stata manuals. We will run through the session by using both menus and dialogs and Stata's commands so that you can become familiar with them both. If you see that your menus and dialogs are not in English, we recommend that you (temporarily) change the locale used by Stata to English, so that you can work along with the examples. See [P] [set locale.ui](#) for how to do this.

Take a seat at your computer, put on some good music, and work along with the book.

## Sample session

The dataset that we will use for this session is a set of data about vintage 1978 automobiles sold in the United States.

To follow along by pointing and clicking, note that the menu items are given by **Menu > Menu item > Submenu item > etc.** To follow along by using the Command window, type the commands that follow a dot (.) in the boxed listings below into the small window labeled **Command**. When there is something to note about the structure of a command, it will be pointed out as a “Syntax note”.

Start by loading the `auto` dataset, which is included with Stata. To use the menus,

1. Select **File > Example datasets...**
2. Click on **Example datasets installed with Stata.**
3. Click on **use for auto.dta.**

The result of this command is fourfold:

- The following output appears in the large Results window:

```
. sysuse auto
(1978 Automobile Data)
```

The output consists of a command and its result. The command, `sysuse auto.dta`, is bold and follows the dot (.). The result, `(1978 Automobile Data)`, is in the standard face here and is a brief description of the dataset.


Note: If a command intrigues you, you can type `help commandname` in the Command window to find help. If you want to explore at any time, **Help > Search...** can be informative.

- A series of variables appears in the small Variables window to the upper right.

You could have opened the dataset by typing `sysuse auto` in the Command window and pressing *Return*. Try this now. `sysuse` is a command that loads (uses) example (system) datasets. As you will see during this session, Stata commands are often simple enough that it is faster to use them directly. This will be especially true once you become familiar with the commands you use the most in your daily use of Stata.


Syntax note: In the above example, `sysuse` is the Stata command, whereas `auto` is the name of a Stata data file.

## Simple data management

We can get a quick glimpse at the data by browsing them in the **Data Editor**. This can be done by clicking on the **Data Editor (Browse)** button, , or by selecting **Data > Data Editor > Data Editor (Browse)** from the menus or by typing the command `browse`.

No command is issued when clicking on either Data Editor button because opening the Data Editor has no effect on the dataset or any possible analysis.

When the Data Editor window opens, you can see that Stata regards the data as one rectangular table. This is true for all Stata datasets. The columns represent *variables*, whereas the rows represent *observations*. The variables have somewhat descriptive names, whereas the observations are numbered.



	make	price	mpg	rep78	headroom
1	AMC Concord	4,099	22	3	2.5
2	AMC Pacer	4,749	17	3	3.0
3	AMC Spirit	3,799	22	.	3.0
4	Buick Century	4,816	20	3	4.5
5	Buick Electra	7,827	15	4	4.0
6	Buick LeSabre	5,788	18	3	4.0
7	Buick Opel	4,453	26	.	3.0
8	Buick Regal	5,189	20	3	2.0
9	Buick Riviera	10,372	16	3	3.5
10	Buick Skylark	4,082	19	3	3.5
11	Cad. Deville	11,385	14	3	4.0
12	Cad. Eldorado	14,500	14	2	3.5
13	Cad. Seville	15,906	21	3	3.0
14	Chev. Chevette	3,299	29	3	2.5
15	Chev. Impala	5,705	16	4	4.0

The data are displayed in multiple colors—at first glance, it appears that the variables listed in black (or white, in dark mode) are numeric, whereas those that are in colors are text. This is worth investigating. Click on a cell under the `make` variable: the input box at the top displays the make of the car. Scroll to the right until you see the `foreign` variable. Click on one of its cells. Although the cell may display “Domestic”, the input box displays a 0. This shows that Stata can store categorical data as numbers but display human-readable text. This is done by what Stata calls *value labels*. Finally, under the `rep78` variable, which looks to be numeric, there are some cells containing just a dot (.). The dots correspond to missing values.

Looking at the data in this fashion, though comfortable, lends little information about the dataset. It would be useful for us to get more details about what the data are and how the data are stored. Close the Data Editor by closing its tab, clicking on its close button.

We can see the structure of the dataset by *describing* its contents. This can be done either by going to **Data > Describe data > Describe data in memory or in a file** in the menus and clicking on **OK** or by typing `describe` in the Command window and pressing *Return*. Regardless of which method you choose, you will get the same result:

```
. describe
Contains data from /Applications/Stata/ado/base/a/auto.dta
  obs:           74           1978 Automobile Data
  vars:          12           13 Apr 2018 17:45
                          (_dta has notes)
```

variable name	storage type	display format	value label	variable label
<b>make</b>	str18	%-18s		<b>Make and Model</b>
<b>price</b>	int	%8.0gc		<b>Price</b>
<b>mpg</b>	int	%8.0g		<b>Mileage (mpg)</b>
<b>rep78</b>	int	%8.0g		<b>Repair Record 1978</b>
<b>headroom</b>	float	%6.1f		<b>Headroom (in.)</b>
<b>trunk</b>	int	%8.0g		<b>Trunk space (cu. ft.)</b>
<b>weight</b>	int	%8.0gc		<b>Weight (lbs.)</b>
<b>length</b>	int	%8.0g		<b>Length (in.)</b>
<b>turn</b>	int	%8.0g		<b>Turn Circle (ft.)</b>
<b>displacement</b>	int	%8.0g		<b>Displacement (cu. in.)</b>
<b>gear_ratio</b>	float	%6.2f		<b>Gear Ratio</b>
<b>foreign</b>	byte	%8.0g	origin	<b>Car type</b>

```
Sorted by: foreign
```

At the top of the listing, some information is given about the dataset, such as where it is stored on disk and when the dataset was last saved. The bold 1978 Automobile Data is the short description that appeared when the dataset was opened and is referred to as a *data label* by Stata. The phrase `_dta has notes` informs us that there are notes attached to the dataset. We can see what notes there are by typing `notes` in the Command window:

```
. notes
_dta:
  1. from Consumer Reports with permission
```

Here we see a short note about the source of the data.

Looking back at the listing from `describe`, we can see that Stata keeps track of more than just the raw data. Each variable has the following:

- A *variable name*, which is what you call the variable when communicating with Stata. Variable names are one type of Stata name. See [U] 11.3 **Naming conventions**.
- A *storage type*, which is the way Stata stores its data. For our purposes, it is enough to know that types like, say, `str#` are *string*, or text, variables, whereas all others in this dataset are numeric. While there are none in this dataset, Stata also allows arbitrarily long strings, or `strLs`. `strLs` can also contain binary information. See [U] 12.4 **Strings**.



- A *display format*, which controls how Stata displays the data in tables. See [U] 12.5 **Formats: Controlling how data are displayed**.
- A *value label* (possibly). This is the mechanism that allows Stata to store numerical data while displaying text. See [GSM] 9 **Labeling data** and [U] 12.6.3 **Value labels**.
- A *variable label*, which is what you call the variable when communicating with other people. Stata uses the variable label when making tables, as we will see.

A dataset is far more than simply the data it contains. It is also information that makes the data usable by someone other than the original creator.

Although describing the data tells us something about the structure of the data, it says little about the data themselves. The data can be summarized by clicking on **Statistics > Summaries, tables, and tests > Summary and descriptive statistics > Summary statistics** and clicking on the **OK** button. You could also type `summarize` in the Command window and press *Return*. The result is a table containing summary statistics about all the variables in the dataset:

. summarize					
Variable	Obs	Mean	Std. Dev.	Min	Max
make	0				
price	74	6165.257	2949.496	3291	15906
mpg	74	21.2973	5.785503	12	41
rep78	69	3.405797	.9899323	1	5
headroom	74	2.993243	.8459948	1.5	5
trunk	74	13.75676	4.277404	5	23
weight	74	3019.459	777.1936	1760	4840
length	74	187.9324	22.26634	142	233
turn	74	39.64865	4.399354	31	51
displacement	74	197.2973	91.83722	79	425
gear_ratio	74	3.014865	.4562871	2.19	3.89
foreign	74	.2972973	.4601885	0	1

From this simple summary, we can learn a bit about the data. First of all, the prices are nothing like today's car prices—of course, these cars are now antiques. We can see that the gas mileages are not particularly good. Automobile aficionados can get a feel for other esoteric characteristics.

There are two other important items here:

- The `make` variable is listed as having no observations. It really has no numerical observations because it is a string (text) variable.
- The `rep78` variable has five fewer observations than the other numerical variables. This implies that `rep78` has five missing values.

Although we could use the `summarize` and `describe` commands to get a bird's eye view of the dataset, Stata has a command that gives a good in-depth description of the structure, contents, and values of the variables: the `codebook` command. Either type `codebook` in the Command window and press *Return* or navigate the menus to **Data > Describe data > Describe data contents (codebook)** and click on **OK**. Look over the output to see that much can be learned from this simple command. You can scroll back in the Results window to see earlier results, if need be. We will focus on the output for `make`, `rep78`, and `foreign`.

To start our investigation, we would like to run the `codebook` command on just one variable, say, `make`. We can do this, as usual, with menus or the command line. To get the `codebook` output for `make` with the menus, start by navigating to **Data > Describe data > Describe data contents**

(codebook). When the dialog appears, there are multiple ways to tell Stata to consider only the make variable:

- We could type make into the *Variables* field.
- The *Variables* field is a combo-box control that accepts variable names. Clicking on the drop triangle to the right of the *Variables* field displays a list of the variables from the current dataset. Selecting a variable from the list will, in this case, enter the variable name into the edit field.

A much easier solution is to type `codebook make` in the Command window and then press *Return*. The result is informative:

```
. codebook make
```

---

```
make                                     Make and Model
```

---

```

           type:  string (str18), but longest is str17
unique values:  74                               missing "":  0/74
  examples:    "Cad. Deville"
               "Dodge Magnum"
               "Merc. XR-7"
               "Pont. Catalina"
warning:      variable has embedded blanks
```

The first line of the output tells us the variable name (`make`) and the variable label (`Make and Model`). The variable is stored as a string (which is another way of saying “text”) with a maximum length of 18 characters, though a size of only 17 characters would be enough. All the values are unique, so if need be, `make` could be used as an identifier for the observations—something that is often useful when putting together data from multiple sources or when trying to weed out errors from the dataset. There are no missing values, but there are blanks within the makes. This latter fact could be useful if we were expecting `make` to be a one-word string variable.

Syntax note: Telling the `codebook` command to run on the `make` variable is an example of using a *varlist* in Stata’s syntax.

Looking at the `foreign` variable can teach us about value labels. We would like to look at the codebook output for this variable, and on the basis of our latest experience, it would be easy to type `codebook foreign` into the Command window (from here on, we will not explicitly say to press the *Return* key) to get the following output:

```
. codebook foreign
```

---

```
foreign                                     Car type
```

---

```

           type:  numeric (byte)
           label:  origin
           range:  [0,1]                               units:  1
unique values:  2                               missing .:  0/74
  tabulation:    Freq.   Numeric   Label
                  52      0   Domestic
                  22      1   Foreign
```

We can glean that `foreign` is an indicator variable because its only values are 0 and 1. The variable has a value label that displays `Domestic` instead of 0 and `Foreign` instead of 1. There are two advantages of storing the data in this form:

- Storing the variable as a byte takes less memory because each observation uses 1 byte instead of the 8 bytes needed to store “Domestic”. This is important in large datasets. See [U] [12.2.2 Numeric storage types](#).
- As an indicator variable, it is easy to incorporate into statistical models. See [U] [26 Working with categorical data and factor variables](#).

Finally, we can learn a little about a poorly labeled variable with missing values by looking at the `rep78` variable. Typing `codebook rep78` into the Command window yields

```
. codebook rep78
```

```

rep78                                     Repair Record 1978
-----
          type:  numeric (int)
          range:  [1,5]
unique values:  5
          units:  1
          missing.: 5/74
          tabulation:  Freq.  Value
                       2    1
                       8    2
                       30   3
                       18   4
                       11   5
                       5    .

```

`rep78` appears to be a categorical variable, but because of lack of documentation, we do not know what the numbers mean. (To see how we would label the values, see [Changing data](#) in [\[GSM\] 6 Using the Data Editor](#) and see [\[GSM\] 9 Labeling data](#).) This variable has five missing values, meaning that there are five observations for which the repair record is not recorded. We could use the Data Editor to investigate these five observations, but we will do this by using the Command window only because doing so is much simpler.

The command equivalent to clicking on the **Data Editor (Browse)** button is `browse`. We would like to browse only those observations for which `rep78` is missing, so we could type

```
. browse if missing(rep78)
```

The screenshot shows the Stata Data Editor window titled "Data Editor (Browse) — auto.dta". The main window displays a dataset with the following data:

	make	price	mpg	rep78	head
3	AMC Spirit	3,799	22	.	
7	Buick Opel	4,453	26	.	
45	Plym. Sapporo	6,486	26	.	
51	Pont. Phoenix	4,424	19	.	
64	Peugeot 604	12,990	14	.	

The right sidebar shows the "Variables" list with the following entries:

Name	Label
<input checked="" type="checkbox"/> make	Make and Model
<input checked="" type="checkbox"/> price	Price
<input checked="" type="checkbox"/> mpg	Mileage (mpg)

The "Properties" panel for the selected variable "make" shows the following details:

Name	make
Label	Make and Model
Type	str18
Format	%-18s
Value label	
Notes	

At the bottom of the window, it shows "Vars: 12 Order: Dataset", "Obs: 5 of 74", "Length: 18", and "Filter: On".

From this, we see that the . entries are indeed missing values. The . is the default numerical missing value; Stata also allows .a, . . . , .z as user missing values, but we do not have any in our dataset. See [U] 12.2.1 Missing values. Close the Data Editor after you are satisfied with this statement.

Syntax note: Using the `if` qualifier above is what allowed us to look at a subset of the observations.

Looking through the data lends no clues about why these particular data are missing. We decide to check the source of the data to see if the missing values were originally missing or if they were omitted in error. Listing the makes of the cars whose repair records are missing will be all we need because we saw earlier that the values of `make` are unique. This can be done with the menus and a dialog:

1. Select **Data > Describe data > List data**.
2. Click on the drop triangle to the right of the *Variables* field to show the variable names.
3. Click on `make` to enter it into the *Variables* field.
4. Click on the **by/if/in** tab in the dialog.
5. Type `missing(rep78)` into the *If: (expression)* box.
6. Click on **Submit**. Stata executes the proper command but the dialog remains open. **Submit** is useful when experimenting, exploring, or building complex commands. We will primarily use **Submit** in the examples. You may click on **OK** in its place if you like, and it will close the dialog box.

The same ends could be achieved by typing `list make if missing(rep78)` in the Command window. The latter is easier once you know that the command `list` is used for listing observations. In any case, here is the output:

```
. list make if missing(rep78)
```

	make
3.	AMC Spirit
7.	Buick Opel
45.	Plym. Sapporo
51.	Pont. Phoenix
64.	Peugeot 604

At this point we should find the original reference to see if the data were truly missing or if they could be resurrected. See [GSM] 10 [Listing data and basic command syntax](#) for more information about all that can be done with the `list` command.

Syntax note: This command uses two new concepts for Stata commands—the `if` qualifier and the `missing()` function. The `if` qualifier restricts the observations on which the command runs to only those observations for which the expression is true. See [U] 11.1.3 [if exp](#). The `missing()` function tests each observation to see if it contains a missing value. See [FN] [Programming functions](#).

Now that we have a good idea about the underlying dataset, we can investigate the data themselves.

## Descriptive statistics


We saw above that the `summarize` command gave brief summary statistics about all the variables. Suppose now that we became interested in the prices while summarizing the data because they seemed fantastically low (it was 1978, after all). To get an in-depth look at the `price` variable, we can use the menus and a dialog:


1. Select **Statistics > Summaries, tables, and tests > Summary and descriptive statistics > Summary statistics**.
2. Enter or select `price` in the *Variables* field.
3. Select *Display additional statistics*.
4. Click on **Submit**.


Syntax note: As can be seen from the Results window, typing `summarize price, detail` will get the same result. The portion after the comma contains *options* for Stata commands; hence, `detail` is an example of an option.

```
. summarize price, detail
```

Price					
Percentiles		Smallest			
1%	3291	3291			
5%	3748	3299			
10%	3895	3667			
25%	4195	3748			
50%	5006.5				
		Largest			
75%	6342	13466			
90%	11385	13594			
95%	13466	14500			
99%	15906	15906			
		Obs	74		
		Sum of Wgt.	74		
		Mean	6165.257		
		Std. Dev.	2949.496		
		Variance	8699526		
		Skewness	1.653434		
		Kurtosis	4.819188		

From the output, we can see that the median price of the cars in the dataset is only \$5,006.50! We can also see that the four most expensive cars are all priced between \$13,400 and \$16,000. If we wished to browse the most expensive cars (and gain some experience with features of the Data Editor), we could start by clicking on the **Data Editor (Browse)** button, .

Once the Data Editor is open, we can click on the **Filter observations** button, , in the sidebar so that the sidebar shows the *Filter observations* window. We can look at the expensive cars by putting `price > 13000` in the *Filter by expression* field:



The screenshot shows the 'Filter observations' dialog box in Stata. At the top, there are icons for a list, a camera, and a blue funnel. The main title is 'Filter observations'. Below the title, there is a section 'Filter by expression:' with a text input field containing 'price > 13000' and a small '...' button to its right. Underneath is the 'Filter by observation' section, which has three radio button options: 'Use in-range qualifier:' (which is selected), 'By observation #', and 'Use live filtering:' (which is checked). The 'By observation #' option has 'From:' and 'To:' fields with values '1' and '74' respectively. At the bottom of the dialog, there are two buttons: 'Apply filter' and 'Remove filter'.

Pressing the **Apply filter** button filters the data, and we can see that the expensive cars are two Cadillacs and two Lincolns, which were not designed for gas mileage:

The screenshot shows the Stata Data Editor interface. The main window displays a dataset with columns: make, price, mpg, rep78, and head. The 'make' variable is filtered to 'make[12]', and the 'Cad. Eldorado' filter is applied. The data rows are:

	make	price	mpg	rep78	head
12	Cad. Eldorado	14,500	14	2	
13	Cad. Seville	15,906	21	3	
27	Linc. Mark V	13,594	12	3	
28	Linc. Versailles	13,466	14	3	

The right sidebar shows the 'Variables' list with 'make', 'price', and 'mpg' selected. The 'Properties' panel shows the variable 'make' with its label 'Make and Model'.

We now decide to turn our attention to foreign cars and repairs because as we glanced through the data, it appeared that the foreign cars had better repair records. (We do not know exactly what the categories 1, 2, 3, 4, and 5 mean, but we know the Chevy Monza was known for breaking down.) Let's start by looking at the proportion of foreign cars in the dataset along with the proportion of cars with each type of repair record. We can do this with one-way tables. The table for foreign cars can be done with menus and a dialog starting with **Statistics > Summaries, tables, and tests > Frequency tables > One-way table** and then choosing the variable *foreign* in the *Categorical variable* field. Clicking on **Submit** yields

```
. tabulate foreign
```

Car type	Freq.	Percent	Cum.
Domestic	52	70.27	70.27
Foreign	22	29.73	100.00
Total	74	100.00	

We see that roughly 70% of the cars in the dataset are domestic, whereas 30% are foreign. The value labels are used to make the table so that the output is nicely readable.

Syntax note: We also see that this one-way table could be made by using the `tabulate` command together with one variable, `foreign`. Making a one-way table for the repair records is simple—it will be simpler if done with the Command window. Typing `tabulate rep78` yields

```
. tabulate rep78
```

Repair Record 1978	Freq.	Percent	Cum.
1	2	2.90	2.90
2	8	11.59	14.49
3	30	43.48	57.97
4	18	26.09	84.06
5	11	15.94	100.00
Total	69	100.00	

We can see that most cars have repair records of 3 and above, though the lack of value labels makes us unsure what a “3” means. Take our word for it that 1 means a poor repair record and 5 means a good repair record. The five missing values are indirectly evident because the total number of observations listed is 69 rather than 74.

These two one-way tables do not help us compare the repair records of foreign and domestic cars. A two-way table would help greatly, which we can get by using the menus and a dialog:

1. Select **Statistics > Summaries, tables, and tests > Frequency tables > Two-way table with measures of association**.
2. Choose `rep78` as the *Row variable*.
3. Choose `foreign` as the *Column variable*.
4. It would be nice to have the percentages within the `foreign` variable, so check the *Within-row relative frequencies* checkbox.
5. Click on **Submit**.

Here is the resulting output:



```
. tabulate rep78 foreign, row
```

Key			
	<i>frequency</i>		
	<i>row percentage</i>		
Repair Record 1978	Car type		Total
	Domestic	Foreign	
1	2 100.00	0 0.00	2 100.00
2	8 100.00	0 0.00	8 100.00
3	27 90.00	3 10.00	30 100.00
4	9 50.00	9 50.00	18 100.00
5	2 18.18	9 81.82	11 100.00
Total	48 69.57	21 30.43	69 100.00

The output indicates that foreign cars are generally much better than domestic cars when it comes to repairs. If you like, you could repeat the previous dialog and try some of the hypothesis tests available from the dialog. We will abstain.

Syntax note: We see that typing the command `tabulate rep78 foreign, row` would have given us the same table. Thus using `tabulate` with two variables yields a two-way table. It makes sense that `row` is an option—we went out of our way to check it in the dialog. Using the `row` option allows us to change the behavior of the `tabulate` command from its default.

Continuing our exploratory tour of the data, we would like to compare gas mileages between foreign and domestic cars, starting by looking at the summary statistics for each group by itself. A direct way to do this would be to use `if` qualifiers to summarize `mpg` for each of the two values of `foreign` separately:

```
. summarize mpg if foreign==0
```

Variable	Obs	Mean	Std. Dev.	Min	Max
mpg	52	19.82692	4.743297	12	34


```
. summarize mpg if foreign==1
```

Variable	Obs	Mean	Std. Dev.	Min	Max
mpg	22	24.77273	6.611187	14	41

It appears that foreign cars get somewhat better gas mileage—we will test this soon.

Syntax note: We needed to use a double equal sign (==) for testing equality. The double equal sign could be familiar to you if you have programmed before. If it is unfamiliar, be aware that it is a common source of errors when initially using Stata. Thinking of equality as “exactly equal” can cut down on typing errors.

There are two other methods that we could have used to produce these summary statistics. These methods are worth knowing because they are less error-prone. The first method duplicates the concept of what we just did by exploiting Stata’s ability to run a command on each of a series of nonoverlapping subsets of the dataset. To use the menus and a dialog, do the following:

1. Select **Statistics > Summaries, tables, and tests > Summary and descriptive statistics > Summary statistics** and click on the **Reset** button, .
2. Select `mpg` in the *Variables* field.
3. Select the *Standard display* option (if it is not already selected).
4. Click on the **by/if/in** tab.
5. Check the *Repeat command by groups* checkbox.
6. Select or type `foreign` in the *Variables that define groups* field.
7. **Submit** the command.

You can see that the results match those from above. They have a better appearance than the two commands above because the value labels `Domestic` and `Foreign` are used rather than the numerical values. The method is more appealing because the results were produced without needing to know the possible values of the grouping variable ahead of time.

```
. by foreign, sort: summarize mpg
```

```
-> foreign = Domestic
```

Variable	Obs	Mean	Std. Dev.	Min	Max
mpg	52	19.82692	4.743297	12	34

```
-> foreign = Foreign
```

Variable	Obs	Mean	Std. Dev.	Min	Max
mpg	22	24.77273	6.611187	14	41

Syntax note: There is something different about the equivalent command that appears above: it contains a *prefix command* called a `by` prefix. The `by` prefix has its own option, namely, `sort`, to ensure that like members are adjacent to each other before being summarized. The `by` prefix command is important for understanding data manipulation and working with subpopulations within Stata. Make good note of this example, and consult [U] 11.1.2 [by varlist:](#) and [U] 13.7 [Explicit subscripting](#) for more information. Stata has other prefix commands for specialized treatment of commands, as explained in [U] 11.1.10 [Prefix commands](#).

The third method for tabulating the differences in gas mileage across the cars’ origins involves thinking about the structure of desired output. We need a one-way table of automobile types (foreign versus domestic) within which we see information about gas mileages. Looking through the menus yields the menu item **Statistics > Summaries, tables, and tests > Other tables > Table of means, std. dev., and frequencies**. Selecting this, entering `foreign` for *Variable 1* and `mpg` for the *Summarize variable*, and submitting the command yields a nice table:

```
. tabulate foreign, summarize(mpg)
```

Car type	Summary of Mileage (mpg)		Freq.
	Mean	Std. Dev.	
Domestic	19.826923	4.7432972	52
Foreign	24.772727	6.6111869	22
Total	21.297297	5.7855032	74

The equivalent command is evidently `tabulate foreign, summarize(mpg)`.

Syntax note: This is a one-way table, so `tabulate` uses one variable. The variable being summarized is passed to the `tabulate` command with an option. Though we will not do it here, the `summarize()` option can also be used with two-way tables.

## A simple hypothesis test

We would like to run a hypothesis test for the difference in the mean gas mileages. Under the menus, **Statistics > Summaries, tables, and tests > Classical tests of hypotheses > t test (mean-comparison test)** leads to the proper dialog. Select the *Two-sample using groups* radio button, enter `mpg` for the *Variable name* and `foreign` for the *Group variable name*, and **Submit** the dialog. The results are

```
. ttest mpg, by(foreign)
```

Two-sample t test with equal variances

Group	Obs	Mean	Std. Err.	Std. Dev.	[95% Conf. Interval]	
Domestic	52	19.82692	.657777	4.743297	18.50638	21.14747
Foreign	22	24.77273	1.40951	6.611187	21.84149	27.70396
combined	74	21.2973	.6725511	5.785503	19.9569	22.63769
diff		-4.945804	1.362162		-7.661225	-2.230384

```
diff = mean(Domestic) - mean(Foreign)          t = -3.6308
Ho: diff = 0                                   degrees of freedom = 72
Ha: diff < 0                                   Ha: diff != 0
Pr(T < t) = 0.0003                             Pr(|T| > |t|) = 0.0005
                                                Ha: diff > 0
                                                Pr(T > t) = 0.9997
```

From this, we could conclude that the mean gas mileage for foreign cars is different from that of domestic cars (though we really ought to have wanted to test this before snooping through the data). We can also conclude that the command, `ttest mpg, by(foreign)`, is easy enough to remember. Feel free to experiment with unequal variances, various approximations to the number of degrees of freedom, and the like.

Syntax note: The `by()` option used here is not the same as the `by` prefix command used earlier. Although it has a similar conceptual meaning, its usage is different because it is a particular option for the `ttest` command.

## Descriptive statistics—correlation matrices

We now change our focus from exploring categorical relationships to exploring numerical relationships: we would like to know if there is a correlation between miles per gallon and weight. We select **Statistics > Summaries, tables, and tests > Summary and descriptive statistics > Correlations and covariances** in the menus. Entering `mpg` and `weight`, either by clicking or by typing, and then submitting the command yields

```
. correlate mpg weight
(obs=74)
```

	mpg	weight
mpg	1.0000	
weight	-0.8072	1.0000

The equivalent command for this is natural: `correlate mpg weight`. There is a negative correlation, which is not surprising because heavier cars should be harder to push about.

We could see how the correlation compares for foreign and domestic cars by using our knowledge of the `by` prefix. We can reuse the `correlate` dialog or use the menus as before if the dialog is closed. Click on the **by/if/in** tab, check the *Repeat command by groups* checkbox, and enter the `foreign` variable to define the groups. As done on page 13, a simple `by foreign, sort:` prefix in front of our previous command would work, too:

```
. by foreign, sort: correlate mpg weight
```

```
-> foreign = Domestic
(obs=52)
```

	mpg	weight
mpg	1.0000	
weight	-0.8759	1.0000

```
-> foreign = Foreign
(obs=22)
```

	mpg	weight
mpg	1.0000	
weight	-0.6829	1.0000

We see from this that the correlation is not as strong among the foreign cars.

Syntax note: Although we used the `correlate` command to look at the correlation of two variables, Stata can make correlation matrices for an arbitrary number of variables:

```
. correlate mpg weight length turn displacement
(obs=74)
```

	mpg	weight	length	turn	displac~t
mpg	1.0000				
weight	-0.8072	1.0000			
length	-0.7958	0.9460	1.0000		
turn	-0.7192	0.8574	0.8643	1.0000	
displacement	-0.7056	0.8949	0.8351	0.7768	1.0000

This can be useful, for example, when investigating collinearity among predictor variables.

## Graphing data

We have found several things in our investigations so far: We know that the average MPG of domestic and foreign cars differs. We have learned that domestic and foreign cars differ in other ways as well, such as in frequency-of-repair record. We found a negative correlation between MPG and weight—as we would expect—but the correlation appears stronger for domestic cars.


We would now like to examine, with an eye toward modeling, the relationship between MPG and weight, starting with a graph. We can start with a scatterplot of `mpg` against `weight`. The command for this is simple: `scatter mpg weight`. Using the menus requires a few steps because the graphs in Stata may be customized heavily.

1. Select **Graphics > Twoway graph (scatter, line, etc.)**.
2. Click on the **Create...** button.
3. Select the *Basic plots* radio button (if it is not already selected).
4. Select *Scatter* as the basic plot type (if it is not already selected).
5. Select `mpg` as the *Y variable* and `weight` as the *X variable*.
6. Click on the **Submit** button.


The Results window shows the command that was issued from the menu:

```
. twoway (scatter mpg weight)
```

The command issued when the dialog was submitted is a bit more complex than the command suggested above. There is good reason for this: the more complex structure allows combining and overlaying graphs, as we will soon see. In any case, the graph that appears is



We see the negative correlation in the graph, though the relationship appears to be nonlinear.

Note: When you draw a graph, the Graph window appears, probably covering up your Results window. Click on the main Stata window to get the Results window back on top. Want to see the graph again? Click on the **Graph** button, . See [The Graph button in \[GSM\] 14 Graphing data](#) for more information about the **Graph** button.

We would now like to see how the different correlations for foreign and domestic cars are manifested in scatterplots. It would be nice to see a scatterplot for each type of car, along with a scatterplot for all the data.


Syntax note: Because we are looking at subgroups, this looks as if it is a job for the `by` prefix. Let's see if this is what we really should use.

Start as before:

1. Select **Graphics > Twoway graph (scatter, line, etc.)** from the menus.
2. If the sheet you used to define the scatterplot is still visible, click on the **Accept** button and skip to step 4.
3. Go through the process on the previous page to create the graph.
4. Click on the **By** tab of the *twoway - Twoway graphs* dialog.
5. Check the *Draw subgraphs for unique values of variables* checkbox.
6. Enter `foreign` in the *Variables* field.
7. Check the *Add a graph with totals* checkbox.
8. Click on the **Submit** button.

The command and the associated graph are

```
. twoway (scatter mpg weight), by(foreign, total)
```



The graphs show that the relationship is nonlinear for both types of cars.

Syntax note: To make the graphs for the combined subgroups, we ended up using a `by()` option, not a `by` prefix. If we had used a `by` prefix, separate graphs would have been generated instead of the combined graph created by the `by()` option.

## Model fitting: Linear regression

After looking at the graphs, we would like to fit a regression model that predicts MPG from the weight and type of the car. From the graphs, we see that the relationship is nonlinear, so we will try modeling MPG as a quadratic in weight. Also from the graphs, we judge the relationship to be different for domestic and foreign cars. We will include an indicator (dummy) variable for `foreign` and evaluate afterward whether this adequately describes the difference. Thus we will fit the model

$$\text{mpg} = \beta_0 + \beta_1 \text{weight} + \beta_2 \text{weight}^2 + \beta_3 \text{foreign} + \epsilon$$

`foreign` is already an indicator (0/1) variable, but we need to create the weight-squared variable. This can be done with the menus, but here using the command line is simpler. Type

```
. generate wtsq = weight^2
```

Now that we have all the variables we need, we can run a linear regression. We will use the menus and see that the command is also simple. To use the menus, select **Statistics > Linear models and related > Linear regression**. In the resulting dialog, choose `mpg` as the *Dependent variable* and `weight`, `wtsq`, and `foreign` as the *Independent variables*. **Submit** the command. Here is the equivalent simple `regress` command and the resulting analysis-of-variance table.

```
. regress mpg weight wtsq foreign
```

Source	SS	df	MS			
Model	1689.15372	3	563.05124	Number of obs	=	74
Residual	754.30574	70	10.7757963	F(3, 70)	=	52.25
Total	2443.45946	73	33.4720474	Prob > F	=	0.0000
				R-squared	=	0.6913
				Adj R-squared	=	0.6781
				Root MSE	=	3.2827

mpg	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
weight	-.0165729	.0039692	-4.18	0.000	-.0244892	-.0086567
wtsq	1.59e-06	6.25e-07	2.55	0.013	3.45e-07	2.84e-06
foreign	-2.2035	1.059246	-2.08	0.041	-4.3161	-.0909002
_cons	56.53884	6.197383	9.12	0.000	44.17855	68.89913

The results look encouraging, so we will plot the predicted values on top of the scatterplots for each of the types of cars. To do this, we need the predicted, or fitted, values. This can be done with the menus, but doing it in the Command window is simple enough. We will create a new variable, `mpghat`, to hold the predicted MPG for each car. Type

```
. predict mpghat
(option xb assumed; fitted values)
```

The output from this command is simply a notification. Go over to the Variables window and scroll to the bottom to confirm that there is now an `mpghat` variable. If you were to try this command when `mpghat` already existed, Stata would refuse to overwrite your data:


```
. predict mpghat
variable mpghat already defined
r(110);
```

The `predict` command, when used after a regression, is called a *postestimation command*. As specified, it creates a new variable called `mpghat` equal to

$$-0.0165729 \text{weight} + 1.59 \times 10^{-6} \text{wtsq} - 2.2035 \text{foreign} + 56.53884$$

For careful model fitting, there are several features available to you after estimation—one is calculating predicted values. Be sure to read [\[U\] 20 Estimation and postestimation commands](#).


We can now graph the data and the predicted curve to evaluate separately the fit on the foreign and domestic data to determine if our shift parameter is adequate. We can draw both graphs together. Using the menus and a dialog, do the following:

1. Select **Graphics > Twoway graph (scatter, line, etc.)** from the menus.
2. If there are any plots listed, click on the **Reset** button, , to clear the dialog box.



3. Create the graph for mpg versus weight:
    - a. Click on the **Create...** button.
    - b. Be sure that *Basic plots* and *Scatter* are selected.
    - c. Select mpg as the *Y variable* and weight as the *X variable*.
    - d. Click on **Accept**.
  4. Create the graph showing mpghat versus weight
    - a. Click on the **Create...** button.
    - b. Select *Basic plots* and *Line*.
    - c. Select mpghat as the *Y variable* and weight as the *X variable*.
    - d. Check the *Sort on x variable* box. Doing so ensures that the lines connect from smallest to largest weight values, instead of the order in which the data happen to be.
    - e. Click on **Accept**.
  5. Show two plots, one each for domestic and foreign cars, on the same graph:
    - a. Click on the **By** tab.
    - b. Check the *Draw subgraphs for unique values of variables* checkbox.
    - c. Enter foreign in the *Variables* field.
  6. Click on the **Submit** button.
- Here are the resulting command and graph:

```
. twoway (scatter mpg weight) (line mpghat weight, sort), by(foreign)
```




Here we can see the reason for enclosing the separate `scatter` and `line` commands in parentheses: they can thereby be overlaid by submitting them together. The fit of the plots looks good and is cause for initial excitement. So much excitement, in fact, that we decide to print the graph and show it to an engineering friend. We print the graph, being careful to print the graph (and not all our results), by choosing **File > Print > Graph — Graph**.

When we show our graph to our engineering friend, she is concerned. “No,” she says. “It should take twice as much energy to move 2,000 pounds 1 mile compared with moving 1,000 pounds the same distance: therefore, it should consume twice as much gasoline. Miles per gallon is not quadratic in weight; gallons per mile is a linear function of weight. Don’t you remember any physics?”

We try out what she says. We need to generate an energy-per-distance variable and make a scatterplot. Here are the commands that we would need—note their similarity to commands issued earlier in the session. There is one new command, the `label variable` command, which allows us to give the `gpm100m` variable a *variable label* so that the graph is labeled nicely.

```
. generate gpm100m = 100/mpg
. label variable gpm100m "Gallons per 100 miles"
. twoway (scatter gpm100m weight), by(foreign, total)
```



Sadly satisfied that the engineer is indeed correct, we rerun the regression:

```
. regress gp100m weight foreign
```

Source	SS	df	MS	Number of obs	=	74
Model	91.1761694	2	45.5880847	F(2, 71)	=	113.97
Residual	28.4000913	71	.400001287	Prob > F	=	0.0000
				R-squared	=	0.7625
				Adj R-squared	=	0.7558
Total	119.576261	73	1.63803097	Root MSE	=	.63246

gp100m	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]
weight	.0016254	.0001183	13.74	0.000	.0013896 .0018612
foreign	.6220535	.1997381	3.11	0.003	.2237871 1.02032
_cons	-.0734839	.4019932	-0.18	0.855	-.8750354 .7280677

We find that foreign cars had better gas mileage than domestic cars in 1978 because they were so light. According to our model, a foreign car with the same weight as a domestic car would use an additional 5/8 gallon (or 5 pints) of gasoline per 100 miles driven. With this conclusion, we are satisfied with our analysis.

## Commands versus menus

In this chapter, you have seen that Stata can operate either with menu choices and dialogs or with the Command window. As you become more familiar with Stata, you will find that the Command window is typically much faster for oft-used commands, whereas the menus and dialogs are faster when building up complex commands, such as those that create graphs.

One of Stata's great strengths is the consistency of its *command syntax*. Most of Stata's commands share the following syntax, where square brackets mean that something is optional, and a *varlist* is a list of variables.

```
[prefix:] command [varlist] [if] [in] [weight] [, options]
```

Some general rules:

- Most commands accept prefix commands that modify their behavior; see [U] 11.1.10 **Prefix commands** for details. One of the common prefix commands is `by`.
- If an optional *varlist* is not specified, all the variables are used.
- *if* and *in* restrict the observations on which the command is run.
- *options* modify what the command does.
- Each command's syntax is found in the system help and the reference manuals.
- Stata's command syntax includes more than we have shown you here, but this introduction should get you started. For more information, see [U] 11 **Language syntax** and `help language`.

We saw examples using all the pieces of this except for the `in` qualifier and the `weight` clause. The syntax for all commands can be found in the system help along with examples—see [GSM] 4 **Getting help** for more information. The consistent syntax makes it straightforward to learn new commands and to read others' commands when examining an analysis.

Here is an example of reading the syntax diagram that uses the `summarize` command from earlier in this chapter. The syntax diagram for `summarize` is typical:

```
summarize [varlist] [if] [in] [weight] [, options]
```


This means that

<i>command</i> by itself is valid:	<code>summarize</code>
<i>command</i> followed by a <i>varlist</i> (variable list) is valid:	<code>summarize mpg</code> <code>summarize mpg weight</code>
<i>command</i> with <i>if</i> (with or without a <i>varlist</i> ) is valid:	<code>summarize if mpg&gt;20</code> <code>summarize mpg weight if mpg&gt;20</code>
and so on.	

You can learn about `summarize` in [R] [summarize](#), or select **Help > Stata command...** and enter `summarize`, or type `help summarize` in the Command window.

## Keeping track of your work

It would have been useful if we had made a log of what we did so that we could conveniently look back at interesting results or track any changes that were made. You will learn to do this in [\[GSM\] 16 Saving and printing results by using logs](#). Your logs will contain commands and their output—another reason to learn command syntax is so that you can remember what you have done.

To make a log file that keeps track of everything appearing in the Results window, click on the **Log** button, which looks like a lab notebook, . Choose a place to store your log file, and give it a name, just as you would for any other document. The log file will save everything that appears in the Results window from the time you start a log file to the time you close it.

## Video example

[What's it like—Getting started in Stata](#)


## Conclusion

This chapter introduced you to Stata's capabilities. You should now read and work through the rest of this manual. Once you are done here, you can read the *User's Guide*.

# 2 The Stata user interface

## The windows

This chapter introduces the core of Stata’s interface: its main windows, its toolbar, its menus, and its dialogs.



The five main windows are the History, Results, Command, Variables, and Properties windows. Each window has its name in its title bar. These five windows are typically in use the whole time Stata is open. There are other, more specialized windows such as the Viewer, Data Editor, Variables Manager, Do-file Editor, Graph, and Graph Editor windows—these are discussed later in this manual.

To open any window or to reveal a window hidden by other windows, select the window from the **Window** menu, or select the proper item from the toolbar. You can also use Mission Control to reveal hidden windows, or use *Command-`* (left quote) to cycle through all open Stata windows. Many of Stata’s windows have functionality that can be accessed by clicking on the right mouse button (right-clicking) within the window. If your mouse has only one button, press the *Control* key while pressing the mouse button to simulate a right-click. Right-clicking displays a contextual menu that, depending on the window, allows you to copy text, set the preferences for the window, or print the contents of the window. When you copy text or print, we recommend that you always right-click

on the window rather than use the menu bar or toolbar so that you can be sure of where and what you are copying or printing.


## The toolbar


This is the toolbar:





The toolbar contains buttons that provide quick access to Stata's more commonly used features. If you forget what a button does, hold the mouse pointer over the button for a moment, and a tooltip will appear with a description of that button.


Buttons that include both an icon and an arrow display a menu if you hold down the mouse button. Here is an overview of the toolbar buttons and their functions:


 **Open** opens a Stata dataset. Click on the button to open a dataset with the *Open* dialog. Click on the arrow to select a dataset from a menu of recently opened datasets.


 **Save** saves the Stata dataset currently in memory to disk.

 **Log** begins a new log or closes, suspends, or resumes the current log. See [\[GSM\] 16 Saving and printing results by using logs](#) for an explanation of log files. You can also choose a file to view in the Viewer.


 **Viewer** opens the Viewer or brings a Viewer to the front of all other windows. Click on the button to open a new Viewer tab. See [\[GSM\] 3 Using the Viewer](#) for more information.

 **Graph** brings the Graph window to the front of all other windows. Click on the button to bring the topmost Graph window to the front. Click on the arrow to select a graph to bring to the front. See [The Graph button](#) in [\[GSM\] 14 Graphing data](#) for more information.


 **Do-file Editor** opens the Do-file Editor or brings a Do-file Editor to the front of all other windows. Click on the button to open a new Do-file Editor. Click on the arrow to select a Do-file Editor tab to bring to the front. See [\[GSM\] 13 Using the Do-file Editor—automating Stata](#) for more information.

 **Data Editor (Edit)** opens the Data Editor or brings the Data Editor to the front of the other Stata windows. See [\[GSM\] 6 Using the Data Editor](#) for more information.

 **Data Editor (Browse)** opens the Data Editor in browse mode. See [Browse mode](#) in [\[GSM\] 6 Using the Data Editor](#) for more information.

 **More** tells Stata to continue when it has paused in the middle of long output. Click on the arrow to choose whether to run the command to completion. See [\[GSM\] B.5 More](#) for more information.

 **Break** stops the current task in Stata. See [\[GSM\] 10 Listing data and basic command syntax](#) for more information.



**Search Help** Searches for help for both official and community-contributed commands. See [GSM] 4 **Getting help** for more information.

## The Command window

Commands are submitted to Stata from the Command window. The Command window supports basic text editing, copying and pasting, a command history, function-key mapping, filename completion, and variable-name completion. The Command window also uses the same syntax highlighting as the Do-file Editor. See [GSM] 13 **Using the Do-file Editor—automating Stata** for more information.

From the Command window, pressing


- Page Up* steps backward through the command history.
- Page Down* steps forward through the command history.
- Tab* autocompletes a partially typed variable name when possible or presents a list of similar names if there could be more than one completion. Further typing will narrow the list. As soon as the name is complete, the full name will be inserted. If the name starts with a double quote, *Tab* attempts to autocomplete a filename in the same manner.

See [U] 10 **Keyboard use** for more information about keyboard shortcuts for the Command window.

The command history allows you to recall a previously submitted command, edit it if you wish, and then resubmit it. Commands submitted by Stata's dialogs are also included in the command history, so you can recall and submit a command without having to open the dialog again.

## The Results window

The Results window contains all the commands and their textual results you have entered during the Stata session.

You can scroll through the Results window to look at work you have done, it is much simpler to search within the Results window by using the find bar. By default, the find bar is hidden. You can toggle its visibility by clicking the **Find** button,  in the Results window title bar.

You can clear out the Results window at any time by right-clicking in the Results window and selecting **Clear results** from the contextual menu. This action is not undoable.

## The Sidebar

The sidebar in the main window has three tabs for controlling what it shows.



**Variables** shows the *Variables* and *Properties* windows.



**History** shows the *History* window.



**Project Manager** shows the *Project Manager* window.

By default, the **Variables** tab is active, showing the *Variables* and *Properties* windows. The behavior of the *Variables* and *History* windows are explained below. For more information on the Project Manager, see [P] **Project Manager**.

## The Variables window

The Variables window shows the list of variables in the dataset, along with the properties of the variables. By default, it shows all the variables and their variable labels. You can change what properties get displayed by right-clicking on the header of any column of the Variables window.

Click once on a variable in the Variables window to select it. Multiple variables can be selected in the usual fashion, either by *Command*-clicking on nonadjacent variables or by clicking on a variable and *Shift*-clicking on a second variable to select all intervening variables.

Double-clicking on a variable in the Variables window puts the selected variable at the insertion point in the Command window. If multiple variables are selected, double-clicking on any selected variable will put all the selected variables at the insertion point in the Command window.

The leftmost column of the Variables window is called the one-click paste column. You can also send variables to the Command window by hovering the mouse over the one-click paste column of the Variables window and clicking on the arrow that appears.

The Variables window supports filtering and changing the display order of the variables. Text entered in the entry field to the right of the magnifying glass will filter the variables appearing in the Variables window. The filter is applied to all visible columns and shows all variables that match the criteria in at least one column. By default, the filter will ignore case and show any variables for which at least one column contains any of the words in the filter. Clicking on the arrow by the magnifying glass will allow you to change this behavior.

You can change the display order of the variables in the Variables window by clicking on any column header. The first click sorts in ascending order, the second click sorts in descending order, and the third click puts the variables back in dataset order. Thus clicking on the *Name* column header will make the Variables window display the variables in alphabetical order. Sorting in the Variables window is live, so if you change a property of a variable when the Variables window is sorted by that property, it will automatically move the variable to its proper location. Reordering the display order of the variables in the Variables window does not affect the order of the variables in the dataset itself.

Right-clicking on a variable in the Variables window displays a menu from which you can select

- **Keep only variable** “*varname*” (or **Keep only selected variables** if multiple variables are selected) to keep just the selected variables in the dataset in memory. You will be asked for confirmation. This affects only the dataset in memory, not the dataset as saved on your disk. See [\[GSM\] 12 Deleting variables and observations](#) for more information.
- **Drop variable** “*varname*” (or **Drop selected variables** if multiple variables are selected) to drop, or eliminate, the selected variables from the dataset in memory. You will be asked for confirmation. Just as above, this affects only the dataset in memory, not the dataset as saved on your disk. See [\[GSM\] 12 Deleting variables and observations](#) for more information.
- **Copy varlist** to copy the selected variable names to the clipboard.
- **Select all** to select all variables in the dataset that satisfy the filter conditions. If no filter has been specified, all variables will be selected.
- **Send varlist to Command window** to send all selected variables to the Command window.
- **Preferences...** to change the preferences for the Variables window.
- **Output compact varlist (e.g., v1-v4)** toggles the preference for shortening the list of variables by variable ranges in place of individual variable names.

Items from the contextual menu issue standard Stata commands, so working by right-clicking is just like working directly in the Command window.





If you would like to hide the Variables window, grab the divider between the Variables window and the Results window and drag it all the way to the right. This is like resizing the Variables window to have zero width. Hiding the Variables window will also hide the Properties window.

To reveal a hidden Variables window, select **Window > Variables**.

## The Properties window


The Properties window displays variable and dataset properties. If a single variable is selected in the Variables window, its properties are displayed. If there are multiple variables selected in the Variables window, the Properties window will display properties that are common across all selected variables.

Clicking the lock icon in the Properties window title bar toggles the ability to alter properties of the selected variables. By default, changes are not allowed. Once the properties are unlocked, you can make any changes to variable or dataset properties you like. Each change you make will create a command that appears in the Results and Command windows, as well as in any command log, so the changes are reproducible. Using the Properties window is one of the simplest ways of managing notes, changing variable and value labels, and changing display formats. See [D] [notes](#), [D] [label](#), and [D] [format](#).

Clicking the arrow buttons next to the lock icon will select the previous or next variable shown in the Variables window, and that selection will be reflected in the Properties window. If you would like to hide the Properties window, click on the disclosure control  at the base of the Variables window. If you would like to reveal a hidden Properties window, click on the disclosure control  at the base of the Variables window.

You should also investigate the Variables Manager, explained in [GSM] 7 [Using the Variables Manager](#), because it extends these capabilities and provides a good interface for managing variables.

## The History window

The History window shows the history of commands that have been entered, with unsuccessful commands and their error codes in red, by default. By default, the History window is on a tab in the sidebar. You can show the History window by clicking on the **History** button, , in the sidebar.

At the base of the History window is a text entry field that filters the commands appearing in the History window. By default, the filter ignores case and finds any commands containing any of the words in the filter. Clicking on the arrow by the magnifying glass allows you to change this behavior. You can hide the commands that produced an error by clicking on the arrow and selecting the *Hide Errors* item from the list that appears.

No commands are deleted by using these tools—all that is affected is their visibility.

To enter a command from the History window, you can

- Click once on a past command to copy it to the Command window, replacing the contents of the Command window.
- Double-click on a past command to resubmit it. Executing the command adds the command to the bottom of the History window.

Right-clicking on the History window displays a menu from which you can select various actions:


- **Cut** removes the selected commands from the History window and places them on the Clipboard.
- **Copy** copies the selected commands to the Clipboard.

- **Delete** removes the selected commands from the History window.
- **Select all** selects all the commands in the History window, including those before and after the commands currently displayed.
- **Clear all** clears out all the commands from the History window, including those before and after the commands currently displayed.
- **Do selected** submits all the selected commands and adds them to the bottom of the command history. Stata will attempt to run all the selected commands, even those containing errors, and will not stop even if a command causes an error.
- **Send selected to Do-file Editor** places all the selected commands into a new Do-file Editor window.
- **Save all...** brings up a *Save review contents* dialog, which allows you to save all the commands in the History window, including those before and after the commands currently displayed, in a *do-file*. (See [GSM] 13 Using the Do-file Editor—automating Stata for more information on *do-files*.)
- **Save selected...** brings up a *Save review contents* dialog, which allows you to save the selected commands in the History window in a *do-file*.
- **Preferences...** allows you to edit the preferences for the History window.

If you would like to pull the History window into a sidebar on the left of the *Results* window so that it is always visible, choose **View > Layout > Widescreen**. After you do this, you might need to widen the main window so that your results will not wrap. Simply hover the pointer over the left or right side of the window until it becomes a resizing symbol, and then drag outward.

To go back to having the History window in the sidebar, choose **View > Layout > Sidebar**.

## Tabs


All windows in Stata can have multiple tabs. If you drag a tab off tab bar, it will create a new window. You may drag a tab from any window and drop it on the tab bar of any other window to move a tab from one window to another. If you do not see the tab bar on a window because the window contains only one tab, you can select **View > Tab bar** to make the tab bar visible. By default, windows of the same type are tabbed together. So, for example, when you create a new *Do-file Editor*, say, it will be put in a window with other *Do-file Editors*. If you click on the **Create new tab** button, , a new tab of the same type as the active tab will be created, unless, of course, it does not make sense to have a second tab of that type (such as the *Results* window). You can change the order of the tabs by dragging the tabs along the tab bar within the window.

If you would like to change the behavior of the tabbing, select **Stata > Preferences > General preferences...**, and select the **Windows** tab in the preference pane, and then select the type of window whose tabbing behavior you would like to change.

## Menus and dialogs

There are two ways by which you can tell Stata what you would like it to do: you can use menus and dialogs, or you can use the Command window. When you worked through the sample session in [GSM] 1 Introducing Stata—sample session, you saw that both ways have strengths. We will discuss the menus and dialogs here.

Stata's **Data**, **Graphics**, and **Statistics** menus provide point-and-click access to almost every command in Stata. As you will learn, Stata is fully programmable, and Stata users can even create their own dialogs and menus. The **User** menu provides a place for programmers to add their own menu items. Initially, it contains only some empty submenus. As an example, suppose you wish to perform a Poisson regression. You could type Stata's `poisson` command, or you could select **Statistics > Count outcomes > Poisson regression**, which would display this dialog:



This dialog provides access to all the functionality of Stata's `poisson` command. Because the dependent and independent variables must be numeric, you will find that the combo box will display only numeric variables for choosing. The `poisson` command has many options that can be accessed by clicking on the multiple tabs across the top of the dialog. The first time you use the dialog for a command, it is a good idea to look at the contents of each tab so that you will know all the dialog's capabilities.

The dialogs for many commands have the **by/if/in** and **Weights** tabs. These provide access to Stata's commands and qualifiers for controlling the estimation sample and dealing with weighted data. See [U] 11 **Language syntax** for more information on these features of Stata's language.

The dialogs for most estimation commands have the **Maximization** tab for setting the maximization options (see [R] [Maximize](#)). For example, you can specify the maximum number of iterations for the optimizer.

Most dialogs in Stata provide the same six buttons you see at the bottom of the *poisson* dialog above.



**OK** issues a Stata command based on how you have filled out the fields in the dialog and then closes the dialog.



**Cancel** closes the dialog without doing anything—just as clicking on the dialog’s red close button does.



**Submit** issues a command just like **OK** but leaves the dialog on the screen so that you can make changes and issue another command. This feature is handy when, for example, you are learning a new command or putting together a complicated graph.



**Help** provides access to Stata’s help system. Clicking on this button will typically take you to the help file for the Stata command associated with the dialog. Clicking on it here would take you to the *poisson* help file. The help file will have tabs above groups of options to show which dialog tab contains which options.



**Reset** resets the dialog to its default state. Each time you open a dialog, it will remember how you last filled it out. If you wish to reset its fields to their default values at any time, simply click on this button.



**Copy command to Clipboard** behaves much like the **Submit** button, but rather than issuing a command, it copies the command to the Clipboard. The command can then be pasted elsewhere (such as in the Do-file Editor).

The command issued by a dialog is submitted just as if you had typed it by hand. You can see the command in the Results window and in the History window after it executes. Looking carefully at the full command will help you learn Stata’s command syntax.

In addition to being able to access the dialogs for Stata commands through Stata’s menus, you can also invoke them by using two other methods. You may know the name of a Stata command for which you want to see a dialog, but you might not remember how to navigate to that command in the menu system. Simply type `db commandname` to launch the dialog for *commandname*:

```
. db poisson
```

You will also find access to the dialog for a command in that command’s help file; see [GSM] 4 [Getting help](#) for more details.

As you read this manual, we will present examples of Stata commands. You may type those examples as presented, but you should also experiment with submitting those commands by using their dialogs. Use the `db` command described above to quickly launch the dialog for any command that you see in this manual.

## The working directory


If you look at the screenshot on page 24, you will notice the status bar at the base of the main Stata window that contains the name of the current working directory `/Users/stata/Documents/Stata`. This path indicates that `/Users/stata/Documents/Stata` is the current working directory. Each session, this is set to the working directory you were using when you last quit Stata. The current working directory is the folder where graphs and datasets will be saved when typing commands such as `save filename`. It does not affect the behavior of menu-driven file actions such as **File > Save** or **File > Open....** Once you have started Stata, you can change the current working directory with the `cd` command. See [D] `cd` for full details. Stata always displays the name of the current working directory so that it is easy to tell where your graphs and datasets will be saved.

# 3 Using the Viewer

## The Viewer's purpose

The Viewer is a versatile tool in Stata. It will be the first place you can turn for help within Stata, but it is far more than just a help system. You can also use the Viewer to add, delete, and manage third-party extensions to Stata that are known as *community-contributed commands*; to view and print Stata logs from both your current and your previous Stata sessions; to view and print any other Stata-formatted (SMCL) or plain-text file; and even to launch your web browser to follow hyperlinks.

This chapter focuses on the general use of the Viewer, its buttons, and a brief summary of the commands that the Viewer understands. There is more information about using the Viewer to find help in [\[GSM\] 4 Getting help](#) and for installing community-contributed commands in [\[GSM\] 19 Updating and extending Stata—Internet functionality](#).

To open a new Viewer window (or open a new tab in an existing Viewer), you can either click on the **Viewer** button, , or select **Window > Viewer > New Viewer**.

## Viewer buttons

The toolbar of the Viewer has multiple buttons, a command box, and a search box.



**Back** goes back one step in your viewing trail.



**Forward** goes forward one step in your viewing trail, assuming you backtracked.



**Reload** refreshes the Viewer, in case you are viewing something that has changed since you opened the Viewer.



**Find** opens the find bar at the bottom of the Viewer (see below).



**Search** Chooses the scope of help searches in the Viewer.

The Find bar is used to find text within the current Viewer. To reveal the Find bar at the bottom of the window, click on the **Find** button:



The Find bar has its own buttons, fields, and checkboxes.



**Find** is the field for entering the search text you would like to find. You can change the search options by clicking on the down arrow near the magnifying glass.



**Previous** Jumps to the previous instance of the search text; it automatically wraps past the start of the Viewer document if there are no previous instances of the search text.



**Next** jumps to the next instance of the search text; it automatically wraps past the end of the Viewer document if there are no further instances of the search text.



**Done** closes the find bar.

## Viewer's function


The Viewer is similar to a web browser. It has links (shown in blue text by default) that you can click on to see related help topics and to install and manage third-party software. When you move the mouse pointer over a link, the status bar at the bottom of the Viewer shows the action associated with that link. If the action of a link is `help logistic`, clicking on that link will show the help file for the `logistic` command in the Viewer. *Command*-clicking on a link in a Viewer window (or middle-clicking if you have a three-button mouse) will open the link in a new tab in the Viewer window. *Shift*-clicking will open the link in a new Viewer window.

You can open a new Viewer by selecting **Window > Viewer > New Viewer** or by clicking on the **Viewer** button on the toolbar of the main window. Entering a `help` command from the Command window will also open a new Viewer.

To bring a Viewer to the front of all other Viewers, select **Window > Viewer** and choose a Viewer from the list there. Selecting **Close all Viewers** closes all open Viewer window and tabs.

## Viewing local text files, including SMCL files

In addition to viewing built-in Stata help files, you can use the Viewer to view Stata Markup and Control Language (SMCL) files such as those typically produced when logging your work (see [\[GSM\] 16 Saving and printing results by using logs](#)) as well as plain-text files. To open a file and view its contents, simply select **File > View...**, and you will be presented with a dialog:



You may either type in the name of the file that you wish to view and click on **OK**, or you may click on the **Browse...** button to open a standard file dialog that allows you to navigate to the file.

If you currently have a log file open, you may view the log file in the Viewer. This method has one advantage over scrolling back in the Results window: what you view stays fixed even as output is added to the Results window. If you wish to view a current log file, select **File > Log > View...**, and the usual dialog will appear but with the path and filename of the current log already in the field. Simply click on **OK**, and the log will appear in the Viewer. See [GSM] 16 **Saving and printing results by using logs** for more details.

## Viewing remote files over the Internet

If you want to look at a remote file over the Internet, the process is similar to viewing a local file, only instead of using the **Browse...** button, you type the URL of the file that you want to see, such as <https://www.stata.com/man/readme.smcl>. You should use the Viewer only to view text or SMCL files. If you enter the URL of, say, an arbitrary webpage, you will see the HTML source of the page instead of the usual browser rendering.

## Navigating within the Viewer

In addition to using the scrollbar to navigate the Viewer window, you also can use the up and down arrow keys and *Page Up* and *Page Down* keys to do the same. Pressing the up or down arrow key scrolls the window a line at a time. Pressing the *Page Up* or *Page Down* key scrolls the window a screen at a time.

## Printing

To print the contents of the Viewer, right-click on the window and select **Print...** You may also select **File > Print > Viewer name** to print.

## Right-clicking on the Viewer window

Right-clicking on the Viewer window displays a contextual menu that offers these options:

- **Select all** to select all text in the Viewer.
- **Preferences...** to edit the preferences for the Viewer window.
- **Print...** to print the contents of the Viewer window.

In other contexts, there could be more items displayed in the contextual menu.

## Searching for help in the Viewer

The search box in the Viewer can be used to search documentation. Click on the magnifying glass; choose *Search all*, *Search documentation and FAQs*, or *Search net resources*; and then type a word or phrase in the search box and press *Return*. For more extensive information about using the Viewer for help, see [GSM] 4 **Getting help**.



## Commands in the Viewer

Everything that can be done in the Viewer by clicking on links and buttons can also be done by typing commands in the command box at the top of the window or on the Stata command line. Some tasks that can be performed in the Viewer are

- obtaining help (see [GSM] 4 Getting help):
  - Type `contents` to view the contents of Stata's help system.
  - Type `commandname` to view the help file for a Stata command.
  - Type `keyword` to search documentation, FAQs, and net resources for a topic.
- searching (see [GSM] 4 Getting help):
  - Type `search keyword` to search documentation, FAQs, and net resources for a topic.
  - Type `search keyword, local` to search only documentation and FAQs for a topic.
  - Type `search keyword, net` to search only net resources for a topic.
- finding and installing community-contributed commands (see [GSM] 4 Getting help and [GSM] 19 Updating and extending Stata—Internet functionality):
  - Type `net from https://www.stata.com/` to find and install *Stata Journal*, *Stata Technical Bulletin*, and community-contributed commands from the Internet.
  - Type `ado` to review community-contributed packages you have installed.
  - Type `ado uninstall` to uninstall community-contributed packages you have installed on your computer.
- viewing files in the Viewer:
  - Type `view filename.smcl` to view SMCL files.
  - Type `view filename.txt` to view text files.
  - Type `view filename.log` to view text log files.
- viewing files in the Results window:
  - Type `type filename.smcl` in the Command window to view SMCL files in the Results window.
  - Type `type filename.txt` in the Command window to view text files in the Results window.
  - Type `type filename.log` in the Command window to view text log files in the Results window.
- launching your browser to view an HTML file:
  - Type `browse URL` to launch your browser.

## Using the Viewer from the Command window

Typing `help commandname` in the Command window will bring up a new Viewer showing the requested help.

# 4 Getting help

## System help

Stata's help system provides a wealth of information to help you learn and use Stata. To find out which Stata command will perform the statistical or data management task you would like to do, you should generally follow these steps:

1. Select **Help > Search...**, choose *Search all*, and enter the topic or keywords. This search will open a new Viewer window containing information about Stata commands, references to articles in the *Stata Journal*, links to Frequently Asked Questions (FAQs) on Stata's website, links to videos on Stata's YouTube channel, links to selected external websites, and links to community-contributed commands.
2. Read through the results. If you find a useful command, click on the link to the appropriate command name to open its help file.
3. Read the help file for the command you chose.
4. If you want more in-depth help, click on the link from the name of the command to the PDF documentation, read it, then come back to Stata.
5. If the first help file you went to is not what you wanted, either click on the **Also see** menu and choose a link to related help files or click on the **Back** button to go back to the previous document and go from there to other help files.
6. With the help file open, click on the Command window and enter the command, or click on the **Dialog** button and choose a link to open a dialog for the command.
7. If, at any time, you want to begin again with a new search, enter the new search terms in the search box of the Viewer window.
8. If you select *Search documentation and FAQs*, Stata searches its keyword database for official Stata commands, *Stata Journal* articles and software, FAQs, and videos. If you select *Search net resources*, Stata searches for community-contributed commands, whether they are from the *Stata Journal* or elsewhere; see [\[GSM\] 19 Updating and extending Stata—Internet functionality](#) for more information.


Let's illustrate the help system with an example. You will get the most benefit from the example if you work along at your computer.

Suppose that we have been given a dataset about antique cars and that we need to know what it contains. Though we still have a vague notion of having seen something like this while working through the example session in [\[GSM\] 1 Introducing Stata—sample session](#), we do not remember the proper command.


Start by typing `sysuse auto, clear` in the Command window to bring the dataset into memory. (See [\[GSM\] 5 Opening and saving Stata datasets](#) for information on the `clear` option.)

Follow the above approach:


1. Select **Help > Search...**
2. Check that the *Search all* radio button is selected.
3. Type `dataset contents` into the search box and click on **OK** or press *Return*. Before we press *Return*, the window should look like



4. Stata will now search for “dataset contents” among the Stata commands, the reference manuals, the *Stata Journal*, the FAQs on Stata’s website, and community-contributed commands. Here is the result:



5. Upon seeing the results of the search, we see two commands that look promising: `codebook` and `describe`. Because we are interested in the contents of the dataset, we decide to check out the `codebook` command. The [D] means that we could look up the `codebook` command in the *Data Management Reference Manual*. The `codebook` link in (`help codebook`) means that there is a system help file for the `codebook` command. This is what we are interested in right now.
6. Click on the `codebook` link. Links can take you to a variety of resources, such as help for Stata commands, dialogs, and even webpages. Here the link goes to the help file for the `codebook` command.



[D] `codebook` — Describe data contents  
([View complete PDF manual entry](#))

**Syntax**


```
codebook [varlist] [if] [in] [, options]
```

<i>options</i>	Description
<code>all</code>	print complete report without missing values
<code>header</code>	print dataset name and last saved date
<code>notes</code>	print any notes attached to variables
<code>mv</code>	report pattern of missing values
<code>tabulate(#)</code>	set tables/summary statistics threshold; default is <code>tabulate(9)</code>

7. What is displayed is typical for help for a Stata command. Help files for Stata commands contain, from top to bottom, these features:
  - a. The quick access toolbar with three buttons:
    - i. The **Dialog** button shows links to any dialogs associated with the command.
    - ii. The **Also see** button shows links to related PDF documentation and help files.
    - iii. The **Jump to** button shows links to other sections within the current help file.
  - b. The second line of a help file shows a `View complete PDF manual entry` link. Clicking on the link will open the complete documentation for the command—in this case, `codebook`—in your PDF viewer.
  - c. The command's syntax, that is, rules for constructing a command that Stata will correctly interpret. The square brackets here indicate that all the arguments to `codebook` are optional but that if we wanted to specify them, we could use a *varlist*, an *if* qualifier, or an *in* qualifier, along with some options. (Options vary greatly from command to command.) The options are listed directly under the command and are explained in some detail later in the help file. You will learn more about command syntax in [\[GSM\] 10 Listing data and basic command syntax](#).

- d. A description of the command. Because “codebook” is the name for big binders containing a hard copy describing each of the elements of a dataset, the description for the codebook command is justifiably terse.
- e. The options that can be used with this command. These are explained in much greater detail than in the listing of the possible options after the syntax. Here, for example, we can see that the `mv` option can look to see if there is a pattern in the missing values—something important for data cleaning and imputation.
- f. Examples of command usage. The codebook examples are real examples that step through using the command on a dataset either shipped with Stata or loadable within Stata from the Internet.
- g. The information the command stores in the returned results. These results are used primarily by programmers.

For now, either click on **Jump to** and choose **Examples** from the drop-down menu or scroll down to the examples. It is worth going through the examples as given in the help file. Here is a screenshot of the top of the examples:



### **Examples**

With standard (monolingual) datasets,

---

Setup

```
. sysuse auto
. note rep78: "investigate missing values"
. label values rep78 repairlbl
```

Display codebook for all variables in dataset

```
. codebook
```

Same as above command

```
. codebook _all
```

Same as above command, but print dataset name, date last saved, dataset label, number of variables and of observations, and dataset size

## Searching help

**Search** is designed to help you find information about statistics, graphics, data management, and programming features in Stata, either as part of the official release or as community-contributed commands. When entering topics for the search, use appropriate terms from statistics, etc. For example, you could enter *Mann-Whitney*. Multiple topic words are allowed, for example, *regression residuals*.

When you are using **Search**, use proper English and proper statistical terminology. If you already know the name of the Stata command and want to go directly to its help file, select **Help > Stata command...** and type the command name. You can also type the command name in the *Search* field at the top of the Viewer and press *Return*.

**Help** distinguishes between topics and Stata commands because some names of Stata commands are also general topic names. For example, *logistic* is a Stata command. If you choose **Stata command...** and type *logistic*, you will go right to the help file for the command. But if you choose **Search...** and type *logistic*, you will get search results listing the many Stata commands that relate to logistic regression.

Remember that you can search for help from within a Viewer window by typing a command in the command box of the Viewer or by clicking the magnifying glass button to the left of the search box, selecting the scope of your search, typing the search criteria in the search box, and pressing *Return*.

## Help and search commands

As you might expect, the help system is accessible from the Command window. This feature is especially convenient when you need help on a particular Stata command. Here is a short listing of the various commands you can use:

- Typing `help commandname` is equivalent to selecting **Help > Stata command...** and typing `commandname`. The help file for the command appears in a new Viewer tab.
- Typing `search topic` in the Command window produces the same output as selecting **Help > Search...**, choosing *Search all*, and typing `topic`. The output appears in a new Viewer tab.
- Typing `search topic, local` in the Command window produces the same output as selecting **Help > Search...**, choosing *Search documentation and FAQs*, and typing `topic`. The output appears in the Results window instead of a Viewer.
- Typing `search topic, net` in the Command window produces the same output as selecting **Help > Search...**, choosing *Search net resources*, and typing `topic`. The output appears in the Results window instead of a Viewer.

See [\[U\] 4 Stata's help and search facilities](#) and [\[U\] 4.8 search: All the details](#) in the *User's Guide* for more information about these command-language versions of the help system. The `search` command, in particular, has a few capabilities (such as author searches) that we have not demonstrated here.

## The Stata reference manuals and User's Guide

All the Stata reference manuals come as PDF files and are included with the software. The manuals themselves have many cross-references in the form of clickable links, so you can easily read the documentation in a nonlinear way.

Many of the links in the help files point to the PDF manuals that came with Stata. It is worth clicking on these links to read the extensive information found in the manuals. The Stata help system, though extensive, contains only a fraction of the information found in the manuals.

Most Stata reference manuals are each arranged alphabetically. Each *Getting Started with Stata* has its own index. A combined index for all other manuals can be found in the *Glossary and Index*. This combined index is a good place to start when you are looking for information about a command.

Entries have names like **collapse**, **egen**, and **summarize**, which are generally themselves Stata commands.

Notations such as [R] **ci**, [R] **regress**, and [R] **ttest** in the **Search** results and help files are references to the *Base Reference Manual*. You may also see things like [P] **python**, which is a reference to the *Programming Reference Manual*, and [U] **12 Data**, which is a reference to the *User's Guide*. For a complete list of manuals and their shorthand notations, see *Cross-referencing the documentation*, which immediately follows the table of contents in this manual.

For advice on how to use the reference manuals, see [GSM] **18 Learning more about Stata**, or see [U] **1.2 The User's Guide and the Reference manuals**.

## Stata videos

The [Stata YouTube channel](#) is an excellent resource for learning about Stata. The brief videos demonstrate many topics using Stata's graphical user interface. They cover basic topics, such as data management, graphics, summary statistics, and hypothesis testing, and advanced topics, such as multilevel models and structural equation models.

There are also several playlists that provide a series of videos about a topic in sequence. For example, the "Power and sample size calculations" playlist includes videos about how to calculate power, sample size, and effect size for two independent proportions and for paired samples. The "Survival analysis" playlist takes you through the process of setting your data up for survival analysis, conducting basic descriptive analysis of survival data, graphing survival data, and calculating survivor functions and life tables. The "Time series" playlist takes you through the process of setting your data up for time-series analysis, creating time-series graphs, using time-series operators in estimation, and fitting ARMA and ARIMA models. There is even a "Back-to-school video" playlist for students who are using Stata for the first time or want a refresher after summer break.

See <https://www.stata.com/links/video-tutorials/> for an up-to-date list of videos organized by topic. The playlists can be accessed directly at <https://www.youtube.com/user/statacorp/>.

## The Stata Journal

When searching in Stata, you will often see links to the *Stata Journal*.

The *Stata Journal* is a printed and electronic journal, published quarterly, containing articles about statistics, data analysis, teaching methods, and effective use of Stata's language. The *Journal* publishes peer-reviewed papers together with shorter notes and comments, regular columns, tips, book reviews, and other material of interest to researchers applying statistics in a variety of disciplines. The *Journal* is a publication for all Stata users, both novice and experienced, with different levels of expertise in statistics, research design, data management, graphics, reporting of results, and Stata, in particular. See <https://www.stata-journal.com> for more information.

Associated with each issue of the *Stata Journal* are the programs and datasets described therein. These programs and datasets are made available for download and installation over the Internet, not only to subscribers but also to all Stata users. See [R] **net** and [R] **sj** for more information.

Because the *Stata Journal* has had several articles about measures of inequality, if you select **Help > Search...**, choose *Search documentation and FAQs*, type *inequality*, and scroll down a bit, you will see some of these references:

The screenshot shows a search viewer window titled "Viewer — search inequality, local". The search bar contains "search inequality, local". The results are listed as follows:

```

SJ-18-3 st0539 Measuring inequality from incomplete income and survival data
. . . . . L. Hong, G. Alfani, C. Gigliarano, and M. Bonetti
(help survgini, survbound, survsl if installed)
Q3/18 SJ 18\(3\):692--715
measures the Gini index from incomplete income and survival data

SJ-18-3 st0427\_2 . . . . . Software update for conindex
. . . . . O. O'Donnell, S. O'Neill, T. Van Ourti, and B. Walsh
(help conindex if installed)
Q3/18 SJ 18\(3\):758--759
uses the community-contributed lorenz command and fix a small bug
in the graph option

SJ-17-1 st0467 . . . . Testing conditional moment inequalities and equalities
. . . . . D. W. K. Andrews, W. Kim, and X. Shi
(help cmi\_test, cmi\_interval if installed)
Q1/17 SJ 17\(1\):56--72
implements testing and inference methods for conditional moment
inequality or equality models proposed in Andrews and Shi (2013,
Econometrica 81: 609-666)

SJ-16-4 st0457 . . . . . Estimating Lorenz and concentration curves
(help lorenz if installed) . . . . . B. Jann
Q4/16 SJ 16\(4\):837--866
estimates Lorenz and concentration curves from individual-level
data and, optionally, displays the results in a graph

SJ-16-2 st0432 . . . . . Assessing inequality using percentile shares
(help pshare if installed) . . . . . B. Jann
Q2/16 SJ 16\(2\):264--300
estimates percentile shares from individual-level data and
displays the results using histograms or stacked bar charts

```

SJ-18-3 refers to volume 18, number 3 of the *Stata Journal*. [st0539](#) refers to the package name; `st` indicates that this package is in the “statistics” category of the *Stata Journal*. Listed next is the title of the software package and the authors. The community-contributed commands found within this package are listed next in parentheses, followed by the reference details of the article. Clicking on an SJ link, such as [SJ 18\(3\):692--715](#), will open a browser and take you to the *Stata Journal* website, where you can view the abstract of the article and purchase the article. The search listing concludes with a brief description of the community-contributed package.

The *Stata Journal* website allows all articles older than three years to be downloaded for free. See [Downloading community-contributed commands](#) in [GSM] 19 **Updating and extending Stata—Internet functionality** for more details on how to install community-contributed software. Also see [R] [ssc](#) for information on a convenient interface to resources available from the Statistical Software Components (SSC) archive.



We recommend that all users subscribe to the *Stata Journal*. See [U] 3.4 **The Stata Journal** for more information.

Links to other sites where you can freely download programs and datasets for Stata can be found on the Stata website; see <https://www.stata.com/links/>.

# 5 Opening and saving Stata datasets

## How to load your dataset from disk and save it to disk

Opening and saving datasets in Stata works similarly to those tasks in other computer applications. There are a few differences, however. First, it is possible to save and open files from within Stata's Command window. Second, Stata allows just one dataset to be active at any one time. That is, while it is possible to have multiple datasets in memory at once (see [D] [frames intro](#)), only one dataset may be active. Keeping this in mind will make Stata's care in opening new datasets clear. This chapter outlines all the possible ways to open and save datasets.

A Stata dataset can be opened in a variety of ways, most of which are probably familiar to you from other applications:

- Double-click on a Stata data file, which is a file whose extension is `.dta`. Note: The file extension may not be visible, depending on what options you have set in your operating system.
- Select **File > Open...** or click on the **Open** button and navigate to the file.
- Select **File > Open recent > filename**.
- Type `use filename` in the Command window. Stata will look for `filename` in the current working directory. If the file is located elsewhere, you will need to give its path. Be aware that if there is a space anywhere in the path or filename, you will need to put the filename inside quotation marks. See [U] [11.6 Filenaming conventions](#).
- Type `sysuse filename` in the Command window. Stata will look for `filename` in a series of directories called the `adopath`. Typically, this is for finding example datasets installed when you installed Stata, but it can also be used for easy access to your own datasets. For more information on the `adopath`, see [P] [sysdir](#).
- Type `webuse filename` in the Command window. The `webuse` command is used to access datasets used in the Stata manuals; for example, `webuse lbw` loads the `lbw` dataset used in the documentation of the `logistic` command. For more information, see [D] [webuse](#).

Opening a dataset in the current frame (see [D] [frames intro](#)) will replace the dataset, if any, that is currently in memory for that frame. Datasets in other frames are unaffected. If there have been changes to the data in the dataset in the current frame, Stata will refuse to discard the dataset unless you force it to do so. If you open the file with any method other than the Command window, you will be prompted. If you use the Command window and the current data have changed, you will get the following error message:

```
. sysuse auto
no; dataset in memory has changed since last saved
r(4);
```

These behaviors protect you from mistakenly losing data.

To save an unnamed dataset (or an old dataset under a new name):

1. select **File > Save as...**; or
2. type `save filename` in the Command window.

To save a dataset for use with Stata 13,

1. select **File > Save as...**, and select **Stata 13 Data (\*.dta)** from the **File format** pop-up menu; or
2. type `save old filename` in the Command window.

To save a dataset that has been changed (overwriting the original data file),

1. select **File > Save**;
2. click on the **Save** button; or
3. type `save, replace` in the Command window.

Once you overwrite a dataset, there is no way to recover your original dataset. With important datasets, you may want to either keep a backup copy of your original `filename.dta` or save your changes to a dataset under a new name. This is no different from working with a word-processing document, except that recovering from an inadvertent save of a dataset is nearly impossible.

Important note: Changes you have made to a dataset are not permanent until you save them. You work with a copy of the dataset in memory, not with the data file itself. This should not be surprising, because it is the way that you work with almost all applications on your computer.

If you do not want to save your dataset, you can clear the dataset in memory and open a new dataset by typing `use filename, clear`.

# 6 Using the Data Editor

## The Data Editor


The Data Editor gives a spreadsheet-like view of data that are currently in memory. You can use it to enter new data, edit existing data, search through the dataset, and edit attributes of the data in the dataset, such as variable names, labels, and display formats, as well as value labels.

In addition to the view of the data, there are two windows for manipulating variables and their properties: the Variables window and the Properties window. These are similar to the same-named windows in the main Stata window.

Any action you take in the Data Editor results in a command being issued to Stata as though you had typed it into the Command window. This means that you can keep good records and learn commands by using the Data Editor.

The Data Editor can be kept open while you work in Stata, giving you a live view of your dataset as you work. To protect your data from inadvertent changes, the Data Editor has two modes: edit mode for active editing and browse mode for viewing. In browse mode, editing within the Data Editor window is disabled. We highly recommend that you use the Data Editor in browse mode and switch to edit mode only when you want to make changes.

You can print your data from the Data Editor by selecting **Print** from the **File** menu.

We will be entering and editing data in this chapter, as well as manipulating the variables by using the Variables and Properties windows, so start the Data Editor in edit mode by clicking on the **Data Editor** button, .

## Buttons on the Data Editor

The toolbar for the Data Editor has some standard buttons and some buttons we have not yet seen:



**Data Editor (Edit):** Changes the Data Editor to edit mode.



**Data Editor (Browse):** Changes the Data Editor to browse mode for safely looking at data.



**Save:** Saves the dataset visible in the Data Editor.



**Find:** Toggles the Find bar for searching in the Data Editor.



**Sidebar:** Opens the sidebar in the Data Editor; see below for details.

The sidebar in the Data Editor has buttons for changing what the sidebar shows. These are technically tabs, but because they look and act like buttons, we will call them buttons throughout.



**Variables:** Brings the *Variables and Properties* windows to the front.



**Snapshots:** Brings the *Snapshots* window to the front. See *Working with snapshots* below.



**Filter:** Brings the *Filter observations* window to the front. This window is useful for looking at a subset of the current dataset.

You can move about in the Data Editor by using the typical methods:

- To move to the right, use the *Tab* key or the right arrow key.
- To move to the left, use *Shift-Tab* or the left arrow key.
- To move down, use *Return* or the down arrow key.
- To move up, use *Shift-Return* or the up arrow key.

You can also click within a cell to select it.

Right-clicking within the Data Editor brings up a contextual menu that allows you to manipulate the data and what you are viewing. Right-clicking on the Data Editor window displays a menu from which you can do many common tasks:

- **Copy** to copy data to the Clipboard.
- **Paste** to paste data from the Clipboard.
- **Paste special...** to paste data from the Clipboard with finer control of delimiters, giving a preview of what will be pasted.
- **Select all** to select all the data displayed in the Data Editor. This could be different from the data in the dataset if the data are filtered or some variables are hidden.
- **Data** which opens a submenu containing
  - **Insert variable...** to bring up a dialog for creating a new variable at the current cursor position.
  - **Add variable...** to bring up a dialog for creating a new variable at the beginning or end of a dataset.
  - **Replace contents of variable...** to bring up a dialog for replacing the values of the selected variable.
  - **Insert observations...** to bring up a dialog for inserting new empty observations at the current cursor position.
  - **Add observations...** to bring up a dialog for adding new empty observations to the end of the dataset.
  - **Sort data...** to sort the dataset by the selected variable.
  - **Value labels** to access a submenu for managing and displaying value labels.
  - **Keep only selected data** to keep only the selected data in the dataset. All remaining data will be dropped (removed) from the dataset. As always, this affects only the data in memory. It will not affect any data on disk.
  - **Drop selected data** to drop the selected data. This is only possible if the selection consists of either entire variables (columns) or observations (rows).
  - **Convert variables from string to numeric...** for converting string variables to numeric variables, which is useful when the string variables contain characters for formatting numbers instead of just numbers.
  - **Convert variables from numeric to string...** for converting numeric variables to strings.
  - **Encode string variable to labeled numeric...** for encoding a string-valued categorical variable to a numeric variable while still displaying the categories in tables and graphs.
  - **Decode labeled numeric variable to string...** for turning an encoded variable back into a string variable.
- **Reset selected column widths** to reset the selected columns to the default width.
- **Hide selected variables** to hide the selected variables.

- **Show only selected variables** to hide all but the selected variables.
- **Show entire dataset** to turn off all filters and unhide all variables.
- **Preferences...** to set the preferences for the Data Editor.
- **Print...** to print the data.

## Data entry


Entering data into the Data Editor is similar to entering data into a spreadsheet. One major difference is that the Data Editor has the concept of observations, which makes the data entry smart. We will illustrate this with an example. It will be useful for you to follow the example at your computer. To work along, you will need to start with an empty dataset, so save your dataset if necessary, and then type `clear` in the Command window.

Note: As a check to see if your data have changed, type `describe, short` (or `d,s` for short). Stata will tell you if your data have changed.

Suppose that we have the following data, and we want to enter them into Stata:


Make	Price	MPG	Weight	Gear Ratio
VW Rabbit	4697	25	1930	3.78
Olds 98	8814	21	4060	2.41
Chev. Monza	3667		2750	2.73
AMC Concord	4099	22	2930	3.58
Datsun 510	5079	24	2280	3.54
	5189	20	3280	2.93
Datsun 810	8129	21	2750	3.55

We do not know MPG for the third car or the make of the sixth.

Start by opening the Data Editor in edit mode. You can do this either by clicking on the **Data Editor** button, , or by typing `edit` in the Command window. You should be greeted by a Data Editor with no data displayed. (If you see data, type `clear` in the Command window.) Stata shows the active cell by highlighting it and displaying `varname[obsnum]` next to the input box in the Cursor Location box. We will see below that we can navigate within a dataset by using this cell reference. The Data Editor starts, by default, in the first row of the first column. Because there are no data, there are no variable names, and so Stata shows `var1[1]` as the active cell.

We can enter these data either by working across the rows (observation by observation) or by working down the columns (variable by variable). To enter the data observation by observation, press `Tab` after entering each value until you have reached the end of the first row. In our case, we would type `VW Rabbit`, press `Tab`, type `4697`, press `Tab`, and continue entering data to complete the first observation.

After you are finished with the first observation, select the second cell in the first column, either by clicking within it or by navigating to it. At this point, your screen should look like this:



We can now enter the data for the second observation in the same fashion as the first—with one nice difference: after we enter the last value in the row, pressing the *Tab* key will bring us to the first cell in the third row. This is possible because the number of variables is known after the first observation has been entered, so Stata knows when it has all the data for an observation.

We can enter the rest of the data by pressing the *Tab* key between entries, simply skipping over missing values by tabbing through them.

If we had wanted to enter the data variable by variable, we could have done that by pressing *Return* between each make of car until all seven observations were entered, skipping past the missing entry by pressing *Return* twice. Once the first variable was entered, we would select the first cell in the second column and enter the price data. We would continue this until we were finished.

## Notes on data entry

There are several things to note about data entry and the feedback you get from the Data Editor as you enter data:

- **Stata does not allow blank columns or rows in the middle of your dataset.**  
Whenever you enter new variables or observations, always begin in the first empty column or row. If you skip columns or rows, Stata will fill in the intervening columns or rows with missing values.
- **Strings and value labels are color coded.**  
To help distinguish between the different types of variables in the Data Editor, string values, value labels (see [GSM] 9 Labeling data), and all other values are displayed in different colors.

You can change the colors for strings and value labels by right-clicking on the Data Editor window and selecting **Preferences...**

- **A period (.) represents Stata's system missing numeric value.**

Stata has a system missing value, '.', and extended missing values '.a' through '.z'. By default, Stata uses its system missing value.

- **The Tab key is smart.**

As we saw above, after the first observation has been entered, Stata knows how many variables you have. So at the end of the second observation (and all subsequent observations), *Tab* will automatically take you back to the first column.

- **The Cursor Location box both shows location and is used for navigation.**

The Cursor Location box gives the location of the current cell. If you see, for example, `var3[4]`, this means that the current cell is the fourth observation of the variable named `var3`. You can navigate to a particular cell by typing the variable name and the observation in the Cursor Location box. If you wanted the second observation of `var1` to be the active cell, typing `var1 2` in the Cursor Location box and pressing *Return* would take you there.

- **Double quotes around text are unnecessary in string variables.**

Once Stata knows that a variable is a string variable (it holds text), there is no need to put quotes around the values, even if the values look like a number. Thus, if you wanted to enter ZIP codes as text, you would enter the first ZIP code with quotes ("02173"), but the rest would not need any quotes.

- **The arrow keys are context sensitive.**


If you select a cell and type new data, using an arrow key will accept the change and move to a new active cell. If you double-click on a cell, you can edit within the cell contents. In this case, the right- and left-arrow keys move within the cell's data.

- **You can throw away changes to a cell.**

If, while you are entering data in a cell, you decide you would like to cancel the changes, press the *Esc* key or click outside the cell.

## Renaming and formatting variables

The data have now been entered into Stata, but the variable names leave something to be desired: they have the default names `var1`, `var2`, ..., `var5`. We would like to rename the variables so that they match the column titles from our dataset. We would also like to give the variables descriptions and change their formatting.

We will step through changing the name, label, and format of the `price` variable. We will then add a note to the variable. Start by making sure that the Variables tab is active in the sidebar. If you do not see a list of variables in the sidebar, click on the Variables button, . Now click on the `var2` variable in the Variables window. The few properties associated with `var2` are now visible and editable in the Properties window. We may now systematically change the properties of `var2` to our choosing:

1. Double-click on `var2` in the *Name* field to select the old variable name, and type `price` to overwrite the name.
2. Double-click under the new `price` name in the *Label* field.
3. Enter a worthwhile label, such as `Price in Dollars`.
4. Click on `%9.0g` in the *Format* field.
5. Click on the ellipsis (...) button that appears. The *Create format* dialog opens.



6. You can see here that there are many possible formats, most of which are related to time. We want commas in our numbers, so check the *Use commas in numeric output* checkbox. When you are done, click on the **OK** button.
7. Click in the *Notes* field.
8. Click on the ellipsis (...) button that appears. A dialog called *Notes for price* opens.
9. Click on the **Add** button and type a clever note.
10. When you are done typing, click on the **Submit** button, and then click on the **Close** button. This note is now attached to the *price* variable.
11. Click on the disclosure control to see the note you just typed in the *Properties* window.

To edit the properties of another variable, either click on the variable in the *Variables* window or use the navigation arrows in the *Properties* window until the variable's name appears. We can name the first variable *make*; the third, *mpg*; the fourth, *weight*; and the fifth, *gear\_ratio*. Just before you rename *var5* to *gear\_ratio*, your screen should look like this:

The screenshot shows the Stata Data Editor (Edit) window. The main window displays a dataset with 7 observations and 5 variables. The 'make' variable is highlighted in red. The 'Variables' window on the right shows 'make', 'price', and 'mpg' selected. The 'Properties' window shows the properties for the 'make' variable, including Name, Label, Type (str11), Format (%11s), Value label, Notes, Data, Frame (default), and Filename.

	make	price	mpg	weight	var5
1	VW Rabbit	4697	25	1930	3.7
2	Olds 98	8814	21	4060	2.4
3	Chev. Monza	3667	.	2750	2.7
4	AMC Concord	4099	22	2930	3.5
5	Datsun 510	5079	24	2280	3.5
6		5189	20	3280	2.9
7	Datsun 810	8129	21	2750	3.5

You need to know some rules for variable names:

- Stata is case sensitive. *Make*, *make*, and *MAKE* are all different names to Stata. If you had named your variables *Make*, *Price*, *MPG*, etc., then you would have to type them correctly capitalized in the future. Using all lowercase letters is easier.
- A variable name must be 1–32 characters long.
- The characters can be letters (A–Z, a–z), digits (0–9), underscores (\_), or Unicode characters that are not symbols.
- Spaces or other characters are not allowed.
- The first character of a variable name must be a letter, an underscore, or a Unicode character. Although you can use an underscore to begin a variable name, it is highly discouraged. Such names are used for temporary variable names in Stata. You would like your data to be permanent, so using a temporary name could lead to great frustration.

For more information about variable names and value labels, see [GSM] 9 Labeling data; for display formats, see [U] 12.5 Formats: Controlling how data are displayed.

## Copying and pasting data

You can copy and paste data by using the Data Editor. This is often a simple way to bring data into Stata from any other applications such as spreadsheets or databases.

1. Select the data that you wish to copy by using one of these means:
  - Click once on a variable name or column heading to select an entire column.
  - Click once on an observation number or row heading to select the entire row.
  - Click and drag the mouse to select a range of cells.
2. Copy the data to the Clipboard by right-clicking within the selected range, and select **Copy**.
3. Paste the data from the Clipboard by right-clicking on the top left cell of the area to which you wish to paste, and select **Paste**.

We will illustrate copying and pasting an observation by making a copy of the first observation and pasting it at the end of the dataset.

Start by clicking on the observation number of the first observation. Doing so highlights all the data in the row. Right-click on the same location (there is no need to move the mouse), and select **Copy**:

The screenshot shows the Stata Data Editor (Edit) window. The dataset is named 'make[1]' and 'VW Rabbit'. The data is displayed in a table with 7 observations and 5 variables: make, price, mpg, weight, and var5. The first observation is selected, and a context menu is open over it. The menu options are: Copy, Paste, Paste special..., Select all, Data, Reset selected column widths, Hide selected variables, Show only selected variables, Show entire dataset, Preferences..., and Print... The Variables panel on the right shows the selected variables: make, price, and mpg. The Properties panel shows the properties for the selected variable 'make': Name: make, Label: (empty), Type: str11, Format: %11s, Value label: (empty), Notes: (empty), Frame: default, and Filename: (empty).

	make	price	mpg	weight	var5
1	VW Rabbit	4697	25	1930	3.7
2	Olds	Copy		50	2.4
3	Chev. Mor	Paste		50	2.7
4	AMC Conco	Paste special...		30	3.5
5	Datsun !	Select all		30	3.5
6		Data		30	2.9
7	Datsun !			50	3.5

Vars: 5 Order: Dataset Obs: 7 Length: 11 Filter: Off

Click on the first cell in the eighth row, right-click while you are still in that cell, and choose **Paste** from the resulting menu. You can see that the observation was successfully duplicated.

## Notes on copying and pasting

- The above example illustrated copying and pasting within the Data Editor. You can use roughly the same technique to copy and paste between other applications and Stata and between Stata and other applications. The easiest way to see if copying and pasting works properly with another application is to try it. The one requirement for things to work well is that the external application must copy tables in some delimited form, as do spreadsheet applications, many database applications, and some word processors. Using **Edit > Paste special...** gives some added flexibility to the formats you can paste into the Data Editor. If a simple paste does not give you what you expected, you should try **Edit > Paste special...** For more information on file-based methods for importing data into Stata, see [GSM] 8 Importing data.
- If you are copying and pasting data with value labels, you have a choice. You can copy variables with value labels as text, using the value labels as the actual values, or you can copy said variables as their underlying encoded numbers. Copying with the value labels is the default. If you would like the other choice, right-click in the Data Editor and select **Data > Value labels > Hide all value labels**.

## Changing data

As its name suggests, the Data Editor can be used to edit your dataset. As we have seen already, it can be used to edit the data themselves as well as the description and display options for the variables.

Here is an example for making some changes to the `auto` dataset, which illustrates both methods for using the Data Editor and its documentation trail. We will also keep snapshots of the dataset as we are working so that we can revert to previous versions of the dataset in case we make a mistake.

We would like to investigate the dataset, work with value labels, delete the `trunk` variable, and make a new variable showing gas consumption per 100 miles. These tasks will illustrate the basics of working in the Data Editor.


Start by typing `sysuse auto` into the Command window. If you worked the previous example, you will get an error and are told that the dataset in memory has changed since it was last saved. This is good—Stata is keeping you from inadvertently throwing away the unsaved changes to your current dataset as it loads the `auto` dataset. If you would like to save the dataset you have been working on, select **File > Save** and save the dataset in an appropriate location. Otherwise, type `clear` in the Command window, and press *Return* to clear out the data, and then load that `auto` data.


Once the `auto` dataset is loaded, start the Data Editor.

1. We remember that our grandfather had a `Toronado`, which looked sleek, but which seemed to require a lot of fill-ups. We would like to see if this car is in the dataset. To find it, we select **Edit > Find > Find...**, type `Toronado`, and press *Return*. We see that this make of car got 16 miles per gallon.
2. We would like to see which cars have the lowest and highest gas mileages. To do this, right-click on the column heading of the `mpg` column. Select **Data > Sort** from the contextual menu. A dialog will pop up asking how you want to sort, defaulting to sorting in ascending order. Click on **OK**. (Stata worries about sort order because sort order can affect reproducibility when using resampling techniques. This is a good thing.) You will see that the data have now been sorted by `mpg` in ascending order. The lowest-mileage cars are at the top of the screen; by scrolling to the bottom of the dataset, you can find the highest-mileage cars.
3. We would like to investigate repair records and hence sort by the `rep78` variable. (Do this now.) We see that the `Starfire` and `Firebird` both had poor repair records, but we would like to see the cars with good repair records. We could scroll to the bottom of the dataset, but it will be faster to use the Cursor Location box: type `rep78 74` and press *Return* to make `rep78[74]`

the active cell. We notice that the last five entries for `rep78` appear as dots. The dots mean that these values are missing. A few items of note:

- As we can see from the result of the sort, Stata views missing values as being larger than all numeric nonmissing values. In technical terms, this means that `rep78 >= .` is equivalent to `missing(rep78)`.
- What we do not see here is that Stata has multiple missing-value indicators: `.` is Stata's default or system missing-value indicator, and `.a`, `.b`, ..., `.z` are Stata's extended missing values. Extended missing values are useful for indicating the reason why a value is unknown.
- The different missing values sort among themselves: `.` < `.a` < `.b` < ... < `.z`. See [U] 12.2.1 **Missing values** for full details.

- We would like to make the repair records readable. Click on `rep78` in the Variables window.
- Click on the *Value label* field in the Properties window, and then click on the ellipsis (...) button that appears. This opens the *Manage value labels* dialog. We need to define a new value label for the repair records.
  - Click on the **Create label** button. You will see the *Create label* sheet.
  - Type a name for the label, say, `repairs`, in the *Label name* box.
  - Press the *Tab* key or click within the *Value* field.
  - Type 1 for the value, press the *Tab* key, and type `atrocious` for the label.
  - Press the **Add** button to create the pairing.
  - Repeat steps d and e to make all the pairings: 2 with "bad", 3 with "OK", 4 with "good", and 5 with "stupendous".
  - Click on the **OK** button to finish creating the value label.
  - Click on the disclosure control, , to show the label—you should see this:



If you have something else, you can edit the label by clicking on the **Edit label** button.

- Click on the **Close** button to close the *Manage value labels* dialog.

Now that the label has been created, attach it to the `rep78` variable by clicking on the double arrows in the *Value label* field and selecting the `repairs` label. You can now see the labels displayed in place of the values.

- Suppose that we found the original source of the data in a time capsule, so we could replace some of the missing values for `rep78`. We could type the values into cells. We can also assign the values by right-clicking within a cell with a missing value and choosing a value from **Data**

- > **Value labels** > **Assign value from value label** “repairs”. This strategy can be useful when a value label has many possible values.
7. We would now like to delete the `trunk` variable. We can do this by right-clicking on the `trunk` variable name at the top of the column and selecting the **Data > Drop selected data** menu item. Because this can lead to data loss, the Data Editor asks whether we would like to drop the selected variable. Click on the **Drop** button.
  8. To finish up, we would like to create a variable containing the gallons of gasoline per 100 miles driven for each of the cars.
    - a. Right-click within any cell, and choose the **Data > Add variable...** menu item to bring up the *generate* dialog.
    - b. Type `gp100m` in the *Variable name* field.
    - c. Being sure that the *Specify a value or an expression* radio button is selected, type `100/mpg` in its field. We could have clicked on the **Create...** button to open the *Expression Builder* dialog, but this formula was simple enough to type. (You might want to explore the Expression Builder right now to see what it can do.)
    - d. Be sure that the *Add at the end of dataset* item is chosen from the *Position of new variable* list.
    - e. Click on **OK**. You can scroll to the right to see the newly created variable.

Throughout this data-editing session, we have been using the Data Editor to manipulate the data. If you look in the Results window, you will see the commands and their output. You can also see all the commands generated by the Data Editor in the History window. If you wanted to save the editing commands to use again later, you could do the following steps:

1. Click in the History window on the last command that came from the Data Editor.
2. Scroll up until you find the `sort mpg` command you ran immediately after opening the Data Editor, and *Shift*-click on it.
3. Right-click on one of the highlighted commands.
4. Select **Send selected to Do-file Editor**.

This procedure will save all the commands you highlighted into the Do-file Editor. You could then save them as a do-file, which you could run again later. We will talk more about the Do-file Editor in [GSM] 13 Using the Do-file Editor—automating Stata. You can find help about do-files in [U] 16 Do-files.

If you want to save this dataset, save it under a new name by using **File > Save as...** to prevent overwriting the original dataset.

## Working with snapshots

The Data Editor allows you to save to disk snapshots of whatever dataset you are working on. These are temporary copies of the dataset—they will be deleted when you quit Stata, so they need to be treated as temporary. Still, there are many uses for snapshots, such as

- saving a temporary copy of the data in memory so that another dataset can be opened and viewed;
- saving stages of work, which can be recovered in case you do something disastrous; and
- saving pieces of datasets while doing analyses.


We will keep using the `auto` dataset from above; if you are starting here, you can start fresh by typing `sysuse auto` in the Command window to open the dataset. (If you get a warning about data in memory being lost, either use `clear` or save your data. See [GSM] 5 Opening and saving Stata datasets for more information.) If we open the Data Editor and click on the **Snapshots** button in the





sidebar, we see the following window. If you are starting afresh, you will see numbers rather than labels for `rep78`.

The screenshot shows the Stata Data Editor window titled "Data Editor (Edit) — auto.dta". The main window displays a dataset with 15 observations. The columns are "make", "price", "mpg", and "rep78". The "rep78" column is highlighted in yellow. The values in the "rep78" column are: 1 atrocious, 2 atrocious, 3 bad, 4 bad, 5 bad, 6 bad, 7 bad, 8 bad, 9 bad, 10 bad, 11 OK, 12 OK, 13 OK, 14 OK, 15 OK. The "Snapshots" window is open on the right, showing a table with columns for "#", "Label", "Timestamp", and "Source". The "Add" button in the toolbar is active.

#	make	price	mpg	rep78
1	Pont. Firebird	4,934	18	atrocious
2	Olds Starfire	4,195	24	atrocious
3	Pont. Sunbird	4,172	24	bad
4	Dodge Magnum	5,886	16	bad
5	Cad. Eldorado	14,500	14	bad
6	Chev. Monte Carlo	5,104	22	bad
7	Dodge Diplomat	4,010	18	bad
8	Chev. Monza	3,667	24	bad
9	Dodge St. Regis	6,342	17	bad
10	Plym. Volare	4,060	18	bad
11	Pont. Grand Prix	5,222	19	OK
12	Chev. Chevette	3,299	29	OK
13	Renault Le Car	3,895	26	OK
14	Plym. Arrow	4,647	28	OK
15	Linc. Continental	11,497	12	OK

Vars: 12 Order: Dataset      Obs: 74      Filter: Off

To begin with, only one button is active in the Snapshots toolbar. Click on the active button—the **Add** button, . It brings up a dialog asking for a label, or name, for the snapshot. Give it an inventive name, such as *Start*, and press *Return*. You can see that a snapshot is now listed in the Snapshots window, and all the buttons in the toolbar are now active. The following buttons appear in the Snapshots window:

-  **Add:** Save a new snapshot with a timestamp and label.
-  **Remove:** Erase a snapshot. This action deletes the temporary snapshot file but does not affect the data in memory.
-  **Change label:** Edit the label of the selected (highlighted) snapshot.
-  **Restore:** Replace the data in memory with the data from the selected snapshot. You will get a dialog asking you to confirm your action.

You should now try manipulating the dataset by using the tools we have seen. Once you have done that, create another snapshot, calling it *Changed*. Open the Snapshots window and restore the *Start* snapshot by either double-clicking it or clicking first on it and then on the **Restore** button to see where you started. You can then go back to where you were working by restoring your *Changed* snapshot.

Snapshots continue to be available either until they are deleted or until you quit Stata. You can thus use snapshots of one dataset while working on another. You will find your own uses for snapshots—just take care to save the datasets you want for future use because the snapshots are temporary.

## Dates and the Data Editor

The Data Editor has two special tools for working with dates in Stata. To see these in action, we will need to open another dataset. Either save your dataset or `clear` it out, and then type `sysuse sp500` in the Command window. Look in the Data Editor to see what you have.

The screenshot shows the Stata Data Editor window titled "Data Editor (Edit) — sp500.dta". The window contains a data table with columns: date, open, high, low, and close. The first row shows the date 02jan2001. To the right of the data table are two panels: "Variables" and "Properties". The "Variables" panel lists the variables date, open, and high, each with a checked box and a label. The "Properties" panel shows the format for the selected variable as "default". At the bottom of the window, it says "Vars: 7 Order: Dataset Obs: 248 Filter: Off".

	date[1]	02jan2001				DMY
	date	open	high	low	close	
1	02jan2001	1320.28	1320.28	1276.05	1283.2	
2	03jan2001	1283.27	1347.76	1274.62	1347.5	
3	04jan2001	1347.56	1350.24	1329.14	1333.3	
4	05jan2001	1333.34	1334.77	1294.95	1298.3	
5	08jan2001	1298.35	1298.35	1276.29	1295.8	
6	09jan2001	1295.86	1311.72	1295.14	1300.	
7	10jan2001	1300.8	1313.76	1287.28	1313.2	
8	11jan2001	1313.27	1332.19	1309.72	1326.8	
9	12jan2001	1326.82	1333.21	1311.59	1318.5	
10	16jan2001	1318.32	1327.81	1313.33	1326.6	
11	17jan2001	1326.65	1346.92	1325.41	1329.4	
12	18jan2001	1329.89	1352.71	1327.41	1347.9	
13	19jan2001	1347.97	1354.55	1336.74	1342.5	
14	22jan2001	1342.54	1353.62	1333.84	1342.	
15	23jan2001	1342.9	1362.9	1339.63	1360.	

You can see a `date` variable that has January 2, 2001, as its first day, though it is being displayed in Stata's default format for dates.

We will start with formatting:

1. Select the `date` variable in the Variables window to the right of the data table.
2. In the Properties window, select the Format row and click on the ellipsis button that appears.
3. The *Create format* dialog tells us three pieces of information about the date format:
  - These are daily dates. As you can see, Stata understands other types of dates that are often used in financial data.
  - Looking at the bottom of the dialog, you can see that Stata's default date format is `%td`. This means that the variable contains time values that are to be interpreted as daily dates.
  - This default format is displayed as, for example, `07apr2009`.
4. There are many premade date formats in the *Samples* pane at the top right of the *Create format* dialog. Click on `April 7, 2009`. You can see how the format would be specified at the bottom of the dialog.
5. Click on **OK** to close the *Create format* dialog. You can see that the dates are now displayed differently.

This is a very simple way to change date formats. For complete information on dates and date formats, see [D] [Datetime](#).

We will now change some of the dates to illustrate how this can be done simply, regardless of the format in which the dates are displayed. If you look in the upper-right corner of the Data Editor, you will see the *Time/Date input mask* field, which shows `DMY`. This field affects how dates are entered when editing data.

By default, the input mask is set to *DMY*. This means dates can be entered in many different fashions, as long as the order of the date components is day, month, year. Try the following:

1. Click in the first observation of `date` so that the Cursor Location shows `date[1]`.
2. Type `18jan2013` and press the *Return* key. Stata understands the *DMY* input mask and knows enough to enter the new date in the selected cell.
3. Enter `30042014` and press *Return*. Stata still understands the input mask, even though there are no separators.
4. Click within the *Time/Date input mask* field, and choose *MDY* from the drop-down menu.
5. Click on any observation in the `date` column.
6. Type `March 15, 2019` and press *Return*. Stata will still understand.

Working in this fashion is the fastest way to edit dates by hand. If you look in the Results window, you will see why.

We are now finished with this dataset, so type `clear` and press *Return*.

## Data Editor advice

As you could see above, a small mistake in the Data Editor could cause large problems in your dataset. You really must take care in how you edit your data.

- People who care about data integrity know that editors are dangerous—it is easy to accidentally make changes. **Never use the Data Editor in edit mode when you just want to look at your data.** Use the Data Editor in browse mode (or use the `browse` command).
- If you must edit your data, protect yourself by limiting the dataset's exposure. For example, if you need to change `rep78` only if it is missing, find a way to look at just the missing values for `rep78` and any other variables needed to make the change. This will make it impossible for you to change (damage) variables or observations other than those you view. We will explore this aspect shortly.
- Even with these caveats, Stata's Data Editor is safer than most because it records commands in the Results window. Use this feature to log your output and make a permanent record of the changes. Then you can verify that the changes you made are the changes you wanted to make. See [\[GSM\] 16 Saving and printing results by using logs](#) for information on creating log files.

## Filtering and hiding

We would now like to investigate restricting our view of the data we see in the editor. This feature is useful for the reasons mentioned above, and as we will see, it helps if we would like to browse through the data of a large dataset. In any case, we would like to focus on some data, not all the data, whether we focus on some of the variables, some of the observations, or even just some observations within some variables. We would also like to change the order of the variables. We will show you how this is done by using both the graphical interface and commands.

Open the `auto` dataset by typing `sysuse auto`. If you get an error message, type `clear` and try again. Once you have done that, open the Data Editor.


Suppose that we would like to edit only those observations for which `rep78` is missing. We will need to look at the make of the car so that we know which observations we are working with, but we do not need to see any other variables. We will work as though we had a very large dataset to work with.



1. Before we get started, try experimenting with the Variables window.
  - a. Drag variables up and down the list. Doing so changes the order of the variables' columns in the Data Editor. It does not change their order in the dataset itself.
  - b. Uncheck some of the checkboxes in the first column to hide some of the variables.
  - c. Type a search criterion in the search field. Just like in the Variables window in the main Stata window, the default is to ignore case and find any variables or variable labels containing any of the words in the filter. Clicking on the arrow by the magnifying glass will allow you to change this behavior. The filtering of variables in the list affects what is displayed in the Variables window; it does not affect what variables' data are displayed. When you are done, delete your filter text.
2. Right-click on any variable in the Variables window, and select **Select all** from the contextual menu.
3. Click on any checkbox to deselect all the variables.
4. Click on the `make` variable to select it, and deselect all the other variables.
5. Click on the checkbox for `make`.
6. Click on the checkbox for `rep78`.

If you look in the Command window, you can see that no commands have been issued, because hiding the variables does not affect the dataset—it affects only what shows in the Data Editor.

We now have protected ourselves by using only those variables that we need. We should now reduce our view to only those observations for which `rep78` is missing. This is simple.

1. Click on the **Filter observations** tab, , in the sidebar.
2. Enter `missing(rep78)` in the *Filter by expression* field.
3. Click on the **Apply filter** button.
4. If you are curious, click on the ellipsis button. It opens up an *Expression Builder* dialog. This lists the wide variety of functions available in Stata. See the [Stata Functions Reference Manual](#).

Now we are focused on the part of the dataset in which we would like to work, and we cannot destroy or mistakenly alter other data by stray keystrokes in the Data Editor window.

It is worth learning how to hide variables and filter observations in the Data Editor from the Command window. This can be quite convenient if you are going to restrict your view, as we did above. To work from the Command window, we must use the `edit` command together with a *varlist* (variable list) along with `if` and `in` qualifiers in the Command window. By using a *varlist*, we restrict the variables we look at, whereas the `if` and `in` qualifiers restrict the observations we see. ([GSM] 10 Listing data and basic command syntax contains many examples of using a command with a variable list and `if` and `in`.) Suppose we want to correct the missing values for `rep78`. The minimum amount of data we need to expose are `make` and `rep78`. To see this minimal amount of information and hence to minimize our exposure to making mistakes, we enter the commands

```
. sysuse auto
(1978 Automobile Data)
. edit make rep78 if missing(rep78)
```

and we would see the following window:

The screenshot shows the Stata Data Editor interface. At the top, there are window controls and a title bar that reads "Data Editor (Edit) — auto.dta". Below the title bar are icons for "Edit mode", "Save", and "Find". The main data grid has two columns: "make" and "rep78". The first row is selected, showing the value "3" in the first column, "AMC Spirit" in the "make" column, and a "." in the "rep78" column. The "make" column contains the following values: "AMC Spirit", "Buick Opel", "Plym. Sapporo", "Pont. Phoenix", and "Peugeot 604". The right sidebar contains a "Variables" list with "make" and "rep78" checked, and "price" unchecked. Below the list is a search bar and a "Properties" panel for the selected variable "make". The "Properties" panel shows the following details:

Variables	
Name	Label
<input checked="" type="checkbox"/> make	Make and Model
<input checked="" type="checkbox"/> rep78	Repair Record 1978
<input type="checkbox"/> price	Price


Properties	
▼ Variables	
Name	make
Label	Make and Model
Type	str18
Format	%-18s
Value label	
Notes	
▼ Data	
Frame	default
► Filename	auto.dta

At the bottom of the window, the status bar shows "Vars: 2 of 12 Order: Dataset", "Obs: 5 of 74", "Length: 18", and "Filter: On".

Once again, we are safe and sound.

Keep this lesson in mind if you edit your data. It is a lesson well learned.

## Browse mode


The purpose of using the Data Editor in browse mode is to look at data without altering them by stray keystrokes. You can start the Data Editor in browse mode by clicking on the **Data Editor (Browse)** button, , or by typing `browse` in the Command window. When you work in browse mode, all contextual menu items that would let you alter the data, the labels, or any of the display formats for the variables are disabled. You may view a variable's properties with the **Properties** menu item, but you may not make any changes. You still can filter observations and hide variables to get a restricted view because these actions do not change the dataset.

Note: Because you can still use Stata menus not related to the Data Editor and because you can still type commands in the Commands window, it is possible to change the data even if the Data Editor is in browse mode. In fact, this means you can watch how your commands affect the dataset. You are merely restricted from using the Data Editor itself to change the data.

# 7 Using the Variables Manager

## The Variables Manager

This chapter discusses Stata's Variables Manager. To get started, open the auto dataset by typing `sysuse auto`, `clear` in the Command window. You open the Variables Manager by selecting **Data > Variables Manager**.



The Variables Manager is a tool for managing properties of variables both individually and in groups. It can be used to create variable and value labels, rename variables, change display formats, and manage notes. It has the ability to filter and group variables as well as to create variable lists. Users will find these features useful for managing large datasets.

Any action you take in the Variables Manager results in a command being issued to Stata as though you had typed it in the Command window. This means that you can keep good records and learn commands by using the Variables Manager.

## The Variable pane

The left pane of the Variables Manager is called the Variable pane, though it has no explicit title on the screen. It shows the list of variables in the dataset. This list can be manipulated in a variety of ways.

- The variables can be filtered by entering text into the filter box in the upper-left corner. This can be a good way to zoom in on similarly named or labeled variables.
- The list can be sorted by clicking on the column title.
  - a. If you click on a column title, it will sort in ascending order.
  - b. A second click on the same column title will change to sorting in descending order.
  - c. A third click on the same column will restore the original dataset order.

The sort order affects only how the data appear in the Variable Managers window—the dataset itself stays the same.

- The order of the columns can be changed by dragging the column titles. To restore the original column headings, right-click on the column titles and select **Restore column defaults**.

## Right-clicking on the Variable pane

Right-clicking on the Variable pane displays a menu from which you can do many common tasks:

- **Keep only selected variables** to keep only the selected variables in the dataset and to drop all the others.
- **Drop selected variables** to drop all the selected variables from the dataset.
- **Manage notes for selected variable...** to open a window that allows adding and deleting notes for a single variable. This is disabled if multiple variables are selected.
- **Manage notes for dataset...** to open a window that allows adding and deleting notes for the dataset as a whole.
- **Copy varlist** to copy the names of the selected variables to the Clipboard.
- **Select all** to select all visible variables. If a variable has become hidden because of the filter, it will not be selected.
- **Send varlist to Command window** to insert the names of the selected variables in the Command window. Combined with grouping and sorting, this can be a useful way to create variable lists in large datasets.
- **Print...** to print the Variable pane. You can change the widths of the printed columns by changing the widths of the columns in the Variables Manager.


## The Variable Properties pane

The Variable Properties pane can be used to manipulate the properties of variables selected in the Variable pane. With one variable selected, you can manipulate all properties of the variable. With many variables selected, you can change their formats or types as well as assign value labels all at once. These fields work in the same fashion as those shown in [Renaming and formatting variables](#) in [GSM] 6 Using the Data Editor. We can also manage the notes Stata allows you to attach to variables and the dataset—we will show an example below.

## Managing notes


Stata allows you to attach notes to both variables and the dataset as a whole. These are simple text notes that you can use to document whatever you like—the source of the dataset, data collection quirks associated with a variable, what you need to investigate about a variable, or anything else.

Start by selecting a variable in the Variable pane. We will work with the `price` variable. Click on the **Manage...** button next to the *Notes* field, and you will see the following dialog appear:



We will add a few notes:

1. Click on the **Add** button to add a note.
2. Type `TS - started working`. `TS` with a trailing space inserts a timestamp in the note.
3. Add two more notes. We added two notes about prices:



It is worth experimenting with adding, deleting, and editing notes. Notes can be an invaluable memory aid when working on projects that last a long time. Anytime you manipulate notes in the Notes Manager, you create Stata commands.

# 8 Importing data

## Copying and pasting

One of the easiest ways to get data into Stata is often overlooked: you can copy data from most applications that understand the concept of a table and then paste the data into the Data Editor. This approach works for all spreadsheet applications, many database applications, some word-processing applications, and even some webpages. Just copy the full range of data, paste it into the Data Editor, and everything will probably work well. You can even copy a text file that has the pieces of data separated by commas and then paste it into the Data Editor.


Suppose that your friend has a small dataset about some very old cars.

```
VW Rabbit,4697,25,1930,3.78
Olds 98,8814,21,4060,2.41
Chev. Monza,3667,,2750,2.73
,4099,22,2930,3.58
Datsun 510,5079,24,2280,3.54
Buick Regal,5189,20,3280,2.93
Datsun 810,8129,,2750,3.55
```

You would like to put these data into Stata. Doing so is easier than you think:

1. Clear out your current dataset by typing `clear`.
2. Copy the above data.
3. Open the Data Editor in edit mode.
4. Select **Edit > Paste special...**
5. Stata sees that the column delimiters are commas and shows how the data would look.
6. Click on the **OK** button.

You can see that Stata has imported the data nicely.

Later in this chapter, we would like to bring these data into Stata without copying and pasting, so we would like to save them as a text file. Go back to the main Stata window, and click on the **Do-file Editor** button, , to open a new Do-file Editor window. Paste the data in the Do-file Editor, then click on the **Save** button. Navigate to your working directory, and save the file as a `few cars.csv`. If you do not know what your working directory is, look in the status bar at the bottom of the main Stata window.

Be careful if you are copying data from a spreadsheet because spreadsheets can contain special formatting that ruins its rectangular form. Be sure that your spreadsheet does not contain blank rows, blank columns, repeated headers, or merged cells because these can cause trouble. As long as your spreadsheet looks like a table, you will be fine.

## Commands for importing data

Copying and pasting is a great way to bring data into Stata, but if you need a clear audit trail for your data, you will need another way to bring data into Stata. The rest of this chapter will explain how to do this. You will also learn methods that lend themselves better to repetitive tasks and methods for importing data from a wide variety of sources.

Stata has various commands for importing data. The three main commands for reading non–Stata datasets in text are

- `import delimited`, which is made for reading text files created by spreadsheet or database programs or, more generally, for reading text files with clearly defined column delimiters such as commas, tabs, semicolons, or spaces;
- `infile`, which is made for reading simple data that are separated by spaces or rigidly formatted data aligned in columns; and
- `infix`, which is made for data aligned in columns but possibly split across rows.

Stata has other commands that can read other types of files and can even get data from external databases without the need for an interim file:

- The `import excel` command can read Microsoft Excel files directly, either as an `.xls` or as an `.xlsx` file.
- The `import sas` command can read native SAS files, so data can be transferred from SAS to Stata in this fashion.
- The `import spss` command can read IBM SPSS Statistics files.
- The `import sasxport5` command can read version SAS V5 Transport files. The `import sasxport8` command can read version SAS V8 Transport files.
- The `odbc` command can be used to pull data directly from any data sources for which you have ODBC (Open Database Connectivity) drivers.

Stata can import more formats; see [D] [import](#) for the full list.

Each command expects the file that it is reading to be in a specific format. This chapter will explain some of those formats and give some examples. For the full description, consult the *Data Management Reference Manual*.

## The import delimited command

The `import delimited` command was developed to read in text files that were created by spreadsheet or database programs because these are common formats for sharing datasets on the Internet. All spreadsheet programs and most database applications have an option to save the dataset as a text file with the columns delimited with either tab characters or commas. Some of these programs also save the column titles (variable names, in Stata) in the text file.

To read in such a file, you have only to type `import delimited filename`, where *filename* is the name of the text file. The `import delimited` command will figure out what the delimiter character is (tab or comma) and what type of data is in each column. As always, if *filename* contains spaces, put double quotes around the filename, and include the path if *filename* is not in the current working directory.

By default, the `import delimited` command understands files that use the tab or comma as the column delimiter automatically. If you have a file that uses another character as the delimiter, use `import delimited's delimiters()` option.

Earlier in this chapter, you saved a file called a few cars.csv in *Copying and pasting*. These data correspond to the make, price, MPG, weight, and gear ratio of a few very old cars. The variable names are not in the file (so `import delimited` will assign its own names), and the fields are separated by commas. Clear out any existing data, then use `import delimited` to read the data in this file. Because there are spaces in the filename, it must be enclosed in double quotes.

```
. clear
. import delimited "a few cars.csv"
(5 vars, 7 obs)
```

You can look at the data in the Data Editor, and it will look just like the earlier result from copying and pasting. We will now list the data so that we can see them in the manual. The `separator(0)` option suppresses the horizontal separator line that is drawn after every fifth observation by default.

```
. list, separator(0)
```

	v1	v2	v3	v4	v5
1.	VW Rabbit	4697	25	1930	3.78
2.	Olds 98	8814	21	4060	2.41
3.	Chev. Monza	3667	.	2750	2.73
4.		4099	22	2930	3.58
5.	Datsun 510	5079	24	2280	3.54
6.	Buick Regal	5189	20	3280	2.93
7.	Datsun 810	8129	.	2750	3.55

If you want to specify better variable names, you can include the desired names in the command. When you specify variable names, you must also use the `using` keyword before the filename.

```
. import delimited make price mpg weight gear_ratio using "a few cars.csv"
(5 vars, 7 obs)
. list, separator(0)
```

	make	price	mpg	weight	gear_r~o
1.	VW Rabbit	4697	25	1930	3.78
2.	Olds 98	8814	21	4060	2.41
3.	Chev. Monza	3667	.	2750	2.73
4.		4099	22	2930	3.58
5.	Datsun 510	5079	24	2280	3.54
6.	Buick Regal	5189	20	3280	2.93
7.	Datsun 810	8129	.	2750	3.55

As a side note about displaying data, Stata listed `gear_ratio` as `gear_r~o` in the output from `list`. `gear_r~o` is a unique abbreviation for the variable `gear_ratio`. Stata displays the abbreviated variable name when variable names are longer than eight characters.



To prevent Stata from abbreviating `gear_ratio`, you could specify the `abbreviate(10)` option:

```
. list, separator(0) abbreviate(10)
```

	make	price	mpg	weight	gear_ratio
1.	VW Rabbit	4697	25	1930	3.78
2.	Olds 98	8814	21	4060	2.41
3.	Chev. Monza	3667	.	2750	2.73
4.		4099	22	2930	3.58
5.	Datsun 510	5079	24	2280	3.54
6.	Buick Regal	5189	20	3280	2.93
7.	Datsun 810	8129	.	2750	3.55

For more information on the `~` abbreviation and on `list`, see [\[GSM\] 10 Listing data and basic command syntax](#).

We will use this dataset again in the next chapter, so we would like to save it. Type `save afeewcars`, and press *Return* in the Command window to save the dataset.

For this simple example, you could have copied the contents of the file and pasted it into the Data Editor by using **Paste special...** and choosing comma as the delimiter.

For text files that have no nice delimiters or for which observations could be spread out across many lines, Stata has two more commands: `infile` and `infix`. See [\[D\] import](#) for more information about how to read in such files.

## Importing files from other software

Stata has some more specialized methods for reading data that were created by other applications and stored in their proprietary formats.

The `import excel` command is made for reading files created by Microsoft Excel. See [\[D\] import excel](#) for full details.

The `import spss` command is made for reading files created by IBM SPSS Statistics. See [\[D\] import spss](#) for full details.

The `import sas` command is made for reading files created by SAS. See [\[D\] import sas](#) for full details.

The `import sasxport5` and `import sasxport8` commands can read SAS V5 and SAS V8 Transport files. See [\[D\] import sasxport5](#) and [\[D\] import sasxport8](#) for full details.

If you have software that supports ODBC, you can read data by using the `odbc` command without the need to create interim files. See [\[D\] odbc](#) for full details. The FAQ for setting up ODBC is also helpful; read it at <https://www.stata.com/support/faqs/data-management/configuring-odbc>.

Here is a brief summary of the choices:

- If you have a Microsoft Excel `.xls` or `.xlsx` file, use `import excel`.
- If you have an IBM SPSS Statistics `.sav` file, use `import spss`.
- If you have a SAS `.sas7bdat` file created on a Windows machine, use `import sas`.
- If you have a file exported from a spreadsheet or database application to a tab-delimited or CSV file, use `import delimited`.

- If you have a fixed-format file, either use `infile` with a dictionary or use `infix`.
- If you have a database accessible with ODBC, use `odbc`.
- If you have a SAS V5 Transport file, use `import sasxport5`.
- If you have a SAS V8 Transport file, use `import sasxport8`.
- If you have economic data from the Federal Reserve Data, use `import fred`.
- If you subscribe to any Haver Analytics databases, use `import haver`.
- If you have a dBASE file, use `import dbase`.
- If you have a table, you could try copying it and pasting it into the Data Editor.
- Finally, you can purchase a third-party transfer program that will convert the other software's data file format to Stata's data file format.

# 9 Labeling data

## Making data readable

This chapter discusses, in brief, labeling of the dataset, variables, and values. Such labeling is critical to careful use of data. Labeling variables with descriptive names clarifies their meanings. Labeling values of numerical categorical variables ensures that the real-world meanings of the encodings are not forgotten. These points are crucial when sharing data with others, including your future self. Labels are also used in the output of most Stata commands, so proper labeling of the dataset will produce much more readable results. We will work through an example of properly labeling a dataset, its variables, and the values of one encoded variable.

## The dataset structure: The describe command

At the end of *The import delimited command* in [\[GSM\] 8 Importing data](#), we saved a dataset called `afewcars.dta`. We will put this dataset into a shape that a colleague would understand. Let's see what it contains.

```
. use fewcars
. list, separator(0)
```

	make	price	mpg	weight	gear_r~o
1.	VW Rabbit	4697	25	1930	3.78
2.	Olds 98	8814	21	4060	2.41
3.	Chev. Monza	3667	.	2750	2.73
4.		4099	22	2930	3.58
5.	Datsun 510	5079	24	2280	3.54
6.	Buick Regal	5189	20	3280	2.93
7.	Datsun 810	8129	.	2750	3.55

The data allow us to make some guesses at the values in the dataset, but, for example, we do not know the units in which the price or weight is measured, and the term “mpg” could be confusing for people outside the United States. Perhaps we can learn something from the description of the dataset. Stata has the aptly named `describe` command for this purpose (as we saw in [\[GSM\] 1 Introducing Stata—sample session](#)).

```

. describe
Contains data from afewcars.dta
  obs:           7
  vars:          5                      14 Mar 2019 13:25
-----
      storage   display   value
variable name  type      format   label   variable label
-----
make         str18    %18s
price        float    %9.0g
mpg          float    %9.0g
weight       float    %9.0g
gear_ratio   float    %9.0g
-----
Sorted by:

```

Though there is precious little information that could help us as a researcher, we can glean some information here about how Stata thinks of the data from the first three columns of the output.

1. The *variable name* is the name we use to tell Stata about a variable.
2. The *storage type* (otherwise known as the *data type*) is the way in which Stata stores the data in a variable. There are six different storage types, each having its own memory requirement:
  - a. For integers:
    - `byte` for integers between  $-127$  and  $100$  (using 1 byte of memory per observation)
    - `int` for integers between  $-32,767$  and  $32,740$  (using 2 bytes of memory per observation)
    - `long` for integers between  $-2,147,483,647$  and  $2,147,483,620$  (using 4 bytes of memory per observation)
  - b. For real numbers:
    - `float` for real numbers with 8.5 digits of precision (using 4 bytes of memory per observation)
    - `double` for real numbers with 16.5 digits of precision (using 8 bytes of memory per observation)
  - c. For strings (text) between 1 and 2,045 bytes (using 1 byte of memory per observation per character for ASCII and up to 4 bytes of memory per Unicode character):
    - `str1` for one-byte-long strings
    - `str2` for two-byte-long strings
    - `str3` for three-byte-long strings
    - ...
    - `str2045` for 2,045-byte-long strings
  - d. Stata also has a `strL` storage type for strings of arbitrary length up to 2,000,000,000 bytes. `strL`s can also hold binary data, often referred to as BLOBS, or binary large objects, in databases. We will not illustrate these here.

Storage types affect both the precision of computations and the size of datasets. A quick guide to storage types is available at `help data types` or in [\[D\] Data types](#).

3. The *display format* controls how the variable is displayed; see [\[U\] 12.5 Formats: Controlling how data are displayed](#). By default, Stata sets it to something reasonable given the storage type.

We would like to make this dataset into something containing all the information we need.

To see what a well-labeled dataset looks like, we can look at a dataset stored at the Stata Press repository. We need not load the data (and disturb what we are doing); we do not even need a copy of the dataset on our machine. (You will learn more about Stata’s Internet capabilities in [GSM] 19 [Updating and extending Stata—Internet functionality](#).) All we need to do is direct describe to look at the proper file by using the command describe using *filename*.

```
. describe using https://www.stata-press.com/data/r16/auto
```

Contains data		1978 Automobile Data	
obs:	74	13 Apr 2018 17:45	
vars:	12		

---

variable name	storage type	display format	value label	variable label
<b>make</b>	str18	%-18s		<b>Make and Model</b>
<b>price</b>	int	%8.0gc		<b>Price</b>
<b>mpg</b>	int	%8.0g		<b>Mileage (mpg)</b>
<b>rep78</b>	int	%8.0g		<b>Repair Record 1978</b>
<b>headroom</b>	float	%6.1f		<b>Headroom (in.)</b>
<b>trunk</b>	int	%8.0g		<b>Trunk space (cu. ft.)</b>
<b>weight</b>	int	%8.0gc		<b>Weight (lbs.)</b>
<b>length</b>	int	%8.0g		<b>Length (in.)</b>
<b>turn</b>	int	%8.0g		<b>Turn Circle (ft.)</b>
<b>displacement</b>	int	%8.0g		<b>Displacement (cu. in.)</b>
<b>gear_ratio</b>	float	%6.2f		<b>Gear Ratio</b>
<b>foreign</b>	byte	%8.0g	origin	<b>Car type</b>

---

Sorted by: **foreign**

This output is much more informative. There are three locations where labels are attached that help explain what the dataset contains:

1. In the first line, 1978 Automobile Data is the *data label*. It gives information about the contents of the dataset. Data can be labeled by selecting **Data > Data utilities > Label utilities > Label dataset**, by using the label data command, or by editing the *Label* field in the Data portion of the Properties window. When doing this in the main window, be sure that the Properties window is unlocked.
2. There is a variable label attached to each variable. Variable labels are how we would refer to the variable in normal, everyday conversation. Here they also contain information about the units of the variables. Variables can be labeled by selecting the variable in the Variables window and editing the *Label* field in the Properties window. You can also change a variable label by using the Variables Manager or by using the label variable command.
3. The foreign variable has an attached value label. Value labels allow numeric variables such as foreign to have words associated with numeric codes. The describe output tells you that the numeric variable foreign has value label origin associated with it. Although not revealed by describe, the variable foreign takes on the values 0 and 1, and the value label origin associates 0 with Domestic and 1 with Foreign. If you browse the data (see [GSM] 6 [Using the Data Editor](#)), foreign appears to contain the values “Domestic” and “Foreign”. The values in a variable are labeled in two stages. The value label must first be defined. This can be done in the Data Editor, or in the Variables Manager, or by selecting **Data > Data utilities > Label utilities > Manage value labels** or by typing the label define command. After the labels have been defined, they must be attached to the proper variables, either by selecting **Data > Data utilities > Label utilities > Assign value label to variables** or by using the label values command.

Note: It is not necessary for the value label to have a name different from that of the variable. You could just as easily have used a value label named `foreign`.

## Labeling datasets and variables

We will now load the `afewcars.dta` dataset and give it proper labels. We will do this with the Command window to illustrate that it is simple to do in this fashion. Earlier in [Renaming and formatting variables](#) in [GSM] 6 Using the Data Editor, we used the Data Editor to achieve a similar purpose. If you use the Data Editor for the material here, you will end up with the same commands in your log; we would like to illustrate a way to work directly with commands.

```
. use fewcars
. describe
Contains data from fewcars.dta
  obs:           7
  vars:          5                               14 Mar 2019 13:25
```

---

variable name	storage type	display format	value label	variable label
<b>make</b>	str18	%18s		
<b>price</b>	float	%9.0g		
<b>mpg</b>	float	%9.0g		
<b>weight</b>	float	%9.0g		
<b>gear_ratio</b>	float	%9.0g		

---

```
Sorted by:
. label data "A few 1978 cars"
. label variable make "Make and Model"
. label variable price "Price (USD)"
. label variable mpg "Mileage (miles per gallon)"
. label variable weight "Vehicle weight (lbs.)"
. label variable gear_ratio "Gear Ratio"
. describe
Contains data from fewcars.dta
  obs:           7                               A few 1978 cars
  vars:          5                               14 Mar 2019 13:25
```

---

variable name	storage type	display format	value label	variable label
<b>make</b>	str18	%18s		<b>Make and Model</b>
<b>price</b>	float	%9.0g		<b>Price (USD)</b>
<b>mpg</b>	float	%9.0g		<b>Mileage (miles per gallon)</b>
<b>weight</b>	float	%9.0g		<b>Vehicle weight (lbs.)</b>
<b>gear_ratio</b>	float	%9.0g		<b>Gear Ratio</b>

---

```
Sorted by:
      Note: Dataset has changed since last saved.
. save fewcars2
file fewcars2.dta saved
```

## Labeling values of variables

We will now add a new indicator variable to the dataset that is 0 if the car was made in the United States and 1 if it was made in another country. Open the Data Editor and use your previously gained knowledge to add a foreign variable whose values match what is shown in this listing:

```
. list, separator(0)
```

	make	price	mpg	weight	gear_ratio	foreign
1.	VW Rabbit	4697	25	1930	3.78	1
2.	Olds 98	8814	21	4060	2.41	0
3.	Chev. Monza	3667	.	2750	2.73	0
4.		4099	22	2930	3.58	0
5.	Datsun 510	5079	24	2280	3.54	1
6.	Buick Regal	5189	20	3280	2.93	0
7.	Datsun 810	8129	.	2750	3.55	1

You can create this new variable in the Data Editor if you would like to work along. (See [\[GSM\] 6 Using the Data Editor](#) for help with the Data Editor.) Though the definitions of the categories “0” and “1” are clear in this context, it still would be worthwhile to give the values explicit labels because it will make output clear to people who are not so familiar with antique automobiles. This is done with a value label.

We saw an example of creating and attaching a value label by using the point-and-click interface available in the Data Editor in [Changing data](#) in [\[GSM\] 6 Using the Data Editor](#). Here we will do it directly from the Command window.

```
. label define origin 0 "domestic" 1 "foreign"
```

```
. label values foreign origin
```

```
. describe
```

```
Contains data from afewcars2.dta
```

```
obs:           7                A few 1978 cars  
vars:          6                14 Mar 2019 13:25
```

variable name	storage type	display format	value label	variable label
<b>make</b>	str18	%18s		<b>Make and Model</b>
<b>price</b>	float	%9.0g		<b>Price (USD)</b>
<b>mpg</b>	float	%9.0g		<b>Mileage (miles per gallon)</b>
<b>weight</b>	float	%9.0g		<b>Vehicle weight (lbs.)</b>
<b>gear_ratio</b>	float	%9.0g		<b>Gear Ratio</b>
<b>foreign</b>	byte	%8.0g	origin	

```
Sorted by:
```

```
Note: Dataset has changed since last saved.
```

```
. save afewcarslab
```

```
file afewcarslab.dta saved
```

From this example, we can see that a value label is defined via

```
label define labelname # "contents" # "contents" ...
```

It can then be attached to a variable via

```
label values variablename labelname
```

Once again, we need to save the dataset to be sure that we do not mistakenly lose the labels later. We saved this under a new filename because we have cleaned it up, and we would like to use it in the next chapter.

If you had wanted to define the value labels by using a point-and-click interface, you could do this with the Properties window in either the Main window or the Data Editor or by using the Variables Manager. See [\[GSM\] 7 Using the Variables Manager](#) for more information.

There is more to value labels than what was covered here; see [\[U\] 12.6.3 Value labels](#) for a complete treatment.

You may also add notes to your data and your variables. This feature was previously discussed in [Renaming and formatting variables](#) in [\[GSM\] 6 Using the Data Editor](#) and [Managing notes](#) in [\[GSM\] 7 Using the Variables Manager](#). You can learn more about notes by typing `help notes`, or you can get the full story in [\[D\] notes](#).



# 10 Listing data and basic command syntax

## Command syntax

This chapter gives a basic lesson on Stata's command syntax while showing how to control the appearance of a data list.

As we have seen throughout this manual, you have a choice between using menus and dialogs and using the Command window. Although many find the menus more natural and the Command window baffling at first, some practice makes working with the Command window often much faster than using menus and dialogs. The Command window can become a faster way of working because of the clean and regular syntax of Stata commands. We will cover enough to get you started; [help language](#) has more information and examples, and [\[U\] 11 Language syntax](#) has all the details.

The syntax for the `list` command can be seen by typing `help list`:

```
list [varlist] [if] [in] [, options]
```

Here is how to read this syntax:

- Anything inside square brackets is optional. For the `list` command,
  - a. *varlist* is optional. A *varlist* is a list of variable names.
  - b. *if* is optional. The *if* qualifier restricts the command to run only on those observations for which the qualifier is true. We saw examples of this in [\[GSM\] 6 Using the Data Editor](#).
  - c. *in* is optional. The *in* qualifier restricts the command to run on particular observation numbers.
  - d. `,` and *options* are optional. *options* are separated from the rest of the command by a comma.
- Optional pieces do not preclude one another unless explicitly stated. For the `list` command, it is possible to use a *varlist* with *if* and *in*.
- If a part of a word is underlined, the underlined part is the minimum abbreviation. Any abbreviation at least this long is acceptable.
  - a. The `l` in `list` is underlined, so `l`, `li`, and `lis` are all equivalent to `list`.
- Anything not inside square brackets is required. For the `list` command, only the command itself is required.

Keeping these rules in mind, let's investigate how `list` behaves when called with different arguments. We will be using the dataset `afewcarslab.dta` from the end of the previous chapter.

## list with a variable list

Variable lists (or *varlists*) can be specified in a variety of ways, all designed to save typing and encourage good variable names.

- The *varlist* is optional for `list`. This means that if no variables are specified, it is equivalent to specifying all variables. Another way to think of it is that the default behavior of the command is to run on all variables unless restricted by a *varlist*.
- You can list a subset of variables explicitly, as in `list make mpg price`.
- There are also many shorthand notations:
  - `m*` means all variables starting with `m`.
  - `price-weight` means all variables from `price` through `weight` in the dataset order.
  - `ma?e` means all variables starting with `ma`, followed by any character, and ending in `e`.

- You can list a variable by using an abbreviation unique to that variable, as in `list gear_r~o`. If the abbreviation is not unique, Stata returns an error message.

```
. list
```

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
5.	Datsun 510	5079	24	2280	3.54	foreign
6.	Buick Regal	5189	20	3280	2.93	domestic
7.	Datsun 810	8129	.	2750	3.55	foreign

```
. li make mpg price
```

	make	mpg	price
1.	VW Rabbit	25	4697
2.	Olds 98	21	8814
3.	Chev. Monza	.	3667
4.		22	4099
5.	Datsun 510	24	5079
6.	Buick Regal	20	5189
7.	Datsun 810	.	8129

```
. list m*
```

	make	mpg
1.	VW Rabbit	25
2.	Olds 98	21
3.	Chev. Monza	.
4.		22
5.	Datsun 510	24
6.	Buick Regal	20
7.	Datsun 810	.

```
. li price-weight
```

	price	mpg	weight
1.	4697	25	1930
2.	8814	21	4060
3.	3667	.	2750
4.	4099	22	2930
5.	5079	24	2280
6.	5189	20	3280
7.	8129	.	2750

```
. list ma?e
```

	make
1.	VW Rabbit
2.	Olds 98
3.	Chev. Monza
4.	
5.	Datsun 510
6.	Buick Regal
7.	Datsun 810

```
. l gear_r~o
```

	gear_r~o
1.	3.78
2.	2.41
3.	2.73
4.	3.58
5.	3.54
6.	2.93
7.	3.55

## list with if

The `if` qualifier uses a logical expression to determine which observations to use. If the expression is true, the observation is used in the command; otherwise, it is skipped. The operators whose results are either true or false are

---

<	less than
<=	less than or equal
==	equal
>	greater than
>=	greater than or equal
!=	not equal
&	and
	or
!	not (logical negation)
()	parentheses are for grouping to specify order of evaluation

---

In the logical expressions, `&` is evaluated before `|` (similar to multiplication before addition in arithmetic). You can use this in your expressions, but it is often better to use parentheses to ensure that the expressions are evaluated in the proper order. See [U] 13.2 **Operators** for complete details.

```
. list
```

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
5.	Datsun 510	5079	24	2280	3.54	foreign
6.	Buick Regal	5189	20	3280	2.93	domestic
7.	Datsun 810	8129	.	2750	3.55	foreign

```
. list if mpg > 22
```

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
3.	Chev. Monza	3667	.	2750	2.73	domestic
5.	Datsun 510	5079	24	2280	3.54	foreign
7.	Datsun 810	8129	.	2750	3.55	foreign

```
. list if (mpg > 22) & !missing(mpg)
```

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
5.	Datsun 510	5079	24	2280	3.54	foreign

```
. list make mpg price gear if (mpg > 22) | (price > 8000 & gear < 3.5)
```

	make	mpg	price	gear_r~o
1.	VW Rabbit	25	4697	3.78
2.	Olds 98	21	8814	2.41
3.	Chev. Monza	.	3667	2.73
5.	Datsun 510	24	5079	3.54
7.	Datsun 810	.	8129	3.55

```
. list make mpg if mpg <= 22 in 2/4
```

	make	mpg
2.	Olds 98	21
4.		22

In the listings above, we see more examples of Stata treating missing numerical values as large values, as well as the care that should be taken when the `if` qualifier is applied to a variable with missing values. See [\[GSM\] 6 Using the Data Editor](#).

## list with if, common mistakes

Here is a series of listings with common errors and their corrections. See if you can find the errors before reading the correct entry.

```
. list
```

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
5.	Datsun 510	5079	24	2280	3.54	foreign
6.	Buick Regal	5189	20	3280	2.93	domestic
7.	Datsun 810	8129	.	2750	3.55	foreign

```
. list if mpg=21
=exp not allowed
r(101);
```

The error arises because “equal” is expressed by ==, not by =. Corrected, it becomes

```
. list if mpg==21
```

	make	price	mpg	weight	gear_r~o	foreign
2.	Olds 98	8814	21	4060	2.41	domestic

Other common errors with logic:

```
. list if mpg==21 if weight > 4000
invalid syntax
r(198);
. list if mpg==21 and weight > 4000
invalid 'and'
r(198);
```

Joint tests are specified with &, not with the word and or multiple ifs. The if qualifier should be if mpg==21 & weight>4000, not if mpg==21 if weight>4000. Here is its correction:

```
. list if mpg==21 & weight > 4000
```

	make	price	mpg	weight	gear_r~o	foreign
2.	Olds 98	8814	21	4060	2.41	domestic

A problem with string variables:

```
. list if make==Datsun 510
Datsun not found
r(111);
```

Strings must be in double quotes, as in `make=="Datsun 510"`. Without the quotes, Stata thinks that `Datsun` is a variable that it cannot find. Here is the correction:

```
. list if make=="Datsun 510"
```

	make	price	mpg	weight	gear_r~o	foreign
5.	Datsun 510	5079	24	2280	3.54	foreign

Confusing value labels with strings:

```
. list if foreign=="domestic"
type mismatch
r(109);
```

Value labels look like strings, but the underlying variable is numeric. Variable `foreign` takes on values 0 and 1 but has the value label that attaches 0 to “domestic” and 1 to “foreign” (see [GSM] 9 Labeling data). To see the underlying numeric values of variables with labeled values, use the `label list` command (see [D] label), or investigate the variable with codebook `varname`. We can correct the error here by looking for observations where `foreign==0`.

There is a second construction that also allows the use of the value label directly.

```
. list if foreign==0
```

	make	price	mpg	weight	gear_r~o	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
6.	Buick Regal	5189	20	3280	2.93	domestic

```
. list if foreign=="domestic":origin
```

	make	price	mpg	weight	gear_r~o	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
6.	Buick Regal	5189	20	3280	2.93	domestic

## list with in

The `in` qualifier uses a *numlist* to give a range of observations that should be listed. *numlists* have the form of one number or *first/last*. Positive numbers count from the beginning of the dataset. Negative numbers count from the end of the dataset. Here are some examples:

. list

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
5.	Datsun 510	5079	24	2280	3.54	foreign
6.	Buick Regal	5189	20	3280	2.93	domestic
7.	Datsun 810	8129	.	2750	3.55	foreign

. list in 1

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign

. list in -1

	make	price	mpg	weight	gear_r~o	foreign
7.	Datsun 810	8129	.	2750	3.55	foreign

. list in 2/4

	make	price	mpg	weight	gear_r~o	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic

. list in -3/-2

	make	price	mpg	weight	gear_r~o	foreign
5.	Datsun 510	5079	24	2280	3.54	foreign
6.	Buick Regal	5189	20	3280	2.93	domestic

## Controlling the list output

The fine control over `list` output is exercised by specifying one or more options. You can use `sepyby()` to separate observations by variable. `abbreviate()` specifies the minimum number of characters to abbreviate a variable name in the output. `divider` draws a vertical line between the variables in the list.

```
. sort foreign
. list ma p g f, sepby(foreign)
```

	make	price	gear_r~o	foreign
1.	<b>Chev. Monza</b>	3667	2.73	domestic
2.		4099	3.58	domestic
3.	<b>Buick Regal</b>	5189	2.93	domestic
4.	Olds 98	8814	2.41	domestic
5.	<b>Datsun 810</b>	8129	3.55	foreign
6.	Datsun 510	5079	3.54	foreign
7.	VW Rabbit	4697	3.78	foreign

```
. list make weight gear, abbreviate(10)
```

	make	weight	gear_ratio
1.	<b>Chev. Monza</b>	2750	2.73
2.		2930	3.58
3.	<b>Buick Regal</b>	3280	2.93
4.	Olds 98	4060	2.41
5.	<b>Datsun 810</b>	2750	3.55
6.	Datsun 510	2280	3.54
7.	VW Rabbit	1930	3.78

```
. list, divider
```

	make	price	mpg	weight	gear_r~o	foreign
1.	<b>Chev. Monza</b>	3667	.	2750	2.73	domestic
2.		4099	22	2930	3.58	domestic
3.	<b>Buick Regal</b>	5189	20	3280	2.93	domestic
4.	Olds 98	8814	21	4060	2.41	domestic
5.	<b>Datsun 810</b>	8129	.	2750	3.55	foreign
6.	Datsun 510	5079	24	2280	3.54	foreign
7.	VW Rabbit	4697	25	1930	3.78	foreign


The separator() option draws a horizontal line at specified intervals. When not specified, it defaults to a value of 5.



```
. list, separator(3)
```

	make	price	mpg	weight	gear_r~o	foreign
1.	<b>Chev. Monza</b>	<b>3667</b>	<b>.</b>	<b>2750</b>	<b>2.73</b>	<b>domestic</b>
2.		<b>4099</b>	<b>22</b>	<b>2930</b>	<b>3.58</b>	<b>domestic</b>
3.	<b>Buick Regal</b>	<b>5189</b>	<b>20</b>	<b>3280</b>	<b>2.93</b>	<b>domestic</b>
4.	<b>Olds 98</b>	<b>8814</b>	<b>21</b>	<b>4060</b>	<b>2.41</b>	<b>domestic</b>
5.	<b>Datsun 810</b>	<b>8129</b>	<b>.</b>	<b>2750</b>	<b>3.55</b>	<b>foreign</b>
6.	<b>Datsun 510</b>	<b>5079</b>	<b>24</b>	<b>2280</b>	<b>3.54</b>	<b>foreign</b>
7.	<b>VW Rabbit</b>	<b>4697</b>	<b>25</b>	<b>1930</b>	<b>3.78</b>	<b>foreign</b>

## Break

If you want to interrupt a Stata command, click on the **Break** button, .

It is always safe to click on the **Break** button. After you click on **Break**, the state of the system is the same as if you had never issued the original command.

# 11 Creating new variables

## generate and replace

This chapter shows the basics of creating and modifying variables in Stata. We saw how to work with the Data Editor in [\[GSM\] 6 Using the Data Editor](#)—this chapter shows how we would do this from the Command window. The two primary commands used for this are

- `generate` for creating new variables. It has a minimum abbreviation of `g`.
- `replace` for replacing the values of an existing variable. It may not be abbreviated because it alters existing data and hence can be considered dangerous.

The most basic form for creating new variables is `generate newvar = exp`, where *exp* is any kind of *expression*. Of course, both `generate` and `replace` can be used with `if` and `in` qualifiers. An expression is a formula made up of constants, existing variables, operators, and functions. Some examples of expressions (using variables from the `auto` dataset) would be `2 + price`, `weight^2` or `sqrt(gear_ratio)`.

The operators defined in Stata are given in the table below:

Arithmetic		Logical		Relational (numeric and string)	
+	addition	!	not	>	greater than
-	subtraction		or	<	less than
*	multiplication	&	and	>=	> or equal
/	division			<=	< or equal
^	power			==	equal
				!=	not equal
+	string concatenation				

Stata has many mathematical, statistical, string, date, time-series, and programming functions. See `help functions` for the basics, and see the [Stata Functions Reference Manual](#) for a complete list and full details of all the built-in functions.

You can use menus and dialogs to create new variables and modify existing variables by selecting menu items from the **Data > Create or change data** menu. This feature can be handy for finding functions quickly. However, we will use the Command window for the examples in this chapter because we would like to illustrate simple usage and some pitfalls.

Stata has some utility commands for creating new variables:

- The `egen` command is useful for working across groups of variables or within groups of observations. See [\[D\] egen](#) for more information.
- The `encode` command turns categorical string variables into encoded numeric variables, while its counterpart `decode` reverses this operation. See [\[D\] encode](#) for more information.
- The `destring` command turns string variables that should be numeric, such as numbers with currency symbols, into numbers. To go from numbers to strings, the `tostring` command is useful. See [\[D\] destring](#) for more information.

We will focus our efforts on `generate` and `replace`.

## generate

There are some details you should know about the `generate` command:

- The basic form of the `generate` command is `generate newvar = exp`, where *newvar* is a new variable name and *exp* is any valid expression. You will get an error message if you try to `generate` a variable that already exists.
- An algebraic calculation using a missing value yields a missing value, as does division by zero, the square root of a negative number, or any other computation which is impossible.
- If missing values are generated, the number of missing values in *newvar* is always reported. If Stata says nothing about missing values, then no missing values were generated.
- You can use `generate` to set the storage type of the new variable as it is generated. You might want to create an indicator (0/1) variable as a `byte`, for example, because it saves 3 bytes per observation over using the default storage type of `float`.

Below are some examples of creating new variables from the `afewcarslab` dataset, which we created in *Labeling values of variables* in [GSM] 9 **Labeling data**. (To work along, start by opening the `auto` dataset with `sysuse auto`. We are using a smaller dataset to make shorter listings.) The last example shows a way to generate an indicator variable for cars weighing more than 3,000 pounds. Logical expressions in Stata result in 1 for “true” and 0 for “false”. The `if` qualifier is used to ensure that the computations are done only for observations where `weight` is not missing.

```
. use afewcarslab
(A few 1978 cars)
. list make mpg weight
```

	make	mpg	weight
1.	VW Rabbit	25	1930
2.	Olds 98	21	4060
3.	Chev. Monza	.	2750
4.		22	2930
5.	Datsun 510	24	2280
6.	Buick Regal	20	3280
7.	Datsun 810	.	2750

```
. * changing MPG to liters per 100km
. generate lphk = 3.7854 * (100 / 1.6093) / mpg
(2 missing values generated)
. label var lphk "Liters per 100km"
. * getting logarithms of price
. g lnprice = ln(price)
. * making an indicator of hugeness
. gen byte huge = weight >= 3000 if !missing(weight)
. l make mpg weight lphk lnprice huge
```

	make	mpg	weight	lphk	lnprice	huge
1.	VW Rabbit	25	1930	9.408812	8.454679	0
2.	Olds 98	21	4060	11.20097	9.084097	1
3.	Chev. Monza	.	2750	.	8.207129	0
4.		22	2930	10.69183	8.318499	0
5.	Datsun 510	24	2280	9.800845	8.532869	0
6.	Buick Regal	20	3280	11.76101	8.554296	1
7.	Datsun 810	.	2750	.	9.003193	0

## replace

Whereas `generate` is used to create new variables, `replace` is the command used for existing variables. Stata uses two different commands to prevent you from accidentally modifying your data. The `replace` command cannot be abbreviated. Stata generally requires you to spell out completely any command that can alter your existing data.

```
. list make weight
```

	make	weight
1.	VW Rabbit	1930
2.	Olds 98	4060
3.	Chev. Monza	2750
4.		2930
5.	Datsun 510	2280
6.	Buick Regal	3280
7.	Datsun 810	2750

```
. * will give an error because weight already exists
```

```
. gen weight = weight/1000
```

```
variable weight already defined
```

```
r(110);
```

```
. * will replace weight in lbs by weight in 1000s of lbs
```

```
. replace weight = weight/1000
```

```
(7 real changes made)
```

```
. list make weight
```

	make	weight
1.	VW Rabbit	1.93
2.	Olds 98	4.06
3.	Chev. Monza	2.75
4.		2.93
5.	Datsun 510	2.28
6.	Buick Regal	3.28
7.	Datsun 810	2.75

Suppose that you want to create a new variable, `predprice`, which will be the predicted price of the cars in the following year. You estimate that domestic cars will increase in price by 5% and foreign cars, by 10%.

One way to create the variable would be to first use `generate` to compute the predicted domestic car prices. Then use `replace` to change the missing values for the foreign cars to their proper values.

```
. gen predprice = 1.05*price if foreign==0
(3 missing values generated)
. replace predprice = 1.10*price if foreign==1
(3 real changes made)
. list make foreign price predprice, nolabel
```

	make	foreign	price	predprice
1.	VW Rabbit	1	4697	5166.7
2.	Olds 98	0	8814	9254.7
3.	Chev. Monza	0	3667	3850.35
4.		0	4099	4303.95
5.	Datsun 510	1	5079	5586.9
6.	Buick Regal	0	5189	5448.45
7.	Datsun 810	1	8129	8941.9

Of course, because `foreign` is an indicator variable, we could generate the predicted variable with one command:

```
. gen predprice2 = (1.05 + 0.05*foreign)*price
. list make foreign price predprice predprice2, nolabel
```

	make	foreign	price	predprice	predprice2
1.	VW Rabbit	1	4697	5166.7	5166.7
2.	Olds 98	0	8814	9254.7	9254.7
3.	Chev. Monza	0	3667	3850.35	3850.35
4.		0	4099	4303.95	4303.95
5.	Datsun 510	1	5079	5586.9	5586.9
6.	Buick Regal	0	5189	5448.45	5448.45
7.	Datsun 810	1	8129	8941.9	8941.9

## generate with string variables

Stata is smart. When you generate a variable and the expression evaluates to a string, Stata creates a string variable with a storage type as long as necessary, and no longer than that. `where` is a `str1` in the following example:

```
. list make foreign
```

	make	foreign
1.	VW Rabbit	foreign
2.	Olds 98	domestic
3.	Chev. Monza	domestic
4.		domestic
5.	Datsun 510	foreign
6.	Buick Regal	domestic
7.	Datsun 810	foreign

```
. gen where = "D" if foreign=="domestic":origin
(3 missing values generated)
```

```
. replace where = "F" if foreign=="foreign":origin
(3 real changes made)
```

```
. list make foreign where
```

	make	foreign	where
1.	VW Rabbit	foreign	F
2.	Olds 98	domestic	D
3.	Chev. Monza	domestic	D
4.		domestic	D
5.	Datsun 510	foreign	F
6.	Buick Regal	domestic	D
7.	Datsun 810	foreign	F

```
. describe where
```

variable name	storage type	display format	value label	variable label
<b>where</b>	str1	%9s		

Stata has some useful tools for working with string variables. Here we split the `make` variable into `make` and `model` and then create a variable that has the model together with where the model was manufactured:

```
. gen model = usubstr(make, ustrpos(make, " ") + 1, .)
(1 missing value generated)
. gen modelwhere = model + " " + where
. list make where model modelwhere
```

	make	where	model	modelw~e
1.	VW Rabbit	F	Rabbit	Rabbit F
2.	Olds 98	D	98	98 D
3.	Chev. Monza	D	Monza	Monza D
4.		D		D
5.	Datsun 510	F	510	510 F
6.	Buick Regal	D	Regal	Regal D
7.	Datsun 810	F	810	810 F

There are a few things to note about how these commands work:

1. `ustrpos( $s_1, s_2$ )` produces an integer equal to the first character in the string  $s_1$  at which the string  $s_2$  is found or 0 if it is not found. In this example, `ustrpos(make, " ")` finds the position of the first space in each observation of `make`.
2. `usubstr( $s, start, len$ )` produces a string of length  $len$  characters, beginning at character  $start$  of string  $s$ . If  $c_1 = .$ , the result is the string from character  $start$  to the end of string  $s$ .
3. Putting 1 and 2 together: `usubstr( $s, ustrpos(s, " ") + 1, .$ )` will always give the string  $s$  with its first word removed. Because `make` contains both the make and the model of each car, and `make` never contains a space in this dataset, we have found each car's model.
4. The operator "+", when applied to string variables, will concatenate the strings (that is, join them together). The expression `"this" + "that"` results in the string `"thisthat"`. When the variable `modelwhere` was generated, a space (" ") was added between the two strings.
5. The missing value for a string is nothing special—it is simply the empty string "". Thus the value of `modelwhere` for the car with no make or model is " D" (note the leading space).
6. If your strings might contain Unicode characters, use the Unicode versions of the string functions, as shown above. See [U] 12.4.2 Handling Unicode strings.



# 12 Deleting variables and observations

## clear, drop, and keep

In this chapter, we will present the tools for paring observations and variables from a dataset. We saw how to do this using the Data Editor in [\[GSM\] 6 Using the Data Editor](#); this chapter presents the methods for doing so from the Command window.

There are three main commands for removing data and other Stata objects, such as value labels, from memory: `clear`, `drop`, and `keep`. Remember that they affect only what is in memory. None of these commands alters anything that has been saved to disk.

## clear and drop `_all`

Suppose that you are working on an analysis or a simulation and that you need to clear out Stata's memory so that you can impute different values or simulate a new dataset. You are not interested in saving any of the changes you have made to the dataset in memory—you would just like to have an empty dataset. What you do depends on how much you want to clear out: at any time, you can have not only data but also metadata such as value labels, stored results from previous commands, and stored matrices. The `clear` command will let you carefully clear out data or other objects; we are interested only in simple usage here. For more information, see `help clear` and [\[D\] clear](#).

If you type the command `clear` into the Command window, it will remove all variables and value labels. In basic usage, this is typically enough. It has the nice property that it does not remove any stored results, so you can load a new dataset and predict values by using stored estimation results from a model fit on a previous dataset. See `help postest` and [\[U\] 20 Estimation and postestimation commands](#) for more information.

If you want to be sure that everything is cleared out, use the command `clear all`. This command will clear Stata's memory of data and all auxiliary objects so that you can start with a clean slate. The first time you use `clear all` while you have a graph or dialog open, you may be surprised when that graph or dialog closes; this is necessary so that Stata can free all memory being used.

If you want to get rid of just the data and nothing else, you can use the command `drop _all`.

## drop

The `drop` command is used to remove variables or observations from the dataset in memory.

- If you want to drop variables, use `drop varlist`.
- If you want to drop observations, use `drop` with an `if` or an `in` qualifier or both.

We will use the `afewcarslab` dataset to illustrate `drop`:

```
. use afewcarslab
```

```
(A few 1978 cars)
```

```
. list
```

	make	price	mpg	weight	gear_ratio	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
5.	Datsun 510	5079	24	2280	3.54	foreign
6.	Buick Regal	5189	20	3280	2.93	domestic
7.	Datsun 810	8129	.	2750	3.55	foreign

```
. drop in 1/3
```

```
(3 observations deleted)
```

```
. list
```

	make	price	mpg	weight	gear_ratio	foreign
1.		4099	22	2930	3.58	domestic
2.	Datsun 510	5079	24	2280	3.54	foreign
3.	Buick Regal	5189	20	3280	2.93	domestic
4.	Datsun 810	8129	.	2750	3.55	foreign

```
. drop if mpg > 21
```

```
(3 observations deleted)
```

```
. list
```

	make	price	mpg	weight	gear_ratio	foreign
1.	Buick Regal	5189	20	3280	2.93	domestic

```
. drop gear_ratio
```

```
. list
```

	make	price	mpg	weight	foreign
1.	Buick Regal	5189	20	3280	domestic

```
. drop m*
```

```
. list
```

	price	weight	foreign
1.	5189	3280	domestic

These changes are only to the data in memory. If you want to make the changes permanent, you need to save the dataset.

## keep

`keep` tells Stata to drop all variables except those specified explicitly or through the use of an `if` or `in` expression. Just like `drop`, `keep` can be used with *varlist* or with qualifiers but not with both at once. We use a `clear` command at the start of this example so that we can reload the `afewcarslab` dataset:

```
. clear
. use awhilecarslab
(A few 1978 cars)
. list
```

	make	price	mpg	weight	gear_r~o	foreign
1.	VW Rabbit	4697	25	1930	3.78	foreign
2.	Olds 98	8814	21	4060	2.41	domestic
3.	Chev. Monza	3667	.	2750	2.73	domestic
4.		4099	22	2930	3.58	domestic
5.	Datsun 510	5079	24	2280	3.54	foreign
6.	Buick Regal	5189	20	3280	2.93	domestic
7.	Datsun 810	8129	.	2750	3.55	foreign

```
. keep in 4/7
(3 observations deleted)
. list
```

	make	price	mpg	weight	gear_r~o	foreign
1.		4099	22	2930	3.58	domestic
2.	Datsun 510	5079	24	2280	3.54	foreign
3.	Buick Regal	5189	20	3280	2.93	domestic
4.	Datsun 810	8129	.	2750	3.55	foreign

```
. keep if mpg <= 21
(3 observations deleted)
. list
```

	make	price	mpg	weight	gear_r~o	foreign
1.	Buick Regal	5189	20	3280	2.93	domestic


```
. keep m*
. list
```

	make	mpg
1.	Buick Regal	20

# 13 Using the Do-file Editor—automating Stata


## The Do-file Editor

Stata comes with an integrated text editor called the Do-file Editor, which can be used for many tasks. It gets its name from the term *do-file*, which is a file containing a list of commands for Stata to run (called a batch file or a script in other settings). See [U] 16 Do-files for more information. Although the Do-file Editor has advanced features that can help in writing such files, it can also be used to build up a series of commands that can then be submitted to Stata all at once. This feature can be handy when writing a loop to process multiple variables in a similar fashion or when doing complex, repetitive tasks interactively.


To get the most from this chapter, you should work through it at your computer. Start by opening the do-file editor, either by clicking on the **Do-file Editor** button, , or by typing `doedit` in the Command window and pressing *Return*.


## The Do-file Editor toolbar

The Do-file Editor has seven buttons. Many of the buttons share a similar purpose with their look-alikes in the main Stata toolbar.




If you ever forget what a button does, hover the mouse pointer over a button, and a tooltip will appear.


 **Open:** Open a do-file from disk in a new tab in the Do-file Editor.


 **Save:** Save the current do-file to disk.

 **Print:** Print the contents of the Do-file Editor.

 **Find:** Open the Find bar for finding text.

 **Show:** Toggle display of invisible characters.

 **Zoom:** Change the display size of the text.

 **Execute (do):** Run the commands in the do-file, showing all commands and their output. If text is highlighted, the button becomes the **Execute selection (do)** button and will run only the selected lines, showing all output. We will refer to this as the **Do** button. If you click on the arrow next to the **Do** button, you will see further choices for what gets done.

## Using the Do-file Editor

Suppose that we would like to analyze fuel usage for 1978 automobiles in a manner similar to what we did in [GSM] 1 [Introducing Stata—sample session](#). We know that we will be issuing many commands to Stata during our analysis and that we want to be able to reproduce our work later without having to type each command again.


We can do this easily in Stata: simply save a text file containing the commands. When that is done, we can tell Stata to run the file and execute each command in sequence. Such a file is known as a Stata *do-file*; see [U] 16 [Do-files](#).

To analyze fuel usage of 1978 automobiles, we would like to create a new variable containing gallons per mile. We would like to see how that variable changes in relation to vehicle weight for both domestic and imported cars. Performing a regression with our new variable would be a good first step.

To get started, click on the **Do-file Editor** button to open the Do-file Editor. After the Do-file Editor opens, type the commands below into the Do-file Editor. Purposely misspell the name of the `foreign` variable on the fifth line. (We are intentionally making some common mistakes and then pointing you to the solutions. This will save you time later.)

```
* an example do-file
sysuse auto
generate gp100m = 100/mpg
label var gp100m "Gallons per 100 miles"
regress gp100m weight foreing
```


Here is what your Do-file Editor should look like now:



You will notice that the color of the text changes as you type. The different colors are examples of the Do-file Editor's syntax highlighting. The colors and text properties of the syntax elements can be changed by right-clicking in the Do-file Editor, selecting **Preferences...** and then clicking on the **Syntax highlighting** tab in the resulting window.


Syntax highlighting extends beyond highlighting Stata commands. You can switch the syntax highlighting from Stata by clicking on the dropdown menu in the lower-left corner of the Do-file Editor and choosing the language you would like. Stata allows highlighting of Markdown because Stata can process Markdown to create dynamic documents. See [RPT] [dyndoc](#) for more information. Highlighting of Python is enabled because it is possible to call out to Python from Stata. See [P] [python](#) for more information. Stata will default to the proper language based on the extension of the file you are editing, but if the file has not been saved yet, you will need to tell it what language to choose.

Also note that if you pause briefly as you type, the Do-file Editor will allow autocompletion of words that are already in the do-file. Once the suggestions appear, more typing will narrow down the possibilities. You can navigate the suggestions using the up- and down-arrow keys or keep typing to narrow them to a single word. Once you have the word you like, pressing *Return* will place the word in your do-file.

Click on the **Do** button, , to execute the commands. Stata executes the commands in sequence, and the results appear in the Results window:

```
. do /tmp/SD00001.000000
. * an example do-file
. sysuse auto
(1978 Automobile Data)
. generate gp100m = 100/mpg
. label var gp100m "Gallons per 100 miles"
. regress gp100m weight foreing
variable foreing not found
r(111);
.
end of do-file
```

The `do "/tmp/..."` command is how Stata executes the commands in the Do-file Editor. Stata saves the commands to a temporary file and issues the `do` command to execute them. Everything worked as planned until Stata saw the misspelled variable. The first three commands were executed, but an error was produced on the fourth. Stata does not know of a variable named `foreing`. We need to go back to the Do-file Editor and change the misspelled variable name to `foreign` in the last line:



Click on the **Do** button again. Alas, Stata now fails on the first line—it will not overwrite the dataset in memory that we changed.


```
. do /tmp/SD00001.000000
. * an example do-file
. sysuse auto
no; dataset in memory has changed since last saved
r(4);
.
end of do-file
```

We now have a choice for what we should do:

- We can put a `clear` command in our do-file as the very first command. This automatically clears out Stata's memory before the do-file tries to load the `auto` dataset. This is convenient but dangerous because it defeats Stata's protection against throwing away changes without warning.
- We can type a `clear` command in the Command window to manually clear the dataset and then process the do-file again. This process can be aggravating when building a complicated do-file.

Here is some advice: Automatically clear Stata's memory while debugging the do-file. Once the do-file is in its final form, decide the context in which it will be used. If it will be used in a highly automated environment (such as when certifying), the do-file should still automatically clear Stata's memory. If it will be used rarely, do not clear Stata's memory. This decision will save much heartache.

We will add a `clear` option to the `sysuse` command to automatically clear the dataset in Stata's memory before the do-file runs:



The do-file now runs well, as clicking on the **Do** button shows:

```
. do /tmp/SD00001.000000
. * an example do-file
. sysuse auto, clear
(1978 Automobile Data)
. generate gp100m = 100/mpg
. label var gp100m "Gallons per 100 miles"
. regress gp100m weight foreign
```

Source	SS	df	MS	Number of obs = 74		
Model	91.1761694	2	45.5880847	F( 2, 71) = 113.97		
Residual	28.4000913	71	.400001287	Prob > F = 0.0000		
Total	119.576261	73	1.63803097	R-squared = 0.7625		
				Adj R-squared = 0.7558		
				Root MSE = .63246		

gp100m	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
weight	.0016254	.0001183	13.74	0.000	.0013896	.0018612
foreign	.6220535	.1997381	3.11	0.003	.2237871	1.02032
_cons	-.0734839	.4019932	-0.18	0.855	-.8750354	.7280677

```
.
end of do-file
```

You might want to select **File > Save as...** to save this do-file while the Do-file Editor is in front. Later, you could select **File > Open...** to open it and then add more commands as you move forward with your analysis. By saving the commands of your analysis in a do-file as you go, you do not have to worry about retyping them with each new Stata session. Think hard about removing the `clear` option from the first command.

After you have saved your do-file, you can execute the commands it contains by typing `do filename`, where the *filename* is the name of your do-file.

## The File menu

When the Do-file Editor is in front, the **File** menu's items apply to do-files. You may choose any of these menu items: create a **New > Do-file, Open...** an existing file, **Save** the current file, save the current file under a new name with **Save as...**, or **Print** the current file. There are also buttons on the Do-file Editor's toolbar that correspond to these features.

Finally, you can create a **New > Project...** to keep track of collections of files used in a project. These can be do-files, data files, graph files, or any other files you like. For more information on the Project Manager, see [P] [Project Manager](#).

## The Edit menu

The **Edit** menu of the Do-file Editor includes the standard **Undo**, **Redo**, **Cut**, **Copy**, **Paste**, and **Find** capabilities. There are several other **Edit** menu features that you might find useful:

- You can select **Insert file...** to insert the contents of another file at the current cursor position in the Do-file Editor.
- You can select the current line with **Select line**.
- You can delete the current line with **Delete line**.
- **Find > Go to line...** will allow you to jump to a specific line number. The line numbers are displayed at the left of the Do-file Editor window.
- **Advanced** leads to a submenu with some programmer's friends:
  - **Shift right** indents the selection by one tab.
  - **Shift left** unindents the selection by one tab.
  - **Re-indent** indents the selection according to its nesting within blocks and programs.
  - **Toggle comment** toggles `//`-style comments at the start of the selected lines.
  - **Add block comment** puts a `/*` before and a `*/` after the selected region, commenting it out.
  - **Remove block comment** undoes the above.
  - **Make selection uppercase** converts the selection to all capital letters.
  - **Make selection lowercase** converts the selection to all lowercase letters.
  - **Complete word** attempts to complete the current word based on words that are already in the do-file. If there are multiple possibilities, all will be shown. You can either pick the completion you would like or keep typing to narrow the choices.
  - **Convert to UTF-8...** converts the current file to UTF-8 encoding.
  - **Convert line endings to macOS/Unix format (\n)** converts the line endings for the current file to macOS/Unix format.
  - **Convert line endings to Windows format (\r\n)** converts the line endings for the current file to Windows format.
  - **Convert tabs to spaces** replaces any tab characters with spaces, leaving the spacing as it currently appears.
  - **Convert leading spaces to tabs** converts any spaces at the start of lines to tab characters. The number of spaces per tab is determined by a preference setting.
  - **Convert all spaces to tabs** converts spaces to tab characters wherever possible. The number of spaces per tab is determined by a preference setting.

Matching and balancing of parentheses ( ), braces { }, and brackets [ ] are also available from the **Edit** menu. When you select **Edit > Find > Match brace**, the Do-file Editor looks at the character immediately to the left and right of the cursor. If either is one of the characters that the editor can match, the editor will find the matching character and place the cursor immediately in front of it. If there is no match, the menu item will be inactive.


When you select **Edit > Find > Balance braces**, the Do-file Editor looks to the left and right of the current cursor position or selection and creates a selection that includes the narrowest level of matching characters. If you select **Balance braces** again, the editor will expand the selection to include the next level of matching characters. If there is no match, the cursor will not move. Balancing braces is useful for working with complicated expressions or blocks of code defined by loops or `if` commands. See [P] [foreach](#), [P] [forvalues](#), [P] [while](#), and [P] [if](#) for more information.

**Balance braces** is easier to explain with an example. Type `(now (is the) time)` in the Do-file Editor. Place the cursor between the words `is` and `the`. Select **Edit > Find > Balance braces**. The



Do-file Editor will select (is the). If you select **Balance braces** again, the Do-file Editor will select (now (is the) time).

Text in Stata strings can include Unicode characters and is encoded as UTF-8 (see [U] 12.4.2 **Handling Unicode strings**). However, you may have do-files, ado-files, or other text files that you used with Stata 13 or earlier, and those files contain characters other than plain ASCII such as accented characters, Chinese, Japanese, or Korean (CJK) characters, Cyrillic characters, and the like. If you open a file that is not encoded in UTF-8, Stata prompts you to specify the encoding for the file so that it can convert the file to UTF-8. If you cancel the conversion or choose the wrong encoding, you can try the conversion again later using **Convert to UTF-8**. The conversion to UTF-8 can be undone by using **Edit > Undo** and is not permanent until you save the do-file. For Stata datasets with characters not encoded in UTF-8 or for bulk conversion of multiple Stata files, you should use the `unicode translate` command.

Editing tip: You can split the Do-file Editor window vertically by clicking on the **Split window** button in the status bar . This is useful for looking at two widely separated places in a file at the same time. To go back to a single pane view, click on the close button in either of the split panes.

## The View > Do-file Editor menu

You have already learned about the **Do** button. Selecting **View > Do-file Editor > Execute (do)** is equivalent to clicking on the **Execute (do)** button.

Selecting **View > Do-file Editor > Execute (do) to bottom** will send all the commands from the current line through the end of the contents of the Do-file Editor to the Command window. This method is a quick way to run a part of a do-file.

Selecting **View > Do-file Editor > Execute quietly (run)** is equivalent to **View > Do-file Editor > Execute (do)** but the commands will be executed quietly; that is, no output will be displayed in the Command window.

Selecting **View > Do-file Editor > Execute (include)** is similar to clicking on the **Execute (do)** button with one major difference: local macros defined in the current session can be expanded in the commands being executed.

**Do** is equivalent to Stata's `do` command, whereas **Execute (include)** is equivalent to Stata's `include` command. See [U] 16 **Do-files** for a complete discussion.

You can also preview files in the Viewer by selecting **View > Do-file Editor > Show file in Viewer**. This feature is useful when working with files that use Stata's SMCL tags, such as when writing help files or editing log files.

## Saving interactive commands from Stata as a do-file

While working interactively with Stata, you might decide that you would like to rerun the last several commands that you typed interactively. From the History window, you can send highlighted commands or even the entire contents to the Do-file Editor. You can also save commands as a do-file and open that file in the Do-file Editor. You can copy a command from a dialog (rather than submit it) and paste it into the Do-file Editor. See [GSM] 6 **Using the Data Editor** for details. Also see [R] **log** for information on the `cmdlog` command, which allows you to log all commands that you type in Stata to a do-file.

## Projects

For advanced users managing many files as part of a project, Stata has a Project Manager that uses the Do-file Editor. For more information on the Project Manager, see [P] [Project Manager](#).

# 14 Graphing data

## Working with graphs


Stata has a rich system for graphical representation of data. The main command for creating graphs is unsurprisingly named `graph`. Behind this plain name is a wealth of tools. In this chapter, we will make one simple graph to point out the basics of the Graph window. See the [G] [Stata Graphics Reference Manual](#) for more information about all aspects of working with graphs.

## A simple graph example

In the sample session of [GSM] 1 [Introducing Stata—sample session](#), we made a scatterplot, added a fitted regression line, and made a grid of scatterplots to allow comparisons across groups. Here, using the `auto` dataset, we make a simple box plot that shows the displacements of the cars' engines and how they compare across repair records within the place of manufacture of the cars. Start by loading the dataset by typing `sysuse auto` in the Command window and pressing `Return`.

We select **Graphics > Box plot**, choose or type `displacement` in the *Variables* field on the **Main** tab, click on the **Categories** tab, check the *Group 1* checkbox and enter `rep78` for the first grouping variable, and check the *Group 2* checkbox and enter `foreign` for the second grouping variable. Finally, we click on the **Submit** button so that we could easily make changes to the graph if need be. After we look at the graph, we realize that we forgot the title. We close the Graph window, click on the **Titles** tab of the *graph box* dialog, type the title `Displacement across Repairs within Origin`, and click on the **Submit** button again.

The Graph window comes up, showing us our nicely titled graph:



## Graph window

When the Graph window comes up, it shows our graph in a window with a toolbar. The first four buttons are familiar to us from other Stata windows: **Open**, **Save**, **Print**, and **Copy**. The next two buttons are new:



**Rename:** This button allows the graph to be renamed. Why would you do this? If you would like to have multiple graphs open at once, the graphs need to be named. So you can click on the **Rename** button to give a graph a name. This graph will then remain open when you create your next graph.



**Graph Editor:** Stata has a Graph Editor that allows you to manipulate and edit your graph. This feature will be introduced in the next chapter.

We decide that we like this graph and would like to save it. We can save it either by clicking on the **Save** button and choosing a name and a location or by right-clicking on the Graph window itself and selecting **Save as...**

## Saving and printing graphs


You can save a graph once it is displayed by right-clicking on its window and selecting **Save as...** You can print a graph by right-clicking on its window and selecting **Print...** You can also use the **File** menu to save or print a graph.

## Right-clicking on the Graph window

Right-clicking on the Graph window displays a menu from which you can select the following:

- **Save as...** to save the graph to disk.
- **Copy** to copy the graph to the Clipboard.
- **Start Graph Editor** to start the Graph Editor.
- **Preferences...** to edit the preferences for graphs.
- **Print...** to print the graph.

## The Graph button

The **Graph** button, , is located on the main toolbar. Clicking on the button brings the topmost Graph window to the front of all other windows. Hold down the button to select a Graph window to bring it to the front of all other windows. If you close the Graph window, you can reopen it only by reissuing a Stata command that draws a new graph.

# 15 Editing graphs


## The Graph Editor


With Stata's Graph Editor, you can change almost anything on your graph; you can add text, lines, arrows, and markers wherever you like.

We will first make a graph to edit and will then point out the tools in the Graph Editor. Start by opening the auto dataset: `sysuse auto`. Here is the command that we will use to make the graph:




```
. scatter mpg weight, name(mygraph) title(Mileage vs. Vehicle Weight)
```


Start the Editor by right-clicking on your graph and selecting **Start Graph Editor**. Click once on the title of the graph. Here is a picture of the Graph Editor with its elements labeled.




Select any of the tools along the bottom left of the Graph Editor window to edit the graph. The Pointer (Select tool), , is selected by default.

You can change the properties of objects or drag them to new locations by using the Pointer. As you select objects with the Pointer, a Contextual Toolbar will appear just above the graph. In the above example, the title of the graph is selected, so the Contextual Toolbar has controls that are relevant for editing titles. You can use any of the controls on the Contextual Toolbar to immediately change the most important properties of the selected object. Right-click on an object to access more properties and operations. Hold the *Shift* key when dragging objects to constrain the movement to horizontal or vertical directions.




Add text, lines, or markers (with optional labels) to your graph by using the three *Add...* tools—, , and . Lines can be changed to arrows by using the Contextual Toolbar. If you do not like the default properties, simply change their settings in the Contextual Toolbar before adding the text, line, or marker. The new settings will then be applied to all added objects, even in future Stata sessions.

Do not be afraid to try things. If you do not like a result, change it back by using the same tool or by clicking on the **Undo** button, , in the Graph Editor toolbar that runs along the bottom of the window. **Edit > Undo** in the main menu does the same thing.

Remember to reselect the Pointer tool when you want to drag objects or change their properties.

You can move objects on the graph and have the rest of the objects adjust their position to accommodate the move with the Grid edit tool, . With this tool, you are repositioning objects in the underlying grid that holds the objects in the graph. Some graphs, for example, by graphs, are composed of nested grids. You can reposition objects only within the grid that contains them; they cannot be moved to other grids.

You can also select objects in the Object Browser along the right of the graph. This window shows a hierarchical listing of the objects in the graph. Clicking or right-clicking on an object in the Object Browser is the same as clicking or right-clicking on the object in the graph.

The Graph Editor has the ability to record your actions and play them back on later graphs. When you click on the **Start recording** button, , every editing action you take, including undos and redos, is recorded. If you would like to do some editing that is not recorded, you can click on the **Pause recording** button, . You can click on the **Pause recording** button again to resume recording. When you are done with your recording, click on the **Start recording** button. You will be prompted to save your recording. Any recording you save is available from the **Play recording** button, , and may be applied to future graphs. You can even play a recording in any Stata `graph` command by using the `play` option. See [Graph Recorder](#) in [G-1] **Graph Editor** for more information.

Stop the editor by selecting **File > Stop Graph Editor** from the main menu or by clicking on the **Graph Editor** button. When you stop the Graph Editor, you will be prompted to save your graph if you have made any changes. If you do not save your graph, your changes will not be lost, but you will risk losing them if you create a new graph in the same Graph window. You must stop the Editor if you would like to work on other tasks in Stata.

Here are a few of the things that you can do with the Editor:

- Add annotations using lines, arrows, and text.
- Add or remove grid lines or reference lines.
- Add or modify titles, captions, and notes.
- Change scatterplots to line plots, connected plots, areas, bars, spikes, or drop lines—and, of course, vice versa.
- Change the size, color, margin, and other properties of your graph's titles (or any other text on the graph).

- Move your legend to another side of the graph, or even place it in the plot region.
- Change the aspect ratio of your graph.
- Stack the bars on a bar graph or turn them into percentages.
- Rotate or change the angle of axis labels.
- Add custom ticks and labels to the axes.
- Change the rule for the number and spacing of ticks and labels on an axis.
- Emphasize a point on the graph, whether marker, bar, spike, or other plot, by making it a custom color, size, or symbol.
- Change the text or properties of a marker label.

Because you can edit every property of every object on the graph, you can change almost anything about your graph. To learn more, see [G-1] **Graph Editor** or type `help graph editor`.

# 16 Saving and printing results by using logs


## Using logs in Stata

When you work on an analysis, it is worthwhile to behave like a bench scientist and keep a lab notebook of your actions so that your work can be easily replicated. Everyone has a feeling of complete omniscience while working intensely—this feeling is wonderful but fleeting. The next day, the exact small details needed for perfect duplication have become obscure. Stata has a lab notebook at hand: the *log* file.

A log file is simply a record of your Results window. It records all commands and all textual output as it happens. Thus it keeps your lab notebook for you as you work. Because it writes the file to disk while it writes the Results window, it also protects you from disastrous failures, be they power failures or computer crashes. We recommend that you start a log file whenever you begin any serious work in Stata.

## Logging output

All the output that appears in the Results window can be captured in a log file. Stata can save the file in one of two different formats. By default, Stata will save the file in its Stata Markup and Control Language (SMCL) format, which preserves all the formatting and links from the Results window. You can open these results in the Viewer, and they will behave as though they were in the Results window. If you would rather have plain-text files without any formatting, you can save the file as a plain log file. We recommend using the SMCL format because SMCL files can be translated into a variety of formats readable by applications other than Stata with the **File > Log > Translate...** menu (see [R] [translate](#)).

To start a log file, click on the **Log** button, . Choose **Begin...** from the drop-down menu to start a new log file. Choose **Append...** if you want to add more Stata output to an existing log file. Both choices open a standard file dialog that allows you to specify a directory and filename for your log. If you do not specify a file extension, the extension `.smcl` will be added to the filename.



Here is an example of a short session:

```

name: <unnamed>
log: /Users/stata/Documents/Stata/base.smcl
log type: smcl
opened on: 4 Feb 2019, 23:36:17
. sysuse auto
(1978 Automobile Data)
. by foreign, sort: summarize price mpg

```

---

```

-> foreign = Domestic

```

Variable	Obs	Mean	Std. Dev.	Min	Max
price	52	6072.423	3097.104	3291	15906
mpg	52	19.82692	4.743297	12	34

---

```

-> foreign = Foreign

```

Variable	Obs	Mean	Std. Dev.	Min	Max
price	22	6384.682	2621.915	3748	12990
mpg	22	24.77273	6.611187	14	41

```

. * be sure to include the above stats in report!
. * now for something completely different
. corr price mpg
(obs=74)

```

	price	mpg
price	1.0000	
mpg	-0.4686	1.0000

```

. log close
name: <unnamed>
log: /Users/stata/Documents/Stata/base.smcl
log type: smcl
closed on: 4 Feb 2019, 23:37:41

```

There are a few items of interest.

- The header showing the log file's location, type, and starting timestamp is part of the log file. This feature helps when working with multiple log files.
- The two lines starting with asterisks (\*) are comments. Stata ignores the text following the asterisk, so you may type any comment you would like, with any special characters you would like. Commenting is a good way to document your thought process and to mark sections of the log for later use.
- In this example, the log file was closed by using the `log close` command. Doing so is not strictly necessary because log files are automatically closed when you quit Stata.

Stata allows multiple log files to be open at once only if the log files are named. For details on this topic, see `help log`.

## Working with logs

Log files are best viewed using Stata's Viewer. There are two ways to open a Viewer window:

- Click on the **Log** button, and select **View...**
- Select **File > Log > View...**

If there is a log file open (as shown by the status bar), it will be the default log file to view; otherwise, you need to either type the name of the log file into the dialog or click on the **Browse...** button to find the file with a standard file dialog.

Once you are in the Viewer window, everything behaves as expected: you can copy text and paste between the Viewer and anything else that uses text, such as word processors or text editors. You can even paste into the Command window or the Do-file Editor, but you should take care to copy only commands, not their output. It is okay to copy the prompt (“.”) at the start of the echoed command because Stata is smart enough to ignore it in the Command window. When working with a word processor, what you paste will be unformatted text; it will look best if you use a fixed-width font, like Monaco, to display it.

Viewing your current log file is a good way to keep a reminder of something you have already done or a view of a previous result. The Viewer window takes a snapshot of your log file and hence will not scroll as you keep working in Stata. If you need to see more recent results in the Viewer, click on the **Reload** button.

For more detailed information about logs, see [U] 15 Saving and printing output—log files and [R] log. For more information about the Viewer, see [GSM] 3 Using the Viewer.

## Printing logs

To print a standard SMCL log file, you need to have the log file open in a Viewer window. Once the log file is in the Viewer, you can click on the **Print** button, right-click on the Viewer window, and select **Print...**, or select **File > Print**. If you do not see the details in the *Print* dialog, click the **Show Details** button.

- You can fill in none of, any of, or all the items *Header*, *User*, and *Project*. You can check or uncheck options to *Print header and footer*, *Print line numbers*, and *Print logo*. These items are saved and will appear again in the print sheet (in this and in future Stata sessions).
- You can set the font size and color scheme the printer will use by clicking on the **Stata Headers and Footers** drop-down menu and choosing **Stata Fonts and Colors**. *Monochrome* is for black-and-white printing, *Color* is for default color printing, and *Custom 1* and *Custom 2* are for customized color printing.

You could also use the `translate` command to generate a PostScript or PDF version of the log file. See [R] `translate` for more information.

If your log file is a plain-text file (`.log` instead of `.smcl`), you can open it in a text editor, such as TextEdit, in the Do-file Editor or in your favorite word processor. You can then edit the log file—add headings, comments, etc.—format it, and print it. If you bring the log file into a word processor, it will be displayed and printed with its default font. The log file will not be easily readable when printed in a proportionally spaced font (for example, Times or Helvetica). It will look much better printed in a fixed-width font (for example, Monaco or Courier New).

## Rerunning commands as do-files

Stata also can log just the commands from a session without recording the output. This feature is a convenient way to make a do-file interactively. Such a file is called a *cmdlog* file by Stata. You can start a *cmdlog* file by typing

```
cmdlog using filename.do
```

and you can close the *cmdlog* file by typing

```
cmdlog close
```

Here, for example, is what a *cmdlog* of the previous session would look like. It contains only commands and comments and hence could be used as a do-file.

```
sysuse auto
by foreign, sort: summarize price mpg
* be sure to include the above stats in report!
* now for something completely different
corr price mpg
```

If you start working and then wish you had started a *cmdlog* file, you can save yourself heartache by saving the contents of the History window. The History window stores the last 5,000 commands you have typed. Simply right-click on the History window and select **Save all...** from the menu. This will work best if you first filter out all the commands that resulted in errors as was shown in [The History window](#) in [\[GSM\] 2 The Stata user interface](#). If you would like to move the commands directly to the Do-file Editor, select **Select all** followed by **Send selected to Do-file Editor**. You may find this method a more convenient way to create a text file containing only the commands that you typed during your session.

See [\[GSM\] 13 Using the Do-file Editor—automating Stata](#), [\[U\] 16 Do-files](#), and [\[U\] 15 Saving and printing output—log files](#) for more information.

# 17 Setting font and window preferences

## Changing and saving fonts and sizes and positions of your windows

You may find that you would like to change the fonts and display style of Stata's windows, depending on your monitor resolution and personal preferences. At the same time, there could be requirements for font usage, say, when you submit graphs to journals. Stata accommodates both of these by allowing sets of preferences for how windows are displayed.

We will first cover what can be changed in each window and then talk about what you can manage with your preferences.

### Graph window

The preferences for the Graph window can be changed by right-clicking on the Graph window and choosing **Preferences...** from the contextual menu. The settings can then be set for how graphs are displayed in Stata. The settings that should be used when printing can be set under the **Graph** tab. The behavior of the Clipboard is controlled under the **Clipboard** tab.

The Graph preferences allow different schemes that control the look of graphs. These schemes provide a quick way to optimize graphs for printing or to display on a screen. There are even schemes defined for *The Economist* and the *Stata Journal* so that you can get the details for these publications right without much fuss. Changing the scheme does not change the current graph—it applies the settings to future graphs.

### All other windows

You can change the display font and font size for most types of windows in Stata.

If fonts and font sizes for a window can be changed, they can be changed by right-clicking on the window and selecting **Preferences...** from the contextual menu. Doing so will bring up the *Windows Preferences* dialog, from which you can pick the font and size of your choice. The font lists for each of the Results, Viewer, Data Editor, and Do-file Editor windows are restricted to fixed-width fonts only. This restriction ensures that output and numbers line up properly and are readable. The other windows can have any font that you would like without any adverse consequences.

### Changing color schemes

In addition to changing the fonts themselves, you can also change the background and foreground colors of text being displayed. You can choose the colors for syntax highlighting, allowing, say, Stata commands to be displayed in a different color from arbitrary text. This syntax highlighting will be applied in both the Do-file Editor and the Command window. Dark mode is supported in macOS 10.14 (Mojave).

The Results and Viewer windows have color schemes that control the display of input, text, results, errors, links, and highlighted text. Each has its color scheme set in the same fashion: you can right-click on the window and select or design your own color scheme. The default setting for both the Results window and the Viewer is the built-in *Standard* scheme, which uses a white background and dark text. There are other built-in schemes as well as slots for custom schemes. The settings for the Viewer affect all Viewer windows at once.

## Managing multiple sets of preferences

Stata's preferences are automatically saved when you quit Stata, and they are reloaded when Stata is launched. However, sometimes you may wish to rearrange Stata's windows and then revert to your preferred arrangement of windows. You can do this by saving your preferences to a named preference set and loading them later. Any changes you make to Stata's preferences after loading a preferences set do not affect the set; the set remains untouched unless you specifically overwrite it.

To manage preferences, open the **Stata > Preferences > Manage preferences** menu, and do any of the following:

- Select **Manage preferences...** to open the *Saved preferences* window from which you can open, replace, or delete an existing preference set.
- Select **Save preferences...** to save the current window arrangement and preferences. If you save your preferences, they will appear in the **Stata > Preferences > Manage preferences** menu the next time you view it.
- Select **Factory settings** to restore all preferences to their original settings.
- Select **Factory window settings** to restore only the windowing preferences to their original settings.

## Closing and opening windows

You can close all windows but the Results and Command windows. If you want to open a closed window, open the **Window** menu and select the desired window.

# 18 Learning more about Stata

## Where to go from here

You now know plenty enough to use Stata. There is still much, much more to learn, because Stata is a rich environment for doing statistical analysis and data management. What should you do to learn more?

- Get an interesting dataset and play with Stata.
  - a. Use the menus and dialog system to experiment with commands. Notice what commands show up in the Results window. You will find that Stata's simple and consistent command syntax will make the commands easy to read so that you will know what you have done and easy to remember so that typing some commands will be faster than using menus.
  - b. Play with graphs and the Graph Editor.
- If you venture into the Command window, you will find that many things will go faster. You will also find that it is possible to make mistakes where you cannot understand why Stata is balking.
  - a. Try `help commandname` or **Help > Stata command...** and entering the command name.
  - b. Look at the command syntax and the examples in the help file, and compare them with what you typed. Compare them closely: small typographical errors make commands impossible for Stata to parse.
- Explore Stata by selecting **Help > Search...** You will uncover many statistical routines that could be of great use.
- Look through the *Combined subject table of contents* in the *Glossary and Index*.
- Read and work your way through the *User's Guide*. It is designed to be read from cover to cover, and it contains most of the information you need to become an expert Stata user. It is well worth reading. If you are not this ambitious and instead prefer to sample the *User's Guide* and the references, there is some advice later in this chapter for you.
- Browse through the reference manuals to read about statistical methods you like to use, making use of the links to jump to other topics. The reference manuals are not meant to be read from cover to cover—they are meant to be referred to as you would an encyclopedia. You can find the datasets used in the examples in the manuals by selecting **File > Example datasets...** and then clicking on `Stata 16 manual datasets`. Doing so will enable you to work through the examples quickly.
- Stata has much information, including answers to frequently asked questions (FAQs), at <https://www.stata.com/support/faqs/>.
- There are many useful links to Stata resources at <https://www.stata.com/links/>. Be sure to look at these materials because many outstanding resources about Stata are listed here.
- Join *Statalist*, a forum devoted to discussion of Stata and statistics.
- Read *The Stata Blog: Not Elsewhere Classified* at <https://blog.stata.com> to read articles written by people at Stata about all things Stata.
- Visit Stata on Facebook at <https://facebook.com/statacorp>, join Stata on Instagram at <https://www.instagram.com/statacorp>, find Stata on LinkedIn at <https://www.linkedin.com/company/statacorp>, and follow Stata on Twitter at <https://twitter.com/stata> to keep up with Stata.
- Subscribe to the *Stata Journal*, which contains reviewed papers, regular columns, book reviews, and other material of interest to researchers applying statistics in a variety of disciplines. Visit <https://www.stata-journal.com>.

- Many supplementary books about Stata are available. Visit the Stata Bookstore at <https://www.stata.com/bookstore/>.
- Take a Stata NetCourse<sup>®</sup>. NetCourse 101 is an excellent choice for learning about Stata. See <https://www.stata.com/netcourse/> for course information and schedules.
- Attend a classroom or a web-based training course taught by StataCorp. Visit <https://www.stata.com/training/classroom-and-web/> for course information and schedules.
- View a webinar led by Stata developers. Visit <https://www.stata.com/training/webinar/> for the current list of topics and schedule.
- Watch Stata videos at <https://www.youtube.com/user/statacorp>.

## Suggested reading from the User's Guide and reference manuals

The *User's Guide* is designed to be read from cover to cover. The reference manuals are designed as references to be sampled when necessary.

Ideally, after reading this *Getting Started* manual, you should read the *User's Guide* from cover to cover, but you probably want to become at least somewhat proficient in Stata right away. Here is a suggested reading list of sections from the *User's Guide* and the reference manuals to help you on your way to becoming a Stata expert.

This list covers fundamental features and points you to some less obvious features that you might otherwise overlook.

### Basic elements of Stata

[U] [11 Language syntax](#)

[U] [12 Data](#)

[U] [13 Functions and expressions](#)

### Data management

[U] [6 Managing memory](#)

[U] [22 Entering and importing data](#)

[D] [import](#) — Overview of importing data into Stata

[D] [append](#) — Append datasets

[D] [merge](#) — Merge datasets

[D] [compress](#) — Compress data in memory

[D] [frames intro](#) — Introduction to frames

### Graphics

[G] [Stata Graphics Reference Manual](#)

### Reproducible research

[U] [16 Do-files](#)

[U] [17 Ado-files](#)

[U] [13.5 Accessing coefficients and standard errors](#)

[U] [13.6 Accessing results from Stata commands](#)

[U] [21 Creating reports](#)

[RPT] [Dynamic documents intro](#) — Introduction to dynamic documents

[RPT] [putdocx intro](#) — Introduction to generating Office Open XML (.docx) files

[RPT] [putexcel](#) — Export results to an Excel file

[RPT] [putpdf intro](#) — Introduction to generating PDF files

[R] [log](#) — Echo copy of session to file

**Useful features that you might overlook**

- [U] [29 Using the Internet to keep up to date](#)
- [U] [19 Immediate commands](#)
- [U] [24 Working with strings](#)
- [U] [25 Working with dates and times](#)
- [U] [26 Working with categorical data and factor variables](#)
- [U] [27 Overview of Stata estimation commands](#)
- [U] [20 Estimation and postestimation commands](#)
- [R] [estimates](#) — Save and manipulate estimation results

**Basic statistics**

- [R] [anova](#) — Analysis of variance and covariance
- [R] [ci](#) — Confidence intervals for means, proportions, and variances
- [R] [correlate](#) — Correlations of variables
- [D] [egen](#) — Extensions to generate
- [R] [regress](#) — Linear regression
- [R] [predict](#) — Obtain predictions, residuals, etc., after estimation
- [R] [regress postestimation](#) — Postestimation tools for regress
- [R] [test](#) — Test linear hypotheses after estimation
- [R] [summarize](#) — Summary statistics
- [R] [table](#) — Flexible table of summary statistics
- [R] [tabulate oneway](#) — One-way table of frequencies
- [R] [tabulate twoway](#) — Two-way table of frequencies
- [R] [ttest](#) —  $t$  tests (mean-comparison tests)

**Matrices**

- [U] [14 Matrix expressions](#)
- [U] [18.5 Scalars and matrices](#)
- [M] *Mata Reference Manual*

**Programming**

- [U] [16 Do-files](#)
- [U] [17 Ado-files](#)
- [U] [18 Programming Stata](#)
- [R] [ml](#) — Maximum likelihood estimation
- [P] *Stata Programming Reference Manual*
- [M] *Mata Reference Manual*

**System values**

- [R] [set](#) — Overview of system parameters
- [P] [creturn](#) — Return c-class values



## Internet resources

The Stata website (<https://www.stata.com>) is a good place to get more information about Stata. You will find answers to FAQs, ways to interact with other users, official Stata updates, and other useful information. You can also join Statalist, a forum devoted to discussion of Stata and statistics.

You will also find information on Stata NetCourses<sup>®</sup>, which are interactive courses offered over the Internet that vary in length from a few weeks to eight weeks. Stata also offers in-person and web-based training sessions, as well as webinars on Stata features. Visit <https://www.stata.com/learn/> for more information.

At the website is the Stata Bookstore, which contains books that we feel may be of interest to Stata users. Each book has a brief description written by a member of our technical staff explaining why we think this book may be of interest.

We suggest that you take a quick look at the Stata website now. You can [register](#) your copy of Stata online and request a free [subscription](#) to the *Stata News*.

Visit <https://www.stata-press.com> for information on books, manuals, and journals published by Stata Press. The datasets used in examples in the Stata manuals are available from the Stata Press website.

Also visit <https://www.stata-journal.com> to read about the *Stata Journal*, a quarterly publication containing articles about statistics, data analysis, teaching methods, and effective use of Stata's language.

Visit Stata's official blog at <https://blog.stata.com> for news and advice related to the use of Stata. The articles appearing in the blog are individually signed and are written by the same people who develop, support, and sell Stata. *The Stata Blog: Not Elsewhere Classified* also has links to other blogs about Stata, written by Stata users around the world.

Follow Stata on Facebook at <https://facebook.com/statacorp>, Twitter at <https://twitter.com/stata>, Instagram at <https://www.instagram.com/statacorp>, and LinkedIn at <https://www.linkedin.com/company/statacorp>. You may also follow Stata on Twitter at [https://twitter.com/stata\\_fr](https://twitter.com/stata_fr) or [https://twitter.com/stata\\_es](https://twitter.com/stata_es). These are good ways to stay up-to-the-minute with the latest Stata information. Watch short example videos of using Stata on YouTube at <https://www.youtube.com/user/statacorp>.

See [\[GSM\] 19 Updating and extending Stata—Internet functionality](#) for details on accessing official Stata updates and free additions to Stata on the Stata website.

# 19 Updating and extending Stata—Internet functionality

## Internet functionality in Stata

Stata works well with the Internet. Stata can use datasets and view remote help files as though they were on your computer. Stata also can keep itself up to date (with your permission, of course). Finally, you can install *community-contributed commands*, which are commands that extend Stata's functionality. These are commands that have been presented in the *Stata Journal* (SJ) or the *Stata Technical Bulletin* (STB) or have simply been written and shared by the greater Stata community.

This chapter will show you how you can expand Stata's horizons.

## Using files from the Internet

Stata understands URLs as though they were local file locations. If you know of a file on the web that you would like to use, be it a dataset, a graph, or a do-file, you can easily open it in Stata. Here is a small example.

There are many datasets at <https://www.stata-press.com/data/>. Suppose that you would like to use the `census12` dataset used in [U] 11 [Language syntax](#) and that you know that its location is `https://www.stata-press.com/data/r16/census12.dta`. Because you know that the command for opening a dataset is `use`, you could type the following:

```
. use https://www.stata-press.com/data/r16/census12.dta
(1980 Census data by state)
. describe
Contains data from https://www.stata-press.com/data/r16/census12.dta
  obs:           50           1980 Census data by state
  vars:           7           6 Apr 2018 15:43
```

---

variable name	storage type	display format	value label	variable label
<code>state</code>	str14	%14s		<b>State</b>
<code>state2</code>	str2	%-2s		<b>Two-letter state abbreviation</b>
<code>region</code>	str7	%9s		<b>Census region</b>
<code>pop</code>	long	%10.0g		<b>Population</b>
<code>median_age</code>	float	%9.2f		<b>Median age</b>
<code>marriage_rate</code>	float	%9.0g		
<code>divorce_rate</code>	float	%9.0g		

---

```
Sorted by:
```

This functionality is everywhere in Stata. Any command that reads a file with a *filename* in its syntax can use a web address as easily as a file that is stored on your computer.

This example used the HTTP protocol for retrieving the file. Stata also understands the HTTPS and FTP protocols.

## Official Stata updates

By official Stata, we mean the pieces of Stata that are provided and supported by StataCorp. The other and equally important pieces are the community-contributed additions published in the SJ, distributed over Statalist, or distributed in other ways.

Stata can fetch both official updates and community-contributed commands from the Internet. Let's start with the official updates. StataCorp often releases updates to official Stata. These updates add new features and, sometimes, fix bugs.

By default, Stata has automatic update checking turned on and set to check for updates every seven days. To change or check your settings, select **Stata > Preferences > General preferences...** and click on the **General** tab.

We recommend using automatic update checking because it is a simple, unobtrusive way to be sure that your copy of Stata is always up to date. If you keep this default, you will be prompted with a dialog when you start Stata if you have not recently checked for updates.

To manually check whether there are any official Stata updates, either click on **Help > Check for updates** or type `update query` in the Command window. Regardless of which choice you make, Stata goes to check for official updates. After it checks, it will show you your update status. If your copy of Stata is already up to date, you will be told. If your copy of Stata needs updating, you will be told, and a link, `Install available updates`, will show up in your Results window. You can click on this link or type `update all` and press *Return*. In either case, Stata will download what is needed to bring your copy of Stata up to date. Stata will need to restart after being updated, so it gives you a chance to postpone the update in case there was something (such as saving the command history) you wanted to do in the current session.

Troubleshooting note: If you do not have write permission for `/Applications/Stata`, you cannot install official updates in this way. You may still download the official updates, but you will need to use the command-line version of `update`; see [U] 29 [Using the Internet to keep up to date](#) for instructions.

## Automatic update checking

Stata can periodically check for updates for you. By default, Stata will check once every seven days for updates from the StataCorp website. The seven-day interval is from the last time an `update query` was performed, regardless of whether it was by Stata or by you. You can change the interval between checks.

Before Stata connects to the Internet to check for an update, it will ask you if you would like to check now, check the next time Stata is launched, or check after the next interval. You can disable the prompt and allow Stata to check without asking.

If an update is available, Stata will notify you. From there, you should follow the recommendations for updating Stata.

You can change the settings for automatic update checking by selecting **Stata > Preferences > General preferences...** and choosing **General**.


## Finding community-contributed commands by keyword

Stata has a built-in utility created specifically to search the Internet for community-contributed Stata commands. You can access it by selecting **Help > Search...**, choosing *Search net resources*, and entering a keyword in the field. Choosing **Help > SJ and community-contributed commands** yields more specific choices for searching. The utility searches all community-contributed commands on the Internet, including the entire collection of SJ and STB commands. The results are displayed in the Viewer, and you can click to go to any of the matches found.

For the syntax on how to use the equivalent `search keywords, net` command, see [R] [search](#).

## Downloading community-contributed commands

Downloading community-contributed commands is easy. Start by selecting **Help > SJ and community-contributed commands**:



As the Viewer says, try `Search...` first.

Suppose that you were interested in finding more information or some community-contributed commands involving cubic splines. You select **Help > Search...**, select *Search all*, type `cubic spline` in the search box, and press *Return*.

The screenshot shows a Stata search window titled "Viewer — search cubic spline". The search bar contains "search cubic spline". Below the search bar, there are navigation buttons: "Back/Forward", "Find", "Reload", "Command", and "Search". The search results are displayed in a list format, starting with "search for cubic spline" and "(manual: [R] search)". The results are categorized under "Search of official help files, FAQs, Examples, and Stata Journals".

```

search for cubic spline (manual: [R] search)

Search of official help files, FAQs, Examples, and Stata Journals

[R]      mkspline . . . . . Linear and restricted cubic spline construction
        (help mkspline)

[M-4]   Mathematical . . . . . Important mathematical functions
        (help \[M-4\] mathematical)

[M-5]   spline3() . . . . . Cubic spline interpolation
        (help \[M-5\] spline3\(\))

FAQ     . . . . . NJC Stata plots
        . . . . . UCLA Academic Technology Services
        7/08 https://stats.idre.ucla.edu/stata/faq/graph/njc-stata-plots/

SJ-17-4 st0245\_1 . . . . . Software update for apcspline
        . . . . . P. D. Sasieni
        (help apcspline, apcspline postestimation, grmean if installed)
        Q4/17 SJ 17\(4\):1024
        software updates for apcspline

SJ-15-4 gr0021\_2 . . . . . Software update for doublesm, diagsm, and polarsm
        (help doublesm, diagsm, polarsm if installed) . . . . . N. J. Cox
        Q4/15 SJ 15\(4\):1186--1187
        added kernel-weighted local polynomial smoothing for doublesm
        and diagsm and an option added to allow specification of an
        alternative regression command to use in polar smoothing for
        polarsm

SJ-12-4 st0165\_1 . Fitting & modeling cure with flex. param. survival models
        . . . . . T. M.-L. Andersson and P. C. Lambert
        (help stpm2, stpm2\_postestimation if installed)
        Q4/12 SJ 12\(4\):623--638
        updated for flexible parametric models that enable cure
        modeling
  
```

The first entry points to the built-in Stata command `mkspline`. You investigate this command and find it interesting. You see that the next two entries point to some built-in routines in Mata. You follow these links because Mata is not only intriguing but also fast. You see that the next link points to an FAQ on UCLA's website. The next three links point to articles in the SJ. Finally, you decide to check the second of these links. It points to an article in the SJ, volume 15, number 4 (fourth quarter, 2015). You should click on the `gr0021_2` link, because it will go to the commands associated with this article.

package **gr0021\_2** from <http://www.stata-journal.com/software/sj15-4>

---

**TITLE**  
SJ15-4 gr0021\_2. Update: Double, diagonal,...

**DESCRIPTION/AUTHOR(S)**  
Update: Double, diagonal, and polar smoothing  
by Nicholas J. Cox, Durham University, UK  
Support: [n.j.cox@durham.ac.uk](mailto:n.j.cox@durham.ac.uk)  
After installation, type help **diagsm**,  
**doublesm**, and **polar**

**INSTALLATION FILES** [\(click here to install\)](#)  
[gr0021\\_2/diagsm.ado](#)  
[gr0021\\_2/diagsm.hlp](#)  
[gr0021\\_2/doublesm.ado](#)  
[gr0021\\_2/doublesm.hlp](#)  
[gr0021\\_2/polarsm.ado](#)  
[gr0021\\_2/polarsm.hlp](#)  
[gr0021\\_2/mylabels.ado](#)

**ANCILLARY FILES** [\(click here to get\)](#)  
[gr0021\\_2/cumcir.dta](#)  
[gr0021\\_2/law.dta](#)  
[gr0021\\_2/speak\\_16.do](#)

---

[\(click here to return to the previous screen\)](#)


You will see that the package has three help files for three new commands. Click the [gr0021\\_2/polarsm.hlp](#) link to see if the **polarsm** command looks interesting. If you decide that you would like to install the command, click the **Back** button and click on the link [click here to install](#). If you decide that you would like to use some of the ancillary files—files that typically help explain the workings of the command, you could download those, too. You do not need to worry—doing so will not interfere in any way with your copy of Stata. We will show you how to safely uninstall these commands shortly.

You can keep the community-contributed commands you have installed up to date by using the `ado update` command. Typing `ado update` will check for updates, while typing `ado update, update` will check for updates and install any available updates.

Now suppose that you decide that you would like to uninstall the package. Doing so is simple enough: select **Help > SJ and community-contributed commands**, and click on the `List` link. You should see the following:



If you click on the one-line description of the package, you will see the full description of what has been installed. Here is what you would see if you scroll to the bottom, with a different install date, of course:



You can uninstall materials by clicking on [click here to uninstall](#) when you are looking at the package description.

For information on downloading community-contributed commands by using the `net` command, see [\[R\] net](#).



# A Troubleshooting Stata

## Contents

A.1	<a href="#">If Stata does not start</a>	124
A.2	<a href="#">Troubleshooting tips</a>	125

## A.1 If Stata does not start

You tried to start Stata and it refused; Stata or your operating system presented a message explaining that something is wrong. Here are the possibilities:

### Cannot find license file

This message means just what it says; nothing is too seriously wrong. Stata simply could not find the license file it was looking for. The most common reason for this is that you did not complete the installation process.

Did you enter the codes on your license to unlock Stata? If not, go back and complete the initialization procedure.

### Error opening or reading the file

Something is distinctly wrong for purely technical reasons. Stata found the file that it was looking for, but there was an I/O error.

About the only way this situation could arise would be a hard-disk error. Stata technical support will be able to help you diagnose the problem; see [\[U\] 3.8 Technical support](#).

### License not applicable

Stata has determined that you have a valid Stata license, but the license does not apply to the version of Stata that you are trying to run.

The most common reason for this message is that you have a license for Stata/IC but you are trying to run Stata/SE or Stata/MP, or you have a license for Stata/SE but you are trying to run Stata/MP. If any of these is the case, reinstall Stata, making sure to choose the appropriate flavor.

### Other messages

The other messages indicate that Stata thinks you are attempting to do something that you are not licensed to do. Most commonly, you are attempting to run Stata over a network when you do not have a network license, but there are many other alternatives. There are two possibilities: either you really are attempting to do something that you are not licensed to do or Stata is wrong. In either case, you are going to have to contact us. Your license can be upgraded, or if Stata is wrong, we can provide codes to make Stata stop thinking that you are violating the license; see [\[U\] 3.8 Technical support](#). You also could be trying to run Stata on OS X 10.8 or earlier. The minimum requirement for Stata is OS X 10.9.

## A.2 Troubleshooting tips

Stata has a minimum requirement of a Mac computer running macOS 10.11 (El Capitan) or better.

If you experience a crash while launching Stata, open the **Preferences** folder in your home directory's **Library** folder. Trash the file `com.stata.stata16.plist`, and restart Stata. It is an uncommon event, but the preference file can become corrupted by previous crashes caused by power outages or by not shutting down your computer properly.

Also see the frequently asked questions (FAQs) for Mac on the Stata website at <https://www.stata.com/support/faqs/mac>. The solution to your problem may be there.

If you want us to help, we will need as much information as possible. Restart Stata and reproduce the problem, writing down everything you do before the problem occurs.

Also tell us about your computer. What model Mac is it? What version of the system software are you using? Click on **Apple Menu > About This Mac**, and then click on the **System Report...** button to open the System Information application. You can generate a profile of your system that you can email to us. Finally, we need your Stata serial number and the revision date of your version of Stata. Include them if you email, and know them if you call. You can obtain them by typing the `about` command in Stata's Command window. `about` lets you know everything about your copy of Stata, including the version and the date it was produced.

# B Advanced Stata usage

## Contents

B.1	Executing commands every time Stata is started	126
B.2	Other ways to launch Stata	127
B.3	Stata batch mode	127
B.4	Changing Stata's locale	129
B.5	More	130
B.6	Memory size considerations	130

## B.1 Executing commands every time Stata is started

Stata looks for the file `profile.do` when it is invoked and, if it finds it, executes the commands in it. Stata looks for `profile.do` first in the directory where Stata is installed, then in the current directory, then along your path, and finally along the `ado-path` (see [P] [sysdir](#)). We recommend that you put `profile.do` in `~/Documents/Stata`.

Say that every time you start Stata, you would like to start a dated log for the session. In `~/Documents/Stata`, create the file `profile.do` containing this rather odd-looking command:

```
log using `: display %tCCYY-NN-DD-HH-MM-SS ///
Clock("c(current_date)' 'c(current_time)'" ,"DMYhms)", ///
name(default_log_file)
```

When you invoke Stata, the usual opening appears but with the following additional command, which will be executed:

```
running ~/Documents/Stata/profile.do ...
```

How does the command work? Let's work from the inside out:

- `c(current_date)` and `c(current_time)` are local system macros containing the current date and current time. See [P] [creturn](#) for more information.
- The left (‘) and right (’) quotes around the local macros expand them. See [P] [macro](#) for a full explanation.
- The `Clock()` function uses the resulting date string and the date mask "DMYhms" to create a datetime number Stata understands. See [D] [Datetime](#).
- The format `%tCCYY-NN-DD-HH-MM-SS` formats this number in year-month-day-hour-minute-second form because this will make the files sort nicely. See [D] [Datetime display formats](#) for the details.
- The odd-looking ‘`: display ...`’ allows the formatted date to be used directly in the command as the file name. This is the advanced concept of an in-line expansion of a macro function. You can see more in [P] [macro](#).
- The `log using` command starts a log file, such as shown in [GSM] [16 Saving and printing results by using logs](#).
- The `name` option gives the log file the internal name `default_log_file` so that it will not likely conflict with other log files. See [R] [log](#) for details.
- Finally, the `///` notations are continuation comments so that the three separate lines are interpreted as a single command. See [P] [comments](#) for more about comments.

There are many advanced Stata programming concepts in this one single command!

`profile.do` is treated just as any other do-file once it is executed; results are just the same as if you had started Stata and then typed `run profile.do`. The only special thing about `profile.do` is that Stata looks for it and runs it automatically.

System administrators might also find `sysprofile.do` useful. This file is handled in the same way as `profile.do`, except that Stata first looks for `sysprofile.do`. If that file is found, Stata will execute any commands it contains. After that, Stata will look for `profile.do` and, if that file is found, execute the commands in it.

One example of how `sysprofile.do` might be useful would be when system administrators want to change the path to one of Stata's system directories. Here `sysprofile.do` could be created to contain the command

```
sysdir set SITE "~/Documents/Stata"
```

See [U] 16 Do-files for an explanation of do-files. They are nothing more than text files containing sequences of commands for Stata to execute.

## B.2 Other ways to launch Stata

You can start Stata by double-clicking on a Stata `.dta` dataset, a Stata `.do` do-file, or a Stata `.gph` graph file. In all cases except for do-files, your current working directory will become the folder containing the file you have double-clicked. Do-files opened for editing do not change your working directory.

Stata will behave as you would expect in each case. If you double-click on a dataset, Stata will open the dataset after Stata starts. If you double-click on a graph, the graph will be opened by Stata. If you double-click on a do-file, the do-file will be opened either in the Do-file Editor, or will execute its commands.

If you would rather have Stata execute the commands in a do-file when it is double-clicked, select **Stata > Preferences > General Preferences...**, click on the **Windows** toolbar button, click on the *Do-file Editor* item, click on the **Advanced** tab, and uncheck the *Edit do-files opened from the Finder in Do-file Editor* checkbox.

## B.3 Stata batch mode

To run Stata in batch mode, you need to start it in the Terminal. The syntax of the command to start Stata from in the Terminal is

```
StataSE [-option [-option [...]]] [stata_command]
```

where the options are

Option	Result
-b	set background (batch) mode and log in plain text
-e	set background (batch) mode and log in plain text without prompting when Stata command has completed
-q	suppress logo and initialization messages
-rngstream#	set random-number generator to mt64s (see [R] <a href="#">set rng</a> ) and set random-number stream to # (see [R] <a href="#">set rngstream</a> )
-s	set background (batch) mode and log in SMCL

For you to run Stata from the Terminal, you need to be sure that the shell can find Stata. To do this, you must add the path to the Stata executable in Stata's application bundle to your shell's path. Once that is done, you can invoke Stata from any directory from a shell.

For example, if Stata is installed in /Applications/Stata, then the path to the executable for Stata/SE is /Applications/Stata/StataSE.app/Contents/MacOS. Type StataSE to start Stata/SE.

For Stata/MP, it is /Applications/Stata/StataMP.app/Contents/MacOS. Type StataMP to start Stata/MP.

For Stata/IC, it is /Applications/Stata/Stata.app/Contents/MacOS. Type Stata to start Stata/IC.

Suppose you had a do-file named bigjob.do. If you want to use Stata in batch mode, typing

```
% StataSE -b do bigjob
```

tells Stata to execute the commands in bigjob.do, suppress all screen output, and route the output to bigjob.log in the same directory. Stata will display a dialog when the commands have finished executing.

Typing

```
% StataSE -e do bigjob
```

tells Stata to execute the commands in bigjob.do, suppress all screen output, and route the output to bigjob.log in the same directory. Stata will simply exit without displaying a dialog when the commands have finished executing.

```
% StataSE -s do bigjob
```

tells Stata to execute the commands in bigjob.do, suppress all screen output, and route the output to bigjob.smcl in the same directory.

Specifying -s -e sets the background (batch) mode and logs in SMCL without prompting when a Stata command has completed.

You can also run the above examples in the background by typing

```
% StataSE -b do bigjob &
% StataSE -e do bigjob &
% StataSE -s do bigjob &
```

Note: Stata runs profile.do before doing bigjob.do, just as it would if you were working interactively.

## General notes

While your do-file is executing, the Stata icon will appear on the dock.

The icon has a badge showing a rough percentage of how much of the do-file Stata has executed. (Stata calculates this percentage from the number of characters in the do-file, so the percentage may not accurately reflect the amount of time left for the job to complete.)

If you right-click on the icon on the taskbar, Stata will display a box asking if you want to cancel the batch job.

Once the do-file is complete, Stata will bounce the icon on the dock. You can then click on the icon to close Stata. If you wish for Stata to automatically exit after running the batch do-file, use `-e` rather than `-b`.

You do not have to run large do-files in batch mode. Any do-file that you run in batch mode can also be run interactively. Simply start Stata, type `log using filename`, and type `do filename`. You can then watch the do-file run, or you can minimize Stata while the do-file is running.

## B.4 Changing Stata's locale

To change the locale of Stata to English, type

```
set locale_ui en
```

To change it back to match the locale set for your operating system, type

```
set locale_ui default
```

For a complete explanation of locales and Stata, see [\[U\] 12.4.2.4 Locales in Unicode](#).


## B.5 More

If you would like Stata to pause every time the screen fills with results, type `set more on`. This will cause a `—more—` prompt to appear at the bottom of the Results window whenever there is more information to be displayed than can fit on the screen. This happens, for example, when you are listing many observations.

```
. list make mpg
```

	make	mpg
1.	Linc. Continental	12
2.	Linc. Mark V	12
3.	Cad. Deville	14
4.	Cad. Eldorado	14
5.	Linc. Versailles	14
6.	Herc. Cougar	14
7.	Herc. XR-7	14
8.	Peugeot 604	14
9.	Buick Electra	15
10.	Herc. Marquis	15
11.	Buick Riviera	16
12.	Chev. Impala	16
13.	Dodge Magnum	16
14.	Olds Toronado	16
15.	AMC Pacer	17
16.	Audi 5000	17
17.	Dodge St. Regis	17
18.	Volvo 260	17
19.	Buick LeSabre	18
20.	Dodge Diplomat	18

```
—more—
```

If you want to see the next screen of text, you have a few options: press any key, such as the Spacebar; click on the **More** button, ; or click on the `—more—` link at the bottom of the Results window. To see just the next line of text, press *Return*. Pressing *q* will interrupt the command. If you click on the arrow of the **More** button, you can also select the **Run to completion** menu item to let the command completely finish.

## B.6 Memory size considerations

Memory management in Stata is automatic. For details on efficiency tweaks needed by a very few Stata users, look at [\[D\] memory](#).

# C More on Stata for Mac

## Contents

C.1	Using Stata datasets and graphs created on other platforms .....	131
C.2	Exporting a Stata graph to another document .....	131
C.3	Stata and the Notification Manager .....	132
C.4	Stata(console) for Mac .....	132

## C.1 Using Stata datasets and graphs created on other platforms

Stata will open any Stata `.dta` dataset or `.gph` graph file, regardless of the platform on which it was created, even if it was a Windows or Unix system. Also, Stata for Windows and Stata for Unix users can use any files that you create. Remember that `.dta` and `.gph` files are binary files, not text files, so they need no translation; simply copy them over to your hard disk as is.

Files created on other platforms can be directly opened in the Command window; for example, you can load a dataset by typing `use filename` or by double-clicking on the file in the Finder.

## C.2 Exporting a Stata graph to another document

Suppose that you wish to export a Stata graph to a document created by your favorite word processor or presentation application. You have two main choices for exporting graphs: you may copy and paste the graph by using the Clipboard, or you may save the graph in one of several formats and import the graph into the application.

### C.2.1 Exporting the graph by using the Clipboard

The easiest way to export a Stata graph into another application is to use drag and drop. You can select the graph in the Graph window and drag it to the location you would like it in another open application.

You can also export graphs by copying and pasting.

Either create your graph or redisplay an existing graph. To copy it to the Clipboard, right-click on the Graph window, and select **Copy**. Stata will copy the graph in PDF format. This is the native graphics format for macOS. Programs made to edit vector graphics can be used to edit the elements of the graph.

After you have copied the graph to the Clipboard, switch to the application into which you wish to import the graph and paste it. In most applications, this is accomplished by selecting **Edit > Paste**. Some applications require you to first create a bounding box for the image to be placed in. If pasting does not immediately work, see your application's documentation on pasting images from the Clipboard into documents.



## C.2.2 Exporting the graph to a file

Stata can export graphs to several different file formats. If you right-click on a graph, select **Save as...**, and then click on the drop-down menu next to *File format*, you will see that Stata can save in the following file types: Portable Document Format (PDF, `.pdf`), Portable Network Graphics (PNG, `.png`), Scalable Vector Graphics (SVG, `.svg`), Joint Photographic Experts Group (JPEG, `.jpg`), Graphics Interchange Format (GIF, `.gif`), Enhanced PostScript (EPS, `.eps`) with or without a TIFF Preview, PostScript (PS, `.ps`), and Tag Image File Format (TIFF, `.tif`). PDF, SVG, EPS, and PS are vector formats, whereas PNG JPEG, GIF, and TIFF are bitmap formats. If you wish to include a thumbnail of the graph with an EPS file, choose **EPS with TIFF Preview (\*.eps)**. Choosing the preview option does not affect how the graph is printed. PNG and SVG are well suited for placing graphs on a webpage. See [G-2] [graph export](#) for more information.

## C.3 Stata and the Notification Manager

You may work in another application while Stata is processing a time-intensive command or do-file. Stata will notify you when it has finished by playing a sound and bouncing its application icon on the Dock. The default notification behavior is for Stata to bounce its application icon on the Dock once. The notification feature works only if Stata is put into the background while it is executing a command or do-file. Stata will not notify you if it is in the foreground or requires further interaction from you (such as a `more` condition). You can control how notifications work in Stata's preferences.

## C.4 Stata(console) for Mac

### C.4.1 Requirements

Stata(console) is included with both Stata/SE and Stata/MP for the Mac. It runs in a Terminal window without a graphical user interface (GUI)—there are no Data Editor, Viewer, or Graph windows. Graphs and datasets can be saved, as usual, they simply cannot be viewed interactively. Stata(console) is meant for running Stata remotely and for running batch jobs in the background.

You can also run background jobs by using your standard Stata installation. The command line options are given in [GSM] [B.3 Stata batch mode](#).

You must already have Stata/SE or Stata/MP for the Mac installed and your license initialized before installing Stata(console). If you have a single-user license and wish to have more than one login ID use Stata at a time, please contact our sales department to purchase an upgrade to a multiuser license. You should have some experience in working from a shell in Unix before attempting to set up Stata(console). You must also have administrator access to your computer to complete the setup. With administrator access, there is always the potential damaging your computer.

In the instructions that follow, use `stata-mp` in place of `stata-se` if you are installing the console version of Stata/MP.

## C.4.2 Installing Stata(console) using the Terminal utility

If you have installed Stata in its default location `/Applications/Stata`, Stata(console) can be installed by selecting **Stata > Install Terminal Utility...** You can then start the console version by typing `stata-se` or `stata-mp` in a Terminal window.

If you rename Stata's folder or move it out of the Applications folder after installing the utility, the symbolic link to the console application will be broken. In this case, just reinstall the utility by selecting **Stata > Install Terminal Utility...** again.

## C.4.3 Installing Stata(console) by hand

If you would rather install Stata(console) by hand instead of using the built-in utility, read this section. If you are not comfortable with Unix or are wary of damaging your computer, skip the rest of this section. If you do not know when to use

```
setenv PATH /Applications/Stata:$PATH
```

and when to use

```
PATH=/Applications/Stata:$PATH
```

you should not attempt the installation.

1. Log in to your Mac with an account that has administrator privileges.
2. Install Stata/SE or Stata/MP in `/Applications/Stata` and initialize your license if Stata is not already installed.

You have completed the installation process. We now wish to verify that everything is installed properly as a regular user. To use Stata as a regular user, your path must include `/Applications/Stata/StataSE.app/Contents/MacOS`. For a quick test, we are going to be crude.

```
mymac: > export PATH=$PATH:/Applications/Stata/StataSE.app/Contents/MacOS
```

```
mymac: > stata-se
```

Stata should come up. Once you have verified that everything is working, make sure that your users modify their shell startup script to include `/Applications/Stata/StataSE.app/Contents/MacOS` in their path. If they do not have a `.bash_profile` file already, they should make one and include the following line:

```
export PATH=$PATH:/Applications/Stata/StataSE.app/Contents/MacOS
```

## C.4.4 Updating Stata(console) in the future

Stata(console) is automatically updated when the regular Stata(GUI) application is updated. All updating should be performed from within Stata(GUI).

# Subject index

This is the subject index for the *Getting Started with Stata for Mac* manual. Readers may also want to consult the [combined subject index](#) (and the [combined author index](#)) in the *Glossary and Index*.

## A

`ado` command, 36  
arithmetic operators, see [operators, arithmetic](#)  
automatic update checking, see [updates, automatic update checking](#)

## B

batch mode, 127–129  
blog, see [Stata Blog](#)  
bouncing dock icon, see [Notification Manager](#)  
Break button, see [button, Break](#)  
`browse` command, 2, 6, 61  
button,

- Break, 25, 84
- Clear more condition, 25, 130
- Data Browser, 2, 47
- Data Editor, 49
- Data Editor (Browse), 25
- Data Editor (Edit), 25, 47
- Do, see [button, Execute \(do\)](#)
- Do-file Editor, 25, 96
- Execute (do), 95, 97, 100
- Execute Quietly (run), 100
- Graph, 17, 25
- Graph Editor, 103
- Log, 23, 25, 107
- Open, 25
- Reset, 19
- Run, see [button, Execute \(do\)](#)
- Save, 25
- Search Help, 26
- Show file in Viewer, 100
- Viewer, 25, 33

`by()` option, 14, 18  
`by` prefix, 13, 15, 22  
`by/if/in` tab, 7, 13, 15, 30

## C

`cd` command, 32  
`clear` command, 92  
clear more condition, see [more condition](#)  
`cmdlog` command, 110  
`codebook` command, 4–6, 39  
command history, 26  
command syntax, 22–23  
Command window, 24, 26

commands,  
    compared with menus, 22  
    downloading and installing, 119–121  
    learning, 31, 113–115  
    uninstalling, 122  
    updating, 122

comments, see [log files, commenting](#)  
contextual menu, 24

- Graph window, 103
- History window, 28
- Variables window, 27
- Viewer window, 35

**Control**-click, see [right-clicking with one-button mouse copying](#),

- data, see [data, copying](#)
- graphs, see [graphs, copying](#)

`correlate` command, 15  
creating variables, see [variables, creating](#)

## D

data,  
    copying, 53, 65  
        tips, 54  
    entering, 49–54  
    graphing, 16–21  
    importing, see [importing data](#)  
    labeling, 70–75  
    listing, 76–84  
    pasting, 53, 65  
    sorting, 54  
    strings, 51  
Data Editor, 2, 47–61  
    attach value labels, 55  
    browse mode, 61  
        toolbar button, 25  
    cell navigation, 51  
    color coding, 2, 50  
    contextual menus, 48  
    create value labels, 55  
    creating variables, 56  
    cursor location box, 49–51, 54  
    date  
        editing, 58–59  
        formats, 58  
        mask, 58–59  
    edit mode toolbar button, 25  
    edit within cell, 51  
    empty columns, 50  
    empty rows, 50  
    enter data by column, 50  
    enter data by row, 49  
    entering data, 49–54  
    filtering, 9, 60  
    fonts, 111  
    hiding variables, 60  
    limiting exposure, 59–61

- Data Editor, *continued*
    - menu, 54–61
    - movement, 48–49
    - opening, 49
    - reordering variables, 60
    - right-clicking, 48
    - searching, 54
    - snapshots, 56–57
    - sorting, 48, 54
    - tips, 59, 68
    - toolbar, 47
    - value labels, 55
    - when to browse, 59
  - data management, 2–8
  - data type, see *variables, data type*
  - dataset, 4
    - changing, 54–61
    - notes, 3
    - opening, 45, 131
    - saving, 45
    - saving in old format, 46
    - structure, 2, 3
  - dates, editing, see *Data Editor, date editing*
  - db command, 31
  - dBASE, 69
  - decode command, 85
  - deleting variables, see *variables, dropping*
  - describe command, 3, 70–75
    - with `short` option, 49
  - descriptive statistics, 8–16
  - destring command, 85
  - dialogs, 29–31
    - accessing from Command window, 31
    - Cancel button, 31
    - Copy button, 31
    - Help button, 31
    - OK button, 31
    - Reset button, 31
    - saving commands, 100
    - Submit button, 31
    - Variables* field, 5, 7
  - directory, working, see *working directory*
  - disclosure control, 28
  - display format, see *variables, display format*
  - displaying graphs, see *graphs, schemes*
  - Do,
    - button, see *button, Execute (do)*
    - menu item, 100
  - do-file, 96–98, 100, 110, 126
    - editing, see *Do-file Editor*
    - tips, 97
    - troubleshooting, 97–98
  - Do-file Editor, 95–100
    - balancing braces, 99–100
    - buttons, 95
    - changing case, 99
    - editing help files, 100
  - Do-file Editor, *continued*
    - editing tools, 99
    - fonts, 111
    - getting History window contents, 29
    - inserting a file, 99
    - matching parentheses, 99
    - split window, 100
    - syntax highlighting, 96
    - toolbar button, 25
    - Tools menu
      - Show file in Viewer, 100
  - drop command, 92–93
  - dropping variables, see *variables, dropping*
  - dummy variable, see *indicator variable*
  - dynamic documents, 114
  - dyndoc command, 96
- ## E
- edit command, 60
  - editing data, see *Data Editor*
  - editing dates, see *Data Editor, date editing*
  - editing do-file, see *Do-file Editor*
  - egen command, 85
  - Encapsulated Postscript, see *EPS*
  - encode command, 85
  - EPS, 132
  - equality, 12–13, 80
  - examples,
    - dialogs, 4, 5, 7, 8, 10, 11, 13–17, 19, 30, 102
    - graphs, 16–21, 102, 104
    - help, 37–40
    - if qualifier, 6, 7, 12, 60–61, 78–81, 93–94
    - in qualifier, 82
    - menus, 1, 3–5, 7, 8, 10, 11, 13–17, 19, 30–31, 102
    - varlist*, 60, 76–78
  - Excel, see *import excel* command
  - exp.* see *expressions*
  - expressions, 78, 85
- ## F
- Facebook, 113, 116
  - Federal Reserve Economic Data, 69
  - filenames, quotes, 45
  - files, double-clicking, 127
  - fitted values, see *predict* command
  - fonts,
    - changing in graphs, see *graphs, schemes*
    - changing in one graph, see *Graph Editor*
    - changing in windows, see *preferences, font*
    - preferences, see *preferences, font*
  - functions, 85

## G

**generate** command, 18, 19, 21, 86–91  
 tips, 89  
 troubleshooting, 88

generating variables, see [variables, creating](#)

Google+, 113

Graph Editor, 104–106  
 abilities, 105  
 closing, see [Graph Editor, stopping](#)  
 contextual toolbar, 104–105  
 experimentation, 105  
 Grid edit tool, 105  
 Object Browser, 105  
 recording, 105  
 starting, 104  
 stopping, 105  
 tools, 105  
 Undo button, 105

graph setup, see [graphs, schemes](#)

Graph window, 17, 103  
 contextual menu, 103  
 right-clicking, 103–104  
 toolbar button, 25

Graphical User Interface, see [GUI](#)

graphs,  
 copy and paste, 131  
 copying, 103  
 drag and drop, 131  
 editing, see [Graph Editor](#)  
 examples, see [examples, graphs](#)  
 export formats, 132  
 exporting, 131  
 opening, 131  
 overlaid, 19–21  
 printing, 21, 103  
 renaming, 103  
 right-clicking, 103  
 saving, 103  
 schemes, 111  
 subgraphs, 17

GUI, 24–32

## H

Haver Analytics databases, 69

**help** command, 41

help for *command*, 36

help system, 37–44  
 FAQs, 37  
 links, 39  
 menu, 37  
 search dialog, 37  
 searching, 37–44, 119–120  
 tips, 41  
 videos, 37, 42

History window, 24, 28–29  
 contextual menu, 28  
 hiding errors, 28  
 reusing commands, 28, 56  
 right-click, 28, 110  
 saving contents, 29  
 sending contents to Do-file Editor, 29  
 tip, 110

hypothesis testing, 14

## I

identifier variable, 5

if qualifier, 6, 7, 12–13, 22, 76, 78–81, 87, 92  
 troubleshooting, 80–81

**import dbase** command, 69

**import delimited** command, 66–68

**import excel** command, 66, 68

**import fred** command, 69

**import haver** command, 69

**import sas** command, 66, 68

**import sasxport** command, 66

**import sasxport5** command, 68, 69

**import sasxport8** command, 68, 69

**import spss** command, 66, 68

importing data, 65–69  
 comma-delimited, see [import delimited command](#)  
 copying and pasting, 54, 65, 68, 69  
 ODBC, see [ODBC](#)  
 paste special, 54  
 tips, 68

in qualifier, 22, 76, 82, 92

indicator variable, 5, 18, 89  
 generating, 86

**infile** command, 66, 69

**infix** command, 66, 69

installation, minimum OS requirement, 125

Internet, 117–123  
 installing programs, see [commands, downloading and installing](#)  
 resources, 113–116  
 searching, 119–120  
 using remote files, 117

## J

JPEG, 132

## K

**keep** command, 92, 94

## L

**label** command, 72

**label data** command, 72

**label define** command, 73, 75

label values command, 72, 75  
 label variable command, 21, 72  
 labels,  
   data, 3, 72–73  
   value, 2, 4–5, 10, 13, 72, 74–75  
     confusing with string variable, 81  
     why needed, 6  
   variable, 3–5, 72  
 line, *twoway* subcommand, 20  
 linear regression, see regression, linear  
 list command, 7, 67, 76–84  
 listing data, see data, listing  
 loading data, see dataset, opening  
 locale, 129  
 Log button, 25  
 log command, 107–109  
 log files, 23, 107–110  
   appending, 107  
   commenting, 108  
   contents, 108  
   keeping just commands, 110  
   multiple open at once, 108  
   overwriting, 107  
   plain text, 107, 109  
   printing, 109  
   rerunning commands, 110  
   SMCL, 107, 109  
   starting, 107  
   tips, 109  
   translating formats, 107, 109  
   types, 109  
   viewing, 109  
 logical  
   expression, 78–80  
   operators, see operators, logical

## M

Markdown, 96  
 median, 9  
 memory, 6, 45, 71, 130  
   allocation, 130  
 menus, 29  
   compared with commands, 22  
   examples, see examples, menus  
 missing() function, 7, 61, 79  
 missing values, 2, 4, 7, 11, 50, 51, 55, 78–79, 86–87, 91  
   extended, 55  
 Mission Control, 24  
 more condition, 25, 130

## N

net command, 36  
 NetCourses, see Stata NetCourses  
 Not Elsewhere Classified, see Stata Blog

notes,  
   managing, 63–64  
   timestamps, 64  
 Notification Manager, 132  
*numlist*, 82

## O

observations, 2  
 ODBC, 69  
 odbc command, 66, 69  
 one-way table, see table, one-way  
 Open toolbar button, 25  
 opening a dataset, see dataset, opening  
 operators,  
   arithmetic, 85  
   logical, 78, 80, 85  
   relational, 78, 85  
   string, 91  
 options, 8, 22, 40, 76, 82  
 output, printing and saving, see log files

## P

pasting,  
   data, see data, pasting  
   graphs, see graphs, copy and paste  
 PDF, 109, 131–132  
 PDF documentation, 37, 39, 41  
 PNG, 132  
 poisson command, 30  
 Portable Document Format, see PDF  
 Portable Network Graphics, see PNG  
 postestimation commands, 19  
 precision, 71  
 predict command, 19  
 preferences, 111–112  
   Clipboard, 111  
   deleting, 125  
   font, 111–112  
   Graph window, 111  
   loading, 112  
   managing, 112  
   saving, 112  
   window, 111–112  
 prefix command, 13, 22  
 printing  
   contents of Viewer, 35  
   graphs, 103  
   output, 109  
 profile.do, 126  
 Project Manager, 98, 101  
 projects, 101  
 Properties window, 24, 51  
   hiding, 28  
   revealing, 28  
 python, 96

## R

reading list, see *Stata reading list*  
 recording sessions, see *log files*  
 reference manuals, 41  
**regress** command, 19, 22  
 regression,  
   linear, 18–22, 98  
   Poisson, 30  
 relational operators, see *operators, relational*  
**replace** command, 85–89  
 reproducible research, 114  
 Results window, 1, 17, 24, 26  
   color scheme, 111  
   fonts, 111  
   searching, 26  
 right-clicking with one-button mouse, 24  
 Run button, see *button, Execute (do)*

## S

sample session, 1–23  
 SAS, see *import sas* command  
 save, 47  
**save** command, 32, 45–46  
 Save toolbar button, 25  
**saveold** command, 46  
 saving  
   data, see *dataset, saving*  
   output, see *log files*  
**scatter**, *twoway* subcommand, 16–18, 20  
**search** command, 36, 41  
 Search Help button, see *button, Search Help*  
 searching help system, see *help system, searching*  
**set more** command, 130  
 Show file in Viewer button, see *button, Show file in Viewer*  
 Sidebar, 26  
 SMCL, 34, 100, 107  
 SPSS, see *import spss* command  
 Stata  
   batch mode, 127–129  
   Blog, 113, 116  
   Bookstore, 114  
   console, 132–133  
   datasets available, 113, 117  
   executing commands at startup, 126  
   FAQs, 113  
   Graph Editor, see *Graph Editor*  
   learning more, 113–116  
   Markup and Control Language, see *SMCL*  
   NetCourses, 114, 116  
   output, 1  
   Press, 116  
   public training courses, 114  
   reading list, 114–115  
   running in Terminal, see *Stata, console*  
   starts with an error, see *troubleshooting*

*Stata, continued*  
   startup options, 127  
   Statalist, 113  
   training, 114, 116  
   troubleshooting, see *troubleshooting*  
   updating, see *updates*  
   user interface, see *GUI*  
   videos, 42, 114  
   webinars, 114  
   won't start, see *troubleshooting*  
   working directory, see *working directory*  
*Stata Journal*, 37–38, 42–44, 113, 116, 117  
*Stata News*, 116  
 status bar, 32  
 storage type, see *variables, data type*  
 string variable, see *variables, string*  
 strings, 90–91  
   quoting, 81  
**summarize** command, 4, 8, 12–13, 22  
 SVG, 132  
 syntax, 39, 76–83  
   abbreviations, 76  
   diagram, 22  
   list command, 76  
 syntax note, 2, 5, 7–15, 17–18, 22  
**sysprofile.do**, 127  
**sysuse** command, 1

## T

table,  
   one-way, 10–11, 13–14  
   two-way, 11–12  
 tabs, 29  
**tabulate** command, 10–14  
 text variables, see *variables, string*  
 TIFF, 132  
 toolbar, main, 25–26  
 tooltip, 25  
**tostring** command, 85  
 training, see *Stata training*  
 troubleshooting, 124–125  
   preferences, 125  
   updates, see *updates, troubleshooting*  
**ttest** command, 14  
 Twitter, 113, 116  
**twoway line** command, 20  
**twoway scatter** command, 16–18, 20  
 two-way table, see *table, two-way*  
 type command, 36

## U

Unicode, 91  
**update** command, 36  
 updates, 36, 118  
   automatic update checking, 118  
   troubleshooting, 118

use command, 45

*User's Guide*, 113

ustrpos() function, 91

ustrsubstr() function, 91

## V

value labels, creating and managing, 55

variables, 2

allowable names, 52

creating, 56, 85–91

data type, 3, 5–6, 71, 86

display format, 4, 71

dropping, 27, 63, 92–93

formatting, 51

generating, see [variables, creating](#)

keeping, 27, 63

missing values, see [missing values](#)

name, 3, 71

abbreviating, 67, 76–78

autocompletion, 26

naming, 51

renaming, 51

storage type, see [variables, data type](#)

string, 3–5, 90–91

confusing with value labels, 81

Unicode, 71

text, see [variables, string](#)

Variables Manager, 62–64

contextual menus, 63

creating *varlists*, 63

dropping variables, 63

filtering variables, 62

keeping variables, 63

notes, 63–64

printing, 63

restore columns, 63

restore sort order, 62

right-clicking, 63

Variable pane, 62–63

Variable Properties pane, 63

Variables window, 1, 19, 24, 27–28

clicking, 27

columns, 27

contextual menu, 27

filtering, 27

hiding, 28

revealing, 28

*varlist*, 5, 22, 76, 92

videos, see [Stata videos](#)

View > Do-file Editor menu, 100

Execute (do), 100

Execute (do) to bottom, 100

Execute (include), 100

Execute quietly (run), 100

view command, 36

Viewer, 33–36

Also see [button](#), 39

buttons, 33

color scheme, 111

commands, 36

contextual menu, 35

Dialog button, 39

Find bar, 34

fonts, 111

Jump to button, 39

links

clicking, 34

middle-clicking, 34

*Shift*-clicking, 34

log files, 109

navigating, 35

new window, 34

opening, 33

preferences, 35

printing, 35

printing log files, 109

right-clicking, 35

selecting one Viewer, 34

toolbar button, 25, 33

viewing

current log, 35

logs, 34

remote files, 35

text files, 34

## W

webinars, see [Stata videos](#)

windows, 24–25

closing, 112

cycle, 24

opening, 112

revealing, 24

working directory, 32

## Y

YouTube videos, see [Stata videos](#)